

Safety Data Sheet



Section 1: Identification

Product identifier

Product Name • Reno Gun Abrade 60 Z-10
Product Code • 126200

Relevant identified uses of the substance or mixture and uses advised against

Recommended use • Refractory applications

Details of the supplier of the safety data sheet

Manufacturer • Reno Refractories, Inc.
P O Box 201
Morris, AL 35116
United States
www.renorefractories.com
sales@renorefractories.com

Telephone (General) • 205-647-0240

Emergency telephone number

Manufacturer • 1-800-262-8200 - CHEMTREC

Section 2: Hazard Identification

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012 • Skin Irritation 2
Serious Eye Damage 1
Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation
Carcinogenicity 1A
Specific Target Organ Toxicity Repeated Exposure 1

Label elements

OSHA HCS 2012

DANGER



Hazard statements • Causes skin irritation
Causes serious eye damage
May cause respiratory irritation
May cause cancer.

Causes damage to organs through prolonged or repeated exposure

Precautionary statements

- Prevention** • Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

- Response** • IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Call a POISON CENTER or doctor/physician if you feel unwell.
If on skin: Wash with plenty of water.
Take off contaminated clothing and wash before reuse.
If skin irritation occurs: Get medical advice/attention.
Specific treatment, see supplemental first aid information.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Get medical advice/attention if you feel unwell.

- Storage/Disposal** • Store in a well-ventilated place. Keep container tightly closed.
Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Other hazards

OSHA HCS 2012

- Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada

According to: WHMIS

Classification of the substance or mixture

- WHMIS
- Other Toxic Effects - D2A
 - Corrosive - E

Label elements

WHMIS



WHMIS

- Other Toxic Effects - D2A
- Corrosive - E

Other hazards

WHMIS

- In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients

Substances

- Material does not meet the criteria of a substance.

Mixtures

Composition					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments
Mullite	CAS:1302-93-8	41.02% TO 50.18%	NDA	OSHA HCS 2012: STOT RE 2 (Lungs)	NDA
Aluminum oxide	CAS:1344-28-1	3.785% TO 15.6%	NDA	OSHA HCS 2012: Not Classified	NDA
Silica, amorphous	CAS:7631-86-9	10.98% TO 14.02%	NDA	OSHA HCS 2012: Not Classified	NDA
Cement, alumina, chemicals	CAS:65997-16-2	1.6% TO 8%	NDA	OSHA HCS 2012: Not Classified	NDA
Calcium aluminate	Proprietary	2% TO 8%	NDA	OSHA HCS 2012: Eye Dam. 1; Skin Irrit. 2; STOT SE 3: Resp. Irrit.	NDA
Zirconium(IV) silicate (1:1)	CAS:14940-68-2	2.94% TO 7%	NDA	OSHA HCS 2012: Not Classified	NDA
Zirconium	CAS:7440-67-7	2.8% TO 6.65%	NDA	OSHA HCS 2012: WHMIS:	NDA
Aluminum(III) silicate (2:1)	CAS:1302-76-7	2.55% TO 6.65%	NDA	OSHA HCS 2012: STOT RE 2 (Lungs)	NDA
Amorphous silica fume	CAS:69012-64-2	1.8% TO 5%	NDA	OSHA HCS 2012: STOT RE 1 (Lungs)	NDA
Zirconium oxide	CAS:1314-23-4	0.21% TO 4.4%	NDA	OSHA HCS 2012: WHMIS:	NDA
Cristobalite	CAS:14464-46-1	< 3.172%	NDA	OSHA HCS 2012: Carc. 1A	NDA
Amorphous/fused silica	CAS:60676-86-0	0.21% TO 2.13%	NDA	OSHA HCS 2012: Not Classified	NDA
Clay	Proprietary	0.9% TO 1.5%	NDA	OSHA HCS 2012: WHMIS: Other Toxic Effects - D2A	NDA
Quartz	CAS:14808-60-7	< 1%	NDA	OSHA HCS 2012: Carc. 1A; STOT RE 1 (Lungs)	NDA
Titanium dioxide	CAS:13463-67-7	< 0.645%	NDA	OSHA HCS 2012: Carc. 2	NDA
Iron oxide	CAS:1309-37-1	< 0.375%	NDA	OSHA HCS 2012: Not Classified	NDA
Sodium hydroxide	CAS:1310-73-2	0.07% TO 0.37%	NDA	OSHA HCS 2012: Exposure limit(s)	NDA
Hafnium oxide	CAS:12055-23-1	< 0.11%	NDA	OSHA HCS 2012: WHMIS:	NDA
Magnesium oxide	CAS:1309-48-4	< 0.048%	NDA	OSHA HCS 2012: Exposure limit(s)	NDA
Calcium oxide	CAS:1305-78-8	< 0.016%	NDA	OSHA HCS 2012: Exposure limit(s)	NDA
Silica, crystalline - tridymite	CAS:15468-32-3	0% TO 0.015%	NDA	OSHA HCS 2012: WHMIS: Other Toxic Effects - D2B	NDA
Various Metal Oxides	NDA	0% TO 0.0033%	NDA	OSHA HCS 2012: Not Classified	NDA

Section 4: First-Aid Measures

Description of first aid measures

Inhalation

- Move victim to fresh air. Give artificial respiration if victim is not breathing. Administer oxygen if breathing is difficult. Get medical attention immediately.

Skin

- In case of contact with substance, immediately flush skin with running water for at

- least 20 minutes. If skin irritation occurs: Get medical advice/attention.
- Eye**
- In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.
- Ingestion**
- Rinse mouth. Do not give anything by mouth to an unconscious person. Get medical attention immediately.

Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

- Notes to Physician**
- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to material other than this product may have occurred.

Section 5: Fire-Fighting Measures

Extinguishing media

- Suitable Extinguishing Media**
- Material is non-combustible. In case of fire use media as appropriate for surrounding fire.

- Unsuitable Extinguishing Media**
- None known.

Special hazards arising from the substance or mixture

- Unusual Fire and Explosion Hazards**
- None known.

- Hazardous Combustion Products**
- None known.

Advice for firefighters

- Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection. Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

- Personal Precautions**
- Isolate hazard area and deny entry to unauthorized and/or unprotected personnel. Do not touch or walk through spilled material. Ensure adequate ventilation to remove vapors, fumes, dust etc.

- Emergency Procedures**
- Ventilate closed spaces before entering. Isolate hazard area and deny entry to unauthorized and/or unprotected personnel.

Environmental precautions

- No specific actions or treatments recommended related to exposure to this material.

Methods and material for containment and cleaning up

- Containment/Clean-up Measures**
- Avoid generating dust.
FOR SMALL SPILLS: Clean with a vacuum with a filtration system sufficient to remove and prevent recirculation of crystalline silica (a vacuum equipped with a high-efficiency particulate air (HEPA) filter is recommended).
FOR LARGE SPILLS: Use a fine spray or mist to control dust creation and carefully scoop or shovel into clean dry container for later reuse or disposal.
If, an appropriate vacuum is unavailable, only wet-clean-up methods should be used (i.e. misting). Moisture should be added as necessary to reduce exposure to airborne respirable silica dust.

Section 7 - Handling and Storage

Precautions for safe handling

Handling

- Do not breathe dust. Avoid contact with skin, eyes, and clothing. Minimize dust generation and accumulation. Use good safety and industrial hygiene practices. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Wear long sleeves and/or protective coveralls. Contaminated clothing must be vacuumed before removal. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Wash thoroughly after handling. Do not use in areas without adequate ventilation.

Conditions for safe storage, including any incompatibilities

Storage

- Store in a covered location. Keep container closed. Keep from freezing. Storage and work area should be periodically cleaned to minimize dust accumulation.

Section 8 - Exposure Controls/Personal Protection

Control parameters

Exposure Limits/Guidelines						
	Result	ACGIH	Canada Ontario	Canada Quebec	Mexico	NIOSH
Calcium oxide (1305-78-8)	TWAs	2 mg/m3 TWA	2 mg/m3 TWA	2 mg/m3 TWAEV	2 mg/m3 TWA LMPE-PPT	2 mg/m3 TWA
Magnesium oxide (1309-48-4)	TWAs	10 mg/m3 TWA (inhalable fraction)	10 mg/m3 TWA (inhalable)	10 mg/m3 TWAEV (fume, as Mg)	10 mg/m3 TWA LMPE-PPT (fume, as Mg)	Not established
Sodium hydroxide (1310-73-2)	Ceilings	2 mg/m3 Ceiling	2 mg/m3 Ceiling	2 mg/m3 Ceiling	2 mg/m3 Ceiling	2 mg/m3 Ceiling
Amorphous/fused silica (60676-86-0)	TWAs	Not established	0.1 mg/m3 TWA (respirable)	0.1 mg/m3 TWAEV (containing no Asbestos and <1% Crystalline silica, respirable dust)	0.1 mg/m3 TWA LMPE-PPT; 10 mg/m3 TWA LMPE-PPT (inhalable particulate); 3 mg/m3 TWA LMPE-PPT (respirable particulate)	Not established
Iron oxide (1309-37-1)	STELs	Not established	Not established	Not established	10 mg/m3 STEL [LMPE-CT] (as Fe)	Not established
	TWAs	5 mg/m3 TWA (respirable fraction)	5 mg/m3 TWA (respirable)	5 mg/m3 TWAEV (dust and fume, as Fe); 10 mg/m3 TWAEV (containing no Asbestos and <1% Crystalline silica, regulated under Rouge, total dust)	5 mg/m3 TWA LMPE-PPT	5 mg/m3 TWA (dust and fume, as Fe)
Titanium dioxide (13463-67-7)	STELs	Not established	Not established	Not established	20 mg/m3 STEL [LMPE-CT] (as Ti)	Not established
	TWAs	10 mg/m3 TWA	10 mg/m3 TWA	10 mg/m3 TWAEV (containing no Asbestos and <1% Crystalline silica, total dust)	10 mg/m3 TWA LMPE-PPT (as Ti)	Not established
			0.10 mg/m3 TWA			

Quartz (14808-60-7)	TWAs	0.025 mg/m3 TWA (respirable fraction)	(designated substances regulation, respirable, listed under Silica, crystalline)	0.1 mg/m3 TWAEV (respirable dust)	0.1 mg/m3 TWA LMPE-PPT (respirable fraction)	0.05 mg/m3 TWA (respirable dust)
Amorphous silica fume (69012-64-2)	TWAs	Not established	2 mg/m3 TWA (respirable, listed under Silica fume)	2 mg/m3 TWAEV (containing no Asbestos and <1% Crystalline silica, respirable dust)	2 mg/m3 TWA LMPE-PPT; 10 mg/m3 TWA LMPE-PPT (inhalable particulate); 3 mg/m3 TWA LMPE-PPT (respirable particulate)	Not established
Cristobalite (14464-46-1)	TWAs	0.025 mg/m3 TWA (respirable fraction)	0.05 mg/m3 TWA (designated substances regulation, respirable, listed under Silica, crystalline)	0.05 mg/m3 TWAEV (respirable dust)	0.05 mg/m3 TWA LMPE-PPT (respirable fraction)	0.05 mg/m3 TWA (respirable dust)
Aluminum oxide (1344-28-1)	TWAs	Not established	Not established	10 mg/m3 TWAEV (containing no Asbestos and <1% Crystalline silica, total dust, as Al)	10 mg/m3 TWA LMPE-PPT	Not established
Silica, amorphous (7631-86-9)	TWAs	Not established	Not established	Not established	Not established	6 mg/m3 TWA

Exposure Limits/Guidelines (Con't.)

	Result	OSHA
Calcium oxide (1305-78-8)	TWAs	5 mg/m3 TWA
Magnesium oxide (1309-48-4)	TWAs	15 mg/m3 TWA (fume, total particulate)
Sodium hydroxide (1310-73-2)	TWAs	2 mg/m3 TWA
Iron oxide (1309-37-1)	TWAs	10 mg/m3 TWA (fume); 15 mg/m3 TWA (total dust, listed under Rouge); 5 mg/m3 TWA (respirable fraction, listed under Rouge)
Titanium dioxide (13463-67-7)	TWAs	15 mg/m3 TWA (total dust)
Aluminum oxide (1344-28-1)	TWAs	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)

Exposure controls

Engineering Measures/Controls

- Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Ensure that dust handling systems (such as exhaust ducts, dust collectors, vessels and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is not leakage from the equipment). Collection systems must be designed and maintained to prevent the accumulation and recirculation of respirable silica into the workplace.

Personal Protective Equipment

Respiratory

- For limited exposure use an N95 dust mask. For prolonged exposure use an air-purifying respirator with high efficiency particulate air (HEPA) filters. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a

NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

- Eye/Face** • Wear protective eyewear (goggles, face shield, or safety glasses).
- Hands** • Wear appropriate gloves.
- Skin/Body** • Wear long sleeves and/or protective coveralls.
- General Industrial Hygiene Considerations** • Avoid breathing dust. Avoid contact with skin, eyes or clothing. Do not remove dusts from clothing by blowing or shaking. Do not eat, drink or smoke during work. Wash hands before eating, drinking, or smoking. Wash thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice.
- Environmental Exposure Controls** • Follow best practice for site management and disposal of waste. Dispose of in an approved landfill.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene
 NIOSH = National Institute of Occupational Safety and Health
 OSHA = Occupational Safety and Health Administration
 STEL = Short Term Exposure Limits are based on 15-minute exposures
 TWAEV = Time-Weighted Average Exposure Value
 TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description			
Physical Form	Solid	Appearance/Description	Gray granular dry powder with an earthy odor.
Color	Gray	Odor	Earthy
Particulate Size	600 µ	Odor Threshold	No data available
General Properties			
Boiling Point	No data available	Melting Point/Freezing Point	No data available
Decomposition Temperature	No data available	pH	Not relevant
Specific Gravity/Relative Density	2.2 to 2.9 Water=1	Water Solubility	Negligible < 0.1 %
Viscosity	No data available	Explosive Properties	No data available
Oxidizing Properties:	No data available		
Volatility			
Vapor Pressure	No data available	Vapor Density	No data available
Evaporation Rate	No data available	VOC (Wt.)	0 %
Flammability			
Flash Point	Not relevant	UEL	Not relevant
LEL	Not relevant	Autoignition	No data available
Flammability (solid, gas)	No data available		
Environmental			
Octanol/Water Partition coefficient	No data available		

Section 10: Stability and Reactivity

Reactivity

- No dangerous reaction known under conditions of normal use.

Chemical stability

- Stable under normal temperatures and pressures.

Possibility of hazardous reactions

- Hazardous polymerization not indicated.

Conditions to avoid

- None known.

Incompatible materials

- None known.

Hazardous decomposition products

- None known.

Section 11 - Toxicological Information**Information on toxicological effects**

Components		
Silica, amorphous (10.98% TO 14.02%)	7631-86-9	Irritation: Eye-Rabbit • 25 mg 24 Hour(s) • Mild irritation
Titanium dioxide (< 0.645%)	13463-67-7	Irritation: Skin-Human • 300 µg 3 Day(s)-Intermittent • Mild irritation; Tumorigen / Carcinogen: Inhalation-Rat TCl ₀ • 250 mg/m ³ 6 Hour(s) 2 Year(s)-Intermittent; Tumorigenic: Carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration: Tumors
Sodium hydroxide (0.07% TO 0.37%)	1310-73-2	Irritation: Eye-Rabbit • 50 µg 24 Hour(s) • Severe irritation; Skin-Rabbit • 500 mg 24 Hour(s) • Severe irritation

GHS Properties	Classification
Acute toxicity	OSHA HCS 2012 • Data lacking
Skin corrosion/Irritation	OSHA HCS 2012 • Skin Irritation 2
Serious eye damage/Irritation	OSHA HCS 2012 • Serious Eye Damage 1
Skin sensitization	OSHA HCS 2012 • Data lacking
Respiratory sensitization	OSHA HCS 2012 • Data lacking
Aspiration Hazard	OSHA HCS 2012 • Data lacking
Carcinogenicity	OSHA HCS 2012 • Carcinogenicity 1A
Germ Cell Mutagenicity	OSHA HCS 2012 • Data lacking
Toxicity for Reproduction	OSHA HCS 2012 • Data lacking
STOT-SE	OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation
STOT-RE	OSHA HCS 2012 • Specific Target Organ Toxicity Repeated Exposure 1

Target Organs

- Lungs

Route(s) of entry/exposure

- Inhalation, Skin, Eye, Ingestion

Medical Conditions

- Any pre-existing conditions of the lungs. Disorders of the lungs.

Aggravated by Exposure**Potential Health Effects****Inhalation****Acute (Immediate)**

- May cause respiratory irritation. Exposure to dust may cause irritation.

Chronic (Delayed)

- Chronic overexposure to dust containing respirable sized crystalline silica can cause delayed lung injury (silicosis). Inhalation of dust containing crystalline silica pulmonary

diseases such as asthma and lung disorder associated with smoking.

Skin

- Acute (Immediate)**
 - Causes skin irritation. Exposure to dust may cause irritation.
- Chronic (Delayed)**
 - No data available.

Eye

- Acute (Immediate)**
 - Causes serious eye damage. Excessive concentrations of nuisance dust in the workplace may reduce visibility and may cause unpleasant deposits in eyes.
- Chronic (Delayed)**
 - No data available.

Ingestion

- Acute (Immediate)**
 - Excessive concentrations of nuisance dust in the workplace may cause mechanical irritation to mucous membranes.
- Chronic (Delayed)**
 - No data available.

Carcinogenic Effects

- May cause cancer. IARC studies have shown sufficient evidence from animal studies to categorize crystalline silica as a group 1 carcinogen.

Carcinogenic Effects			
	CAS	IARC	NTP
Titanium dioxide	13463-67-7	Group 2B-Possible Carcinogen	Not Listed
Quartz	14808-60-7	Group 1-Carcinogenic	Known Human Carcinogen
Cristobalite	14464-46-1	Group 1-Carcinogenic	Not Listed

Key to abbreviations

- MLD = Mild
- SEV = Severe
- TC = Toxic Concentration
- TD = Toxic Dose

Section 12 - Ecological Information

Toxicity

- Material data lacking.

Persistence and degradability

- Material data lacking.

Bioaccumulative potential

- Material data lacking.

Mobility in Soil

- Material data lacking.

Other adverse effects

- No studies have been found.

Section 13 - Disposal Considerations

Waste treatment methods

Product waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class (es)	Packing group	Environmental hazards
DOT	NDA	Not Regulated	NDA	NDA	NDA
TDG	NDA	Not Regulated	NDA	NDA	NDA
IATA/ICAO	NDA	Not Regulated	NDA	NDA	NDA

Special precautions for user • None specified.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code • No data available

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute, Chronic

State Right To Know				
Component	CAS	MA	NJ	PA
Aluminum oxide	1344-28-1	Yes	Yes	Yes
Clay	<i>Proprietary</i>	No	No	No
Calcium oxide	1305-78-8	Yes	Yes	Yes
Cristobalite	14464-46-1	Yes	Yes	Yes
Hafnium oxide	12055-23-1	No	No	No
Iron oxide	1309-37-1	Yes	Yes	Yes
Quartz	14808-60-7	Yes	Yes	Yes
Silica, amorphous	7631-86-9	Yes	Yes	Yes
Silica, crystalline - tridymite	15468-32-3	Yes	Yes	Yes
Sodium aluminate	1302-42-7	No	No	No
Sodium hydroxide	1310-73-2	Yes	Yes	Yes
Titanium dioxide	13463-67-7	Yes	Yes	Yes
Zirconium	7440-67-7	Yes	Yes	Yes
Zirconium oxide	1314-23-4	Yes	No	No
Zirconium(IV) silicate (1:1)	14940-68-2	No	No	No

Inventory			
Component	CAS	Canada DSL	TSCA
Aluminum oxide	1344-28-1	Yes	Yes
Clay	<i>Proprietary</i>	Yes	Yes
Calcium oxide	1305-78-8	Yes	Yes
Cristobalite	14464-46-1	Yes	Yes
Hafnium oxide	12055-23-1	Yes	Yes
Iron oxide	1309-37-1	Yes	Yes

Quartz	14808-60-7	Yes	Yes
Silica, amorphous	7631-86-9	Yes	Yes
Silica, crystalline - tridymite	15468-32-3	No	No
Sodium aluminate	1302-42-7	Yes	Yes
Sodium hydroxide	1310-73-2	Yes	Yes
Titanium dioxide	13463-67-7	Yes	Yes
Zirconium	7440-67-7	Yes	Yes
Zirconium oxide	1314-23-4	Yes	Yes
Zirconium(IV) silicate (1:1)	14940-68-2	Yes	Yes

Canada

Labor

Canada - WHMIS - Classifications of Substances

• Zirconium(IV) silicate (1:1)	14940-68-2	Uncontrolled product according to WHMIS classification criteria
• Hafnium oxide	12055-23-1	Not Listed
• Sodium aluminate	1302-42-7	E
• Silica, crystalline - tridymite	15468-32-3	D2A
• Calcium oxide	1305-78-8	E
• Iron oxide	1309-37-1	Uncontrolled product according to WHMIS classification criteria
• Sodium hydroxide	1310-73-2	E (including 0.04% in aqueous solution, 0.08%, 0.4% in aqueous solution, 2%, 2.5%, 4% in aqueous solution, 5%, 10%, 16%, 20%, 40%, 50% in aqueous solution, 8.7N) D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Titanium dioxide, mixture containing on Health Canada's WHMIS Division website.)
• Titanium dioxide	13463-67-7	Uncontrolled product according to WHMIS classification criteria
• Zirconium	7440-67-7	Uncontrolled product according to WHMIS classification criteria
• Aluminum oxide	1344-28-1	Uncontrolled product according to WHMIS classification criteria D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS Division website.)
• Cristobalite	14464-46-1	Uncontrolled product

• Silica, amorphous	7631-86-9	according to WHMIS classification criteria
• Zirconium oxide	1314-23-4	Uncontrolled product according to WHMIS classification criteria D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS Division website.)
• Quartz	14808-60-7	
• Clay	<i>Proprietary</i>	D2A

Canada - WHMIS - Ingredient Disclosure List

• Zirconium(IV) silicate (1:1)	14940-68-2	1 %
• Hafnium oxide	12055-23-1	Not Listed
• Sodium aluminate	1302-42-7	Not Listed
• Silica, crystalline - tridymite	15468-32-3	1 %
• Calcium oxide	1305-78-8	1 %
• Iron oxide	1309-37-1	1 %
• Sodium hydroxide	1310-73-2	1 %
• Titanium dioxide	13463-67-7	Not Listed
• Zirconium	7440-67-7	1 %
• Aluminum oxide	1344-28-1	1 %
• Cristobalite	14464-46-1	1 %
• Silica, amorphous	7631-86-9	1 %
• Zirconium oxide	1314-23-4	Not Listed
• Quartz	14808-60-7	1 %
• Clay	<i>Proprietary</i>	Not Listed

United States

Environment

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

• Zirconium(IV) silicate (1:1)	14940-68-2	Not Listed
• Hafnium oxide	12055-23-1	Not Listed
• Sodium aluminate	1302-42-7	Not Listed
• Silica, crystalline - tridymite	15468-32-3	Not Listed
• Calcium oxide	1305-78-8	Not Listed
• Iron oxide	1309-37-1	Not Listed
• Sodium hydroxide	1310-73-2	1000 lb final RQ; 454 kg final RQ
• Titanium dioxide	13463-67-7	Not Listed
• Zirconium	7440-67-7	Not Listed
• Aluminum oxide	1344-28-1	Not Listed
• Cristobalite	14464-46-1	Not Listed
• Silica, amorphous	7631-86-9	Not Listed
• Zirconium oxide	1314-23-4	Not Listed
• Quartz	14808-60-7	Not Listed
• Clay	<i>Proprietary</i>	Not Listed

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

• Zirconium(IV) silicate (1:1)	14940-68-2	Not Listed
• Hafnium oxide	12055-23-1	Not Listed

• Sodium aluminate	1302-42-7	Not Listed
• Silica, crystalline - tridymite	15468-32-3	Not Listed
• Calcium oxide	1305-78-8	Not Listed
• Iron oxide	1309-37-1	Not Listed
• Sodium hydroxide	1310-73-2	Not Listed
• Titanium dioxide	13463-67-7	Not Listed
• Zirconium	7440-67-7	Not Listed
• Aluminum oxide	1344-28-1	1.0 % de minimis concentration (fibrous forms)
• Cristobalite	14464-46-1	Not Listed
• Silica, amorphous	7631-86-9	Not Listed
• Zirconium oxide	1314-23-4	Not Listed
• Quartz	14808-60-7	Not Listed
• Clay	<i>Proprietary</i>	Not Listed

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

• Zirconium(IV) silicate (1:1)	14940-68-2	Not Listed
• Hafnium oxide	12055-23-1	Not Listed
• Sodium aluminate	1302-42-7	Not Listed
• Silica, crystalline - tridymite	15468-32-3	Not Listed
• Calcium oxide	1305-78-8	Not Listed
• Iron oxide	1309-37-1	Not Listed
• Sodium hydroxide	1310-73-2	Not Listed
• Titanium dioxide	13463-67-7	carcinogen, initial date 9/2/11 (airborne, unbound particles of respirable size)
• Zirconium	7440-67-7	Not Listed
• Aluminum oxide	1344-28-1	Not Listed
• Cristobalite	14464-46-1	Not Listed
• Silica, amorphous	7631-86-9	Not Listed
• Zirconium oxide	1314-23-4	Not Listed
• Quartz	14808-60-7	carcinogen, initial date 10/1/88 (airborne particles of respirable size)
• Clay	<i>Proprietary</i>	Not Listed

United States - Pennsylvania

Labor

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

• Zirconium(IV) silicate (1:1)	14940-68-2	Not Listed
• Hafnium oxide	12055-23-1	Not Listed
• Sodium aluminate	1302-42-7	Not Listed
• Silica, crystalline - tridymite	15468-32-3	Not Listed
• Calcium oxide	1305-78-8	Not Listed
• Iron oxide	1309-37-1	Not Listed
• Sodium hydroxide	1310-73-2	Not Listed
• Titanium dioxide	13463-67-7	Not Listed
• Zirconium	7440-67-7	Not Listed
• Aluminum oxide	1344-28-1	Not Listed
• Cristobalite	14464-46-1	Not Listed
• Silica, amorphous	7631-86-9	Not Listed

• Zirconium oxide	1314-23-4	Not Listed
• Quartz	14808-60-7	Not Listed
• Clay	Proprietary	Not Listed

Other Information

- WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information

Revision Date	<ul style="list-style-type: none">• 27/April/2018
Last Revision Date	<ul style="list-style-type: none">• 05/October/2015
Preparation Date	<ul style="list-style-type: none">• 05/October/2015
Disclaimer/Statement of Liability	<ul style="list-style-type: none">• The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. Reno Refractories MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key to abbreviations

NDA = No data available