Safety Data Sheet



Section 1: Identification

Product identifier							
Product Name •	Reno Lite Gun 24-60						
Product Code •	135550						
Relevant identified uses o	f the substance or mixture and uses advised against						
Recommended use •	Refractory applications						
Details of the supplier of the	he safety data sheet						
Manufacturer •	Reno Refractories, Inc.						
	P O Box 201 Morris, AL 35116 United States www.renorefractories.com sales@renorefractories.com						
Telephone (General) •	205-647-0240						
Emergency telephone number							
Manufacturen							

Manufacturer

• 1-800-262-8200 - CHEMTREC

Section 2: Hazard Identification

United States (US) According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012	Skin Irritation 2 Serious Eve Damage 1
	Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation
	Carcinogenicity 1A
	Specific Target Organ Toxicity Repeated Exposure 1

Label elements OSHA HCS 2012

DANGER



Hazard statements · Causes skin irritation

Causes skin irritation Causes serious eye damage May cause respiratory irritation May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Precautionary statements	
Prevention •	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves, clothing , and eye/face protection , .
Response -	 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. If on skin: Wash with plenty of water . Take off contaminated clothing and wash before reuse. Specific treatment, see supplemental first aid information. If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/attention. Get medical advice/attention.
Storage/Disposal	Store in a well-ventilated place. Keep container tightly closed. Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.
Other hazards	
OSHA HCS 2012	Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.
Canada	

Canada

According to: WHMIS

WHMIS	Other Toxic Effects - D2A Corrosive - E
Label elements	
WHMIS	
WHMIS	Other Toxic Effects - D2A Corrosive - E
Other hazards	
WHMIS	 In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients

Substances

• Material does not meet the criteria of a substance.

Mixtures

Composition						
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments	
Aluminum calcium oxide	CAS: 12042- 68-1	15% TO 35%	NDA	OSHA HCS 2012: Eye Dam. 1; Skin Irrit. 2; STOT SE 3: Resp. Irrit.	NDA	
Perlite	CAS: 93763- 70-3	20% TO 25%	NDA	OSHA HCS 2012: Not Classified	NDA	
Mullite	CAS: 1302-93 -8	14% TO 19.8%	NDA	OSHA HCS 2012: STOT RE 2 (Lungs)	NDA	
Cristobalite	CAS: 14464- 46-1	5.6% TO 12.347%	NDA	OSHA HCS 2012: Carc. 1A	NDA	
Kaolin	CAS: 1332-58 -7	6.4% TO 12%	NDA	OSHA HCS 2012: STOT RE 2 (Lungs)	NDA	
Silica, amorphous	CAS: 7631-86 -9	4.2% TO 8.25%	NDA	OSHA HCS 2012: Not Classified	NDA	
Aluminum(III) silicate (2:1)	CAS :1302-76 -7	2.55% TO 6.65%	NDA	OSHA HCS 2012: STOT RE 2 (Lungs)	NDA	
Bentonite	CAS :1302-78 -9	0.6% TO 4%	NDA	OSHA HCS 2012: STOT RE 2 (Lungs)	NDA	
Quartz	CAS :14808- 60-7	0.16% TO 3.65%	NDA	OSHA HCS 2012: Carc. 1A; STOT RE 1 (Lungs)	NDA	
Silica, crystalline - tridymite	CAS :15468- 32-3	0% TO 2.44%	NDA	OSHA HCS 2012: STOT RE 1 (Lungs, Inhl)	NDA	
Amorphous/fused silica	CAS:60676- 86-0	0% TO 2.1%	NDA	OSHA HCS 2012: Not Classified	NDA	
Titanium dioxide	CAS: 13463- 67-7	0.03% TO 1.4%	NDA	OSHA HCS 2012: Carc. 2	NDA	
Iron oxide	CAS: 1309-37 -1	0% TO 1.4%	NDA	OSHA HCS 2012: Not Classified	NDA	
Sodium aluminate	CAS :1302-42 -7	< 0.25%	NDA	OSHA HCS 2012: Skin Corr. 1C; Eye Dam.	NDA	
Magnesium oxide	CAS: 1309-48 -4	0% TO 0.21%	NDA	OSHA HCS 2012: Not Classified	NDA	
Sodium hydroxide	CAS: 1310-73 -2	0% TO 0.175%	NDA	OSHA HCS 2012: Skin Corr. 1B; Eye Dam.	NDA	
1-Propene, homopolymer	CAS :9003-07 -0	< 0.15%	Ingestion/Oral-Rat LD50 • >8 g/kg	OSHA HCS 2012: Not Classified	NDA	
Calcium oxide	CAS: 1305-78 -8	0% TO 0.07%	NDA	OSHA HCS 2012: Exposure limits	NDA	

Section 4: First-Aid Measures

Description of first aid measures

Inhalation	 Move victim to fresh air. Give artificial respiration if victim is not breathing. Administer oxygen if breathing is difficult. Get medical attention immediately. 					
Skin	 In case of contact with substance, immediately flush skin with running water for at least 20 minutes. If skin irritation occurs: Get medical advice/attention. 					
Eye	 In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention. 					
Ingestion	 Rinse mouth. Do not give anything by mouth to an unconscious person. Get medical attention immediately. 					
Most important symptoms and effects, both acute and delayed						

Most important symptoms and effects, both acute and delayed

• Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

 All treatments should be based on observed signs and symptoms of distress in thepatient. Consideration should be given to the possibility that overexposure to materialsother than this product may have occurred.

Section 5: Fire-Fighting Measures

Extinguishing media

Suitable Extinguishing Media • Material is non-combustible. In case of fire use media as appropriate for surrounding fire.

Unsuitable Extinguishing • None known. Media

Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards	None known.
Hazardous Combustion Products	None known.
Advice for firefighters	

Wear positive pressure self-contained breathing apparatus (SCBA).
 Structural firefighters' protective clothing will only provide limited protection.
 Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions	 Isolate hazard area and deny entry to unauthorized and/or unprotected personnel. Do not touch or walk through spilled material. Ensure adequate ventilation to remove vapors, fumes, dust etc. 				
Emergency Procedures	 Ventilate closed spaces before entering. Isolate hazard area and deny entry to unauthorized and/or unprotected personnel. 				
Environmental precaution	ons				
	No specific actions or treatments recommended related to exposure to this material.				
Methods and material for containment and cleaning up					

Containment/Clean-up Measures	 Avoid generating dust. FOR SMALL SPILLS: Clean with a vacuum with a filtration system sufficient to remove and prevent recirculation of crystalline silica (a vacuum equipped with a high-efficiency particulate air (HEPA) filter is recommended). FOR LARGE SPILLS: Use a fine spray or mist to control dust creation and carefully scoop or shovel into clean dry container for later reuse or disposal. If, an appropriate vacuum is unavailabe, only wet-clean-up methods should be used (i.e. misting). Moisture should be added as necessary to reduce exposure to airborne respirable silica dust.
----------------------------------	--

Section 7 - Handling and Storage

Precautions for safe handling

Handling

Do not breathe dust. Avoid contact with skin, eyes, and clothing. Minimize dust generation and accumulation. Use good safety and industrial hygiene practices. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Wear long sleeves and/or protective coveralls. Contaminated clothing must be vacuumed before removal. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Wash thoroughly after

handling. Do not use in areas without adequate ventilation.

Conditions for safe storage, including any incompatibilities

• Store in a covered location. Keep container closed. Keep from freezing. Storage and work area should be periodically cleaned to minimize dust accumulation.

Section 8 - Exposure Controls/Personal Protection

Control parameters

Exposure Limits/Guidelines						
	Result	ACGIH	Canada Ontario	Canada Quebec	Mexico	NIOSH
Sodium hydroxide (1310-73-2)	Ceilings	2 mg/m3 Ceiling	2 mg/m3 Ceiling	2 mg/m3 Ceiling	2 mg/m3 Ceiling	2 mg/m3 Ceiling
	STELs	Not established	Not established	Not established	10 mg/m3 STEL [LMPE-CT] (as Fe)	Not established
Iron oxide (1309-37-1)	TWAs	5 mg/m3 TWA (respirable fraction)	5 mg/m3 TWA (respirable)	5 mg/m3 TWAEV (dust and fume, as Fe); 10 mg/m3 TWAEV (containing no Asbestos and <1% Crystalline silica, regulated under Rouge, total dust)	5 mg/m3 TWA LMPE- PPT	5 mg/m3 TWA (dust and fume, as Fe)
Silica, crystalline - tridymite (15468-32-3)	TWAs	Not established	Not established	0.05 mg/m3 TWAEV (respirable dust)	0.05 mg/m3 TWA LMPE-PPT (respirable fraction)	0.05 mg/m3 TWA (respirable dust)
Calcium oxide (1305-78-8)	TWAs	2 mg/m3 TWA	2 mg/m3 TWA	2 mg/m3 TWAEV	2 mg/m3 TWA LMPE- PPT	2 mg/m3 TWA
Magnesium oxide (1309-48-4)	TWAs	10 mg/m3 TWA (inhalable fraction)	10 mg/m3 TWA (inhalable)	10 mg/m3 TWAEV (fume, as Mg)	10 mg/m3 TWA LMPE -PPT (fume, as Mg)	Not established
Amorphous/fused silica (60676-86-0)	TWAs	Not established	0.1 mg/m3 TWA (respirable)	0.1 mg/m3 TWAEV (containing no Asbestos and <1% Crystalline silica, respirable dust)	0.1 mg/m3 TWA LMPE-PPT; 10 mg/m3 TWA LMPE-PPT (inhalable particulate); 3 mg/m3 TWA LMPE-PPT (respirable particulate)	Not established
	STELs	Not established	Not established	Not established	20 mg/m3 STEL [LMPE-CT] (as Ti)	Not established
Titanium dioxide (13463-67-7)	TWAs	10 mg/m3 TWA	10 mg/m3 TWA	10 mg/m3 TWAEV (containing no Asbestos and <1% Crystalline silica, total dust)	10 mg/m3 TWA LMPE -PPT (as Ti)	Not established
Quartz (14808-60-7)	TWAs	0.025 mg/m3 TWA (respirable fraction)	0.10 mg/m3 TWA (designated substances regulation, respirable, listed under Silica, crystalline)	0.1 mg/m3 TWAEV (respirable dust)	0.1 mg/m3 TWA LMPE-PPT (respirable fraction)	0.05 mg/m3 TWA (respirable dust)
				2 mg/m3 TWAEV (as Al)	2 mg/m3 TWA LMPE- PPT	2 mg/m3 TWA (as Al)

Storage

Sodium aluminate	TWAs	Not established	Not	established		Aluminum, uble salts	as Aluminum, soluble salts	as Aluminum, soluble salts	
Silica, amorphous (7631-86-9)	TWAs	Not established	Not established		Not	established	Not established	6 mg/m3 TWA	
Cristobalite (14464-46-1)	TWAs	0.025 mg/m3 TWA (respirable fraction)				5 mg/m3 TWAEV spirable dust)	0.05 mg/m3 TWA LMPE-PPT (respirable fraction)	0.05 mg/m3 TWA (respirable dust)	
	STELs	Not established	Not	established	Not	established	20 mg/m3 STEL [LMPE-CT]	Not established	
Kaolin (1332-58-7)	TWAs	2 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)	2 mg/m3 TWA (containing no Asbestos and <1% Crystalline silica, respirable)		(co Ast Cry	ng/m3 TWAEV ntaining no pestos and <1% rstalline silica, pirable dust)	10 mg/m3 TWA LMPE -PPT	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)	
Perlite (93763-70-3)	TWAs	Not established	10 mg/m3 TWA (containing no Asbestos and <1% Crystalline silica)		Not	established	10 mg/m3 TWA LMPE -PPT	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)	
		Ex	pos	ure Limits/Gui	del	ines (Con't.)			
				Result		OSHA			
Sodium hydroxide (1310-73-2)				TWAs 2 mg/m3		2 mg/m3 TWA	mg/m3 TWA		
Iron oxide (1309-37-1)			TWAs		10 mg/m3 TWA (fume); 15 mg/m3 TWA (total dust, listed under Rouge); 5 mg/m3 TWA (respirable fraction, listed under Rouge)				
Calcium oxide (1305-78-8)			TWAs		5 mg/m3 TWA				
Magnesium oxide (1309-48-4)		TWAs		15 mg/m3 TWA (fume, total particulate)					
Titanium dioxide (13463-67-7)		TWAs		15 mg/m3 TWA (total dust)					
Kaolin (1332-58-7)		TWAs		15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)					

Exposure Control Notations

Mexico

• Iron oxide (1309-37-1): Carcinogens: (A4 - Not classifiable as a human carcinogen)

•Kaolin (1332-58-7): Carcinogens: (A4 - Not classifiable as a human carcinogen)

• Titanium dioxide (13463-67-7): Carcinogens: (A4 - Not classifiable as a human carcinogen)

•Perlite (93763-70-3): Carcinogens: (A4 - Not classifiable as a human carcinogen)

Canada Ontario

•Cristobalite (14464-46-1): Designated Substances: (0.05 mg/m3 TWA (respirable fraction, listed under Silica, crystalline))

•Quartz (14808-60-7): Designated Substances: (0.10 mg/m3 TWA (respirable fraction, listed under Silica, crystalline))

Canada Quebec

•Quartz (14808-60-7): Carcinogens: (C2 carcinogen - effect suspected in humans)

ACGIH

- •Iron oxide (1309-37-1): Carcinogens: (A4 Not Classifiable as a Human Carcinogen)
- •Magnesium oxide (1309-48-4): Carcinogens: (A4 Not Classifiable as a Human Carcinogen)
- •Kaolin (1332-58-7): Carcinogens: (A4 Not Classifiable as a Human Carcinogen)
- Titanium dioxide (13463-67-7): Carcinogens: (A4 Not Classifiable as a Human Carcinogen)

•Cristobalite (14464-46-1): Carcinogens: (A2 - Suspected Human Carcinogen)

•Quartz (14808-60-7): Carcinogens: (A2 - Suspected Human Carcinogen)

Exposure Limits Supplemental OSHA

•Cristobalite (14464-46-1): **Mineral Dusts:** ((1/2)(30)/(%SiO2 + 2) mg/m3 TWA, total dust; (1/2)(250)/(%SiO2 + 5) mppcf TWA, respirable fraction; (1/2)(10)/(%SiO2 + 2) mg/m3 TWA, respirable fraction)

•Quartz (14808-60-7): Mineral Dusts: ((30)/(%SiO2 + 2) mg/m3 TWA, total dust; (250)/(%SiO2 + 5) mppcf TWA, respirable fraction; (10)/(%SiO2 + 2) mg/m3 TWA, respirable fraction)

•Silica, crystalline - tridymite (15468-32-3): **Mineral Dusts:** ((1/2)(30)/(%SiO2 + 2) mg/m3 TWA, total dust; (1/2)(250)/(%SiO2 + 5) mppcf TWA, respirable fraction; (1/2)(10)/(%SiO2 + 2) mg/m3 TWA, respirable fraction)

•Amorphous/fused silica (60676-86-0): Mineral Dusts: ((80)/(% SiO2) mg/m3 TWA; 20 mppcf TWA)

•Silica, amorphous (7631-86-9): Mineral Dusts: (20 mppcf TWA; (80)/(% SiO2) mg/m3 TWA)

ACGIH

•Calcium oxide (1305-78-8): TLV Basis - Critical Effects: (upper respiratory tract irritation)

•Iron oxide (1309-37-1): TLV Basis - Critical Effects: (pneumoconiosis)

•Sodium hydroxide (1310-73-2): TLV Basis - Critical Effects: (eye, skin and upper respiratory tract irritation)

•Kaolin (1332-58-7): TLV Basis - Critical Effects: (pneumoconiosis)

• Titanium dioxide (13463-67-7): TLV Basis - Critical Effects: (lower respiratory tract irritation) | Notice of Intended Changes (TLVs): (1

mg/m3 TWA (respirable fraction); A3 - confirmed animal carcinogen with unknown relevance to humans; TLV basis: lower respiratory tract irritation, pneumoconiosis)

•Cristobalite (14464-46-1): TLV Basis - Critical Effects: (lung cancer; pulmonary fibrosis)

•Quartz (14808-60-7): TLV Basis - Critical Effects: (lung cancer; pulmonary fibrosis)

Exposure controls

Engineering Measures/Controls	conditions. If applicabl engineering controls to If exposure limits have level. Adequate ventila contaminants below a systems (such as exh are designed in a man is not leakage from the	 Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Ensure that dust handling systems (such as exhaust ducts, dust collectors, vessels and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is not leakage from the equipment). Collection systems must be designed and maintained to prevent the accumalation and recirculation of respirable silica into the workplace. 					
Personal Protective Equipme	nt						
Respiratory	purifying respirator wit respirator regulations f NIOSH/MSHA or Euro	For limited exposure use an N95 dust mask. For prolonged exposure use an air- purifying respirator with high efficiency particulate air (HEPA) filters. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.					
Eye/Face	Wear protective eyewe	Wear protective eyewear (goggles, face shield, or safety glasses).					
Hands	Wear appropriate glove	Wear appropriate gloves.					
Skin/Body	Wear long sleeves and	Wear long sleeves and/or protective coveralls.					
General Industrial Hygiene Considerations	from clothing by blowing hands before eating, d	Avoid breathing dust. Avoid contact with skin, eyes or clothing. Do not remove dusts from clothing by blowing or shaking. Do not eat, drink or smoke during work. Wash hands before eating, drinking, or smoking. Wash thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice.					
Environmental Exposure Controls	 Follow best practice for approved landfill. 	Follow best practice for site management and disposal of waste. Dispose of in an approved landfill.					
Key to abbreviations							
ACGIH = American Conference of Gove Hygiene	rnmental Industrial	STEL = Short Term Exposure Limits are based on 15-minute exposures					
NIOSH = National Institute of Occupation	onal Safety and Health	TWAEV = Time-Weighted Average Exposure Value					
OSHA = Occupational Safety and Hea	th Administration	TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures					
Dreparation Date: 01/December/2012							

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description			
Physical Form	Solid	Appearance/Description	Gray granular dry powder with an earthy odor.
Color	Gray	Odor	Earthy
Particulate Size	600 µ	Odor Threshold	No data available
General Properties			
Boiling Point	No data available	Melting Point/Freezing Point	No data available
Decomposition Temperature	No data available	рН	Not relevant
Specific Gravity/Relative Density	2.2 to 2.9 Water=1	Water Solubility	Negligible < 0.1 %
Viscosity	No data available		
Volatility	•	•	
Vapor Pressure	No data available	Vapor Density	No data available
Evaporation Rate	No data available	VOC (Wt.)	0 %
VOC (Vol.)	0 %		
Flammability		•	•
Flash Point	Not relevant	UEL	Not relevant
LEL	Not relevant	Autoignition	No data available
Flammability (solid, gas)	No data available		
Environmental	-		•
Octanol/Water Partition coefficient	No data available		

Section 10: Stability and Reactivity

Reactivity

• No dangerous reaction known under conditions of normal use.

Chemical stability

• Stable under normal temperatures and pressures.

Possibility of hazardous reactions

• Hazardous polymerization not indicated.

Conditions to avoid

• None known.

Incompatible materials

• None known.

Hazardous decomposition products

• None known.

Section 11 - Toxicological Information

Information on toxicological effects

	Components				
Kaolin (6.4% TO 12%) 1332-58 Reproductive: Ingestion/Oral-Rat TDLo • 370 g/kg (37D pre/1-22D preg); Reproductive Effects:Maternal Fifects:Other effects; Reproductive Effects:Effects on Newborn:Other neonatal measures or effects					
Titanium dioxide (0.03% TO 1.4%)	13463- 67-7	ritation: Skin-Human • 300 μg 3 Day(s)-Intermittent • Mild irritation; umorigen / Carcinogen: Inhalation-Rat TCLo • 250 mg/m³ 6 Hour(s) 2 Year(s)-Intermittent; umorigenic:Carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration:Tumors			
Silica, crystalline - tridymite (0% TO 2.44%)	15468- 32-3	Acute Toxicity: Inhalation-Human TCLo • 16 mppcf 8 Hour(s) 17.9 Year(s)-Intermittent; Lungs, Thorax, or Respiration:Fibrosis, focal (pneumoconiosis); Lungs, Thorax, or Respiration:Cough; Lungs, Thorax, or Respiration:Dyspnea			
Silica, amorphous (4.2% TO 8.25%)	7631-86 -9	rritation: Eye-Rabbit • 25 mg 24 Hour(s) • Mild irritation			
1-Propene, homopolymer (< 0.15%)	9003-07 -0	Acute Toxicity: Ingestion/Oral-Rat LD50 • >8 g/kg			
Perlite (20% TO 25%)	93763- 70-3	Acute Toxicity: Ingestion/Oral-Mouse LD50 • 12960 mg/kg			

GHS Properties		Classification	
Acute toxicity		OSHA HCS 2012 • No data available	
Skin corrosion/Irritation		OSHA HCS 2012 • Skin Irritation 2	
Serious eye damage/Irritation		OSHA HCS 2012 • Serious Eye Damage 1	
Skin sensitization		OSHA HCS 2012 • No data available	
Respiratory sensitization		OSHA HCS 2012 • No data available	
Aspiration Hazard		OSHA HCS 2012 • No data available	
Carcinogenicity		OSHA HCS 2012 • Carcinogenicity 1A	
Germ Cell Mutagenicity		OSHA HCS 2012 • No data available	
Toxicity for Reproduction		OSHA HCS 2012 • No data available	
STOT-SE		OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 3: Respiratory Tract Irritation	
STOT-RE		OSHA HCS 2012 • Specific Target Organ Toxicity Repeated Exposure 1	
Target Organs • [206]			
Route(s) of entry/exposure	 Inhalation, S 	kin, Eye, Ingestion	
Medical Conditions Aggravated by Exposure Potential Health Effects Inhalation	 Any pre-existing conditions of the lungs. Disorders of the lungs. 		
Acute (Immediate)	 May cause re 	espiratory irritation. Exposure to dust may cause irritation.	
delayed lung		exposure to dust containing respirable sized crystalline silica can cause injury (silicosis). Inhalation of dust containing crystalline silica pulmonary th as asthma and lung disorder associated with smoking.	
Skin			
Acute (Immediate)	 Causes skin 	 Causes skin irritation. Exposure to dust may cause irritation. 	
Chronic (Delayed)	hronic (Delayed)		
Evo			

Eye

- Acute (Immediate)
- Causes serious eye damage. Excessive concentrations of nuisance dust in the workplace may reduce visibility and may cause unpleasant deposits in eyes.

Chronic (Delayed)	•	No data available.		
Ingestion				
Acute (Immediate)		Excessive concentrations of nuisance dust in the workplace may cause mechanical irritation to mucous membranes.		
Chronic (Delayed)	•	No data available.		
Carcinogenic Effects		May cause cancer. IARC studies have shown sufficient evidence from animal studies to categorize crystalline silica as a group 1 carcinogen.		
Carcinogenic Effects				
	CAS	IARC	NTP	

	CAS	IARC	NTP
Silica, crystalline - tridymite	15468-32-3	Group 1-Carcinogenic	Not Listed
Titanium dioxide	13463-67-7	Group 2B-Possible Carcinogen	Not Listed
Quartz	14808-60-7	Group 1-Carcinogenic	Known Human Carcinogen
Cristobalite	14464-46-1	Group 1-Carcinogenic	Not Listed

Key to abbreviations

LD = Lethal Dose

TC = Toxic Concentration

TD = Toxic Dose

Section	12 - E	cological	Information
---------	--------	-----------	-------------

Toxicity

•	Material data lacking.					
Persistence and degradability						
•	Material data lacking.					
Bioaccumulative potential						
•	Material data lacking.					
Mobility in Soil						
•	Material data lacking.					
Other adverse effects						
•	No studies have been found.					

Section 13 - Disposal Considerations

Waste treatment methods

Product waste	ose of content and/or container in accordance with local, regional, national, and/or national regulations.
Packaging waste	ose of content and/or container in accordance with local, regional, national, and/or national regulations.

Section 14 - Transport Information

UN	UN proper shipping	Transport hazard class	Packing	Environmental
number	name	(es)	group	hazards

DOT	NDA	Not Regulated	NDA	NDA	NDA
TDG	NDA	Not Regulated	NDA	NDA	NDA
IATA/ICAO	NDA	Not Regulated	NDA	NDA	NDA

Special precautions for user • None specified.

Transport in bulk according • No data available to Annex II of MARPOL 73/78 and the IBC Code

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute, Chronic

	State Right To Know					
Component	CAS	MA	NJ	PA		
Amorphous/fused silica	60676-86-0	Yes	Yes	No		
Bentonite	1302-78-9	No	No	No		
Calcium oxide	1305-78-8	Yes	Yes	Yes		
Cristobalite	14464-46-1	Yes	Yes	Yes		
Iron oxide	1309-37-1	Yes	Yes	Yes		
Kaolin	1332-58-7	Yes	Yes	Yes		
Perlite	93763-70-3	Yes	Yes	Yes		
Quartz	14808-60-7	Yes	Yes	Yes		
Silica, amorphous	7631-86-9	Yes	Yes	Yes		
Silica, crystalline - tridymite	15468-32-3	Yes	Yes	Yes		
Sodium aluminate	1302-42-7	No	No	No		
Sodium hydroxide	1310-73-2	Yes	Yes	Yes		
Titanium dioxide	13463-67-7	Yes	Yes	Yes		

	Inventory					
Component	CAS	Canada DSL	TSCA			
Amorphous/fused silica	60676-86-0	Yes	Yes			
Bentonite	1302-78-9	Yes	Yes			
Calcium oxide	1305-78-8	Yes	Yes			
Cristobalite	14464-46-1	Yes	Yes			
Iron oxide	1309-37-1	Yes	Yes			
Kaolin	1332-58-7	Yes	Yes			
Perlite	93763-70-3	Yes	No			
Quartz	14808-60-7	Yes	Yes			
Silica, amorphous	7631-86-9	Yes	Yes			
Silica, crystalline - tridymite	15468-32-3	No	No			
Sodium aluminate	1302-42-7	Yes	Yes			

Sodium hydroxide	1310-73-2	Yes	Yes
Titanium dioxide	13463-67-7	Yes	Yes

Canada

Canada - WHMIS - Classifications of Substances • Sodium aluminate	1302-42-7	E
Solica, crystalline - tridymite	15468-32-3	E D2A
• Kaolin	1332-58-7	D2A D2A
• Perlite	93763-70-3	D2A (expanded, containing >0.1% Crystalline silica); Uncontrolled product according to WHMIS classification criteria (expanded)
Calcium oxide	1305-78-8	E
Iron oxide	1309-37-1	Uncontrolled product according to WHMIS classification criteria
Sodium hydroxide	1310-73-2	E (including 0.04% in aqueou solution, 0.08%, 0.4% in aqueous solution, 2%, 2.5%, 4% in aqueous solution, 5%, 10%, 16%, 20%, 40%, 50% in aqueous solution, 8.7N)
• Titanium dioxide	13463-67-7	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specif Issues - Titanium dioxide, mixture containing on Health Canada's WHMIS Division website.)
• Cristobalite	14464-46-1	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specif Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS Division website.)
Silica, amorphous	7631-86-9	Uncontrolled product according to WHMIS classification criteria
Amorphous/fused silica	60676-86-0	Uncontrolled product according to WHMIS classification criteria
• Quartz	14808-60-7	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specif Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS Division website.)
Bentonite	1302-78-9	D2A

Canada - WHMIS - Ingredient Disclosure List

Sodium aluminate	1302-42-7	Not Listed
Silica, crystalline - tridymite	15468-32-3	1 %
• Kaolin	1332-58-7	Not Listed
• Perlite	93763-70-3	Not Listed
Calcium oxide	1305-78-8	1 %
Iron oxide	1309-37-1	1 %
Sodium hydroxide	1310-73-2	1 %
Titanium dioxide	13463-67-7	Not Listed
Cristobalite	14464-46-1	1 %
Silica, amorphous	7631-86-9	1 %
Amorphous/fused silica	60676-86-0	1 %
• Quartz	14808-60-7	1 %
Bentonite	1302-78-9	Not Listed

United States

Environment

U.S CERCLA/SARA - Hazardous Substances and their Reportable Quantities			
Sodium aluminate	1302-42-7	Not Listed	
Silica, crystalline - tridymite	15468-32-3	Not Listed	
• Kaolin	1332-58-7	Not Listed	
• Perlite	93763-70-3	Not Listed	
Calcium oxide	1305-78-8	Not Listed	
Iron oxide	1309-37-1	Not Listed	
Sodium hydroxide	1310-73-2	1000 lb final RQ; 454 kg final RQ	
Titanium dioxide	13463-67-7	Not Listed	
Cristobalite	14464-46-1	Not Listed	
Silica, amorphous	7631-86-9	Not Listed	
Amorphous/fused silica	60676-86-0	Not Listed	
• Quartz	14808-60-7	Not Listed	
Bentonite	1302-78-9	Not Listed	
			1

United States - California

Environment U.S California - Proposition 65 - Carcinogens List		
Sodium aluminate	1302-42-7	Not Listed
Silica, crystalline - tridymite	15468-32-3	Not Listed
• Kaolin	1332-58-7	Not Listed
• Perlite	93763-70-3	Not Listed
Calcium oxide	1305-78-8	Not Listed
Iron oxide	1309-37-1	Not Listed
Sodium hydroxide	1310-73-2	Not Listed
Titanium dioxide	13463-67-7	carcinogen, initial date 9/2/11 (airborne, unbound particles of respirable size)
Cristobalite	14464-46-1	Not Listed
Silica, amorphous	7631-86-9	Not Listed
Amorphous/fused silica	60676-86-0	Not Listed
• Quartz	14808-60-7	carcinogen, initial date 10/1/88 (airborne particles of respirable size)
Bentonite	1302-78-9	Not Listed

United States - Pennsylvania

d List	
1302-42-7	Not Listed
15468-32-3	Not Listed
1332-58-7	Not Listed
93763-70-3	Not Listed
1305-78-8	Not Listed
1309-37-1	Not Listed
1310-73-2	
13463-67-7	Not Listed
14464-46-1	Not Listed
7631-86-9	Not Listed
60676-86-0	Not Listed
14808-60-7	Not Listed
1302-78-9	Not Listed
	1302-42-7 15468-32-3 1332-58-7 93763-70-3 1305-78-8 1309-37-1 1310-73-2 13463-67-7 14464-46-1 7631-86-9 60676-86-0 14808-60-7

Other Information

• WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information		
Revision Date	• 03/January/2018	
Last Revision Date	• 22/December/2014	
Preparation Date	• 01/December/2013	
Disclaimer/Statement of Liability	• The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. Reno Refractories MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.	

Key to abbreviations NDA = No data available