Safety Data Sheet



Section 1: Identification

Product identifier

Product Name Reno Cast 65 UL

Product Code • 150400

Relevant identified uses of the substance or mixture and uses advised against

Recommended use • Refractory applications

Details of the supplier of the safety data sheet

Manufacturer • Reno Refractories, Inc.

P O Box 201 Morris, AL 35116 United States

www.renorefractories.com sales@renorefractories.com

Telephone (General) • 205-647-0240

Emergency telephone number

Manufacturer • 1-800-262-8200 - CHEMTREC

Section 2: Hazard Identification

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012 • Carcinogenicity 1A

Specific Target Organ Toxicity Repeated Exposure 1

Label elements
OSHA HCS 2012

DANGER



Hazard statements • May cause cancer.

Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention • Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves, clothing, and eye/face protection, .

Response • IF exposed or concerned: Get medical advice/attention.

Storage/Disposal • Dispose of content and/or container in accordance with local, regional, national, and/or

international regulations.

Other hazards

• Under United States Regulations (29 CFR 1910.1200 - Hazard Communication

Standard), this product is considered hazardous.

Canada

According to: WHMIS

Classification of the substance or mixture

• Other Toxic Effects - D2A
Other Toxic Effects - D2B

Label elements

WHMIS .

(T)

• Other Toxic Effects - D2A Other Toxic Effects - D2B

Other hazards

WHMIS
 In Canada, the product mentioned above is considered hazardous under the

Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients

Substances

Material does not meet the criteria of a substance.

Mixtures

Classifications According to
Regulation/Directive Comme
OSHA HCS 2012: STOT RE 2 (Lungs)
O.2 OSHA HCS 2012: Not Classified NDA
OSHA HCS 2012: Not Classified NDA
OSHA HCS 2012: STOT RE 2 (Lungs)
OSHA HCS 2012: STOT RE 1 (Lungs)
OSHA HCS 2012: Not Classified NDA

Quartz	CAS :14808-60-7	0.35% TO 1.008%	NDA	OSHA HCS 2012: Carc. 1A; STOT RE 1 (Lungs)	NDA
Titanium dioxide	CAS :13463-67-7	0.07% TO 0.5%	NDA	OSHA HCS 2012: Carc. 2	NDA
Cristobalite	CAS :14464-46-1	0.159% TO 0.175%	NDA	OSHA HCS 2012: Carc. 1A	NDA
Dispersing Agent	Proprietary	< 0.1395%	Ingestion/Oral-Rat LD50 • 3120 mg/kg Skin-Rabbit LD50 • >4640 mg/kg	OSHA HCS 2012: Eye Irrit. 2A; Skin Irrit. 2; STOT SE 3: Resp. Irrit.	NDA
Diphosphoric acid, sodium salt (1:4)	CAS :7722-88-5	< 0.0075%	Ingestion/Oral-Rat LD50 • 4 g/kg	OSHA HCS 2012: Exposure limits	NDA
Formaldehyde	CAS:50-00-0	<= 0.00002%	Ingestion/Oral-Rat LD50 • 100 mg/kg Inhalation-Rat LC50 • 250 ppm 2 Hour(s) Skin-Rabbit LD50 • 270 mg/kg	OSHA HCS 2012: Exposure limits	NDA

Section 4: First-Aid Measures

Description of first aid measures

Inhalation

 Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. Get medical attention immediately.

Skin

In case of contact with substance, immediately flush skin with running water for at least 20 minutes. If skin irritation occurs: Get medical advice/attention.

Eye

 In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.

Ingestion

Rinse mouth. Do not give anything by mouth to an unconscious person. Get medical attention immediately.

Most important symptoms and effects, both acute and delayed

Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

 All treatments should be based on observed signs and symptoms of distress in thepatient. Consideration should be given to the possibility that overexposure to materialsother than this product may have occurred.

Section 5: Fire-Fighting Measures

Extinguishing media

Suitable Extinguishing Media • Material is non-combustible. In case of fire use media as appropriate for surrounding fire.

Unsuitable Extinguishing Media

· None known.

Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

None known.

Hazardous Combustion Products

None known.

Advice for firefighters

Wear positive pressure self-contained breathing apparatus (SCBA).

Structural firefighters' protective clothing will only provide limited protection. Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Isolate hazard area and deny entry to unauthorized and/or unprotected personnel. Do
not walk through spilled material. Ensure adequate ventilation to remove vapors,
fumes, dust etc. Wear appropriate personal protective equipment, avoid direct contact.

Emergency Procedures

 Ventilate closed spaces before entering. Isolate hazard area and deny entry to unauthorized and/or unprotected personnel.

Environmental precautions

No specific actions or treatments recommended related to exposure to this material.

Methods and material for containment and cleaning up

Containment/Clean-up Measures

· Avoid generating dust.

FOR SMALL SPILLS: Clean with a vacuum with a filtration system sufficient to remove and prevent recirculation of crystalline silica (a vacuum equipped with a high-efficiency particulate air (HEPA) filter is recommended).

FOR LARGE SPILLS: Use a fine spray or mist to control dust creation and carefully scoop or shovel into clean dry container for later reuse or disposal.

If, an appropriate vacuum is unavailabe, only wet-clean-up methods should be used (i.e. misting). Moisture should be added as necessary to reduce exposure to airborne respirable silica dust.

Section 7 - Handling and Storage

Precautions for safe handling

Handling

Use good safety and industrial hygiene practices. Use only in well ventilated areas.
Wear appropriate personal protective equipment, avoid direct contact. Wear long
sleeves and/or protective coveralls. Do not breathe dust. Avoid contact with skin,
eyes, and clothing. Minimize dust generation and accumulation. Routine
housekeeping should be instituted to ensure that dusts do not accumulate on
surfaces. Contaminated clothing must be vacuumed before removal. Contaminated
work clothing should not be allowed out of the workplace. Wash contaminated clothing
before reuse. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage

 Store in a covered location. Keep container closed. Keep from freezing. Storage and work area should be periodically cleaned to minimize dust accumulation.

Section 8 - Exposure Controls/Personal Protection

Control parameters

Exposure Limits/Guidelines								
	Result	ACGIH	Canada Ontario	Canada Quebec	Mexico	NIOSH		
Formaldehyde (50-00-0)	Ceilings	0.3 ppm Ceiling	1.5 ppm Ceiling	2 ppm Ceiling; 3 mg/m3 Ceiling	2 ppm Ceiling; 3 mg/m3 Ceiling	0.1 ppm Ceiling (15 min)		
	STELs	Not established	1.0 ppm STEL	Not established	Not established	Not established		
	TWAs	Not established	Not established	Not established	Not established	0.016 ppm TWA		
Diphosphoric acid, sodium salt (1:4) (7722-88-5)	TWAs	Not established	5 mg/m3 TWA	5 mg/m3 TWAEV	Not established	5 mg/m3 TWA		

	STELs	Not established	Not	established	Not	established	20 mg/m3 STEL [LMPE-CT] (as Ti)	Not established
Titanium dioxide (13463-67-7)	TWAs	10 mg/m3 TWA	10 r	ng/m3 TWA	(coi Ast	mg/m3 TWAEV ntaining no pestos and <1% stalline silica, total st)	10 mg/m3 TWA LMPE -PPT (as Ti)	Not established
Cristobalite (14464-46-1)	TWAs	0.025 mg/m3 TWA (respirable fraction)	(des sub regi	5 mg/m3 TWA signated stances ulation, respirable, ed under Silica, stalline)		5 mg/m3 TWAEV spirable dust)	0.05 mg/m3 TWA LMPE-PPT (respirable fraction)	0.05 mg/m3 TWA (respirable dust)
Quartz (14808-60-7)	TWAs	0.025 mg/m3 TWA (respirable fraction)	(des sub regi	o mg/m3 TWA signated stances ulation, respirable, ed under Silica, stalline)		mg/m3 TWAEV spirable dust)	0.1 mg/m3 TWA LMPE-PPT (respirable fraction)	0.05 mg/m3 TWA (respirable dust)
Cement, alumina, chemicals	TWAs	10 mg/m3 TWA (inhalable particles, recommended); 3 mg/m3 TWA (respirable particles, recommended) as Particulates not otherwise classified (PNOC)	10 mg/m3 TWA (inhalable); 3 mg/m3 TWA (respirable) as Particulates not otherwise classified (PNOC)		(incorrection or repair con Ask Cry dust as a cother cother correction or repair cother cothe	mg/m3 TWAEV Illuding dust, inert inuisance ticulates; taining no vestos and <1% stalline silica, total it) Particulates not verwise classified VOC)	Not established	Not established
Amorphous silica fume (69012-64-2)	TWAs	Not established	(res	g/m3 TWA pirable, listed er Silica fume)	(co Asb Cry	g/m3 TWAEV ntaining no pestos and <1% stalline silica, pirable dust)	2 mg/m3 TWA LMPE- PPT; 10 mg/m3 TWA LMPE-PPT (inhalable particulate); 3 mg/m3 TWA LMPE-PPT (respirable particulate)	Not established
Silica, amorphous (7631-86-9)	TWAs	Not established	Not	established	Not	established	Not established	6 mg/m3 TWA
Aluminum oxide (1344-28-1)	TWAs	1 mg/m3 TWA (respirable fraction)	(respirable) (c		(co Asb Cry	mg/m3 TWAEV ntaining no pestos and <1% stalline silica, total	10 mg/m3 TWA LMPE -PPT	Not established
		insoluble compounds	_	npounds	ш	t, as AI)		
		Ex	pos	ure Limits/Gui Result	aeli	nes (Con't.)	OSHA	
Formaldehyde				STELs		2 ppm STEL (see 2	29 CFR 1910.1048)	
(50-00-0)				TWAs		0.75 ppm TWA	·	
Titanium dioxide (13463-67-7)				TWAs		15 mg/m3 TWA (to	tal dust)	
Cement, alumina, ch	nemicals			TWAs		,	otal dust); 5 mg/m3 TW, t otherwise classified (, ,

1	Aluminum oxide	I_T\A/A a	15 mg/m2 TMA (total dupt): 5 mg/m2 TMA (requireble fraction)	
	(1344-28-1)	TWAs	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	

Exposure Limits Supplemental OSHA

- •Cristobalite (14464-46-1): Mineral Dusts: ((1/2)(30)/(%SiO2 + 2) mg/m3 TWA, total dust; (1/2)(250)/(%SiO2 + 5) mppcf TWA, respirable fraction; (1/2)(10)/(%SiO2 + 2) mg/m3 TWA, respirable fraction)
- •Quartz (14808-60-7): Mineral Dusts: ((30)/(%SiO2 + 2) mg/m3 TWA, total dust; (250)/(%SiO2 + 5) mppcf TWA, respirable fraction; (10)/(%SiO2
- + 2) mg/m3 TWA, respirable fraction)
- •Silica, amorphous (7631-86-9): Mineral Dusts: (20 mppcf TWA; (80)/(% SiO2) mg/m3 TWA)

Exposure controls

Engineering Measures/Controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Ensure that dust handling systems (such as exhaust ducts, dust collectors, vessels and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is not leakage from the equipment). Collection systems must be designed and maintained to prevent the accumulation and recirculation of respirable silica into the workplace.

Personal Protective Equipment

Respiratory

 For limited exposure use an N95 dust mask. For prolonged exposure use an airpurifying respirator with high efficiency particulate air (HEPA) filters. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face

Wear protective eyewear (goggles, face shield, or safety glasses).

Hands

Wear appropriate gloves.

Skin/Body

Wear long sleeves and/or protective coveralls.

General Industrial Hygiene Considerations

 Do not breathe dust. Avoid contact with skin, eyes or clothing. Do not remove dusts from clothing by blowing or shaking. Do not eat, drink or smoke during work. Wash thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice.

Environmental Exposure Controls

Follow best practice for site management and disposal of waste. Dispose of in an approved landfill.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial

Hygiene

STEL = Short Term Exposure Limits are based on 15-minute exposures

NIOSH = National Institute of Occupational Safety and Health

TWAEV = Time-Weighted Average Exposure Value

OSHA = Occupational Safety and Health Administration

_ Time-Weighted Averages are based on 8h/day, 40h/week TWA exposures

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description						
Physical Form	Solid	Appearance/Description	Gray granular dry powder with an earthy odor.			
Color	Gray	Odor	Earthy			
Particulate Size	600 µ	Odor Threshold	No data available			

Revision Date: 27/April/2018

Preparation Date: 30/June/2011

Boiling Point	No data available	Melting Point/Freezing Point	No data available
Decomposition Temperature	No data available	рН	No data available
Specific Gravity/Relative Density	= 2.53 Water=1	Water Solubility	Negligible < 0.1 %
Viscosity	No data available		
Volatility			
Vapor Pressure	No data available	Vapor Density	No data available
Evaporation Rate	No data available	VOC (Wt.)	0 %
VOC (Vol.)	0 %		
Flammability			
Flash Point	No data available	UEL	No data available
LEL	No data available	Autoignition	No data available
Flammability (solid, gas)	No data available		
Environmental			
Octanol/Water Partition coefficient	No data available		

Section 10: Stability and Reactivity

Reactivity

· No dangerous reaction known under conditions of normal use.

Chemical stability

• Stable under normal temperatures and pressures.

Possibility of hazardous reactions

· Hazardous polymerization will not occur.

Conditions to avoid

· No data available

Incompatible materials

· No data available

Hazardous decomposition products

· No data available

Section 11 - Toxicological Information

Information on toxicological effects

	Components					
Titanium dioxide (0.07% TO 0.5%)	13463-67- 7	Irritation: Skin-Human • 300 μg 3 Day(s)-Intermittent • Mild irritation; Tumorigen / Carcinogen: Inhalation-Rat TCLo • 250 mg/m³ 6 Hour(s) 2 Year(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration:Tumors				
Cristobalite (0.159% TO 0.175%)	14464-46- 1	Acute Toxicity: Inhalation-Human TCLo • 16 mppcf 8 Hour(s) 17.9 Year(s)-Intermittent; Lungs, Thorax, or Respiration:Fibrosis, focal (pneumoconiosis); Lungs, Thorax, or Respiration:Dyspnea; Multi-dose Toxicity: Inhalation-Mouse TCLo • 43 mg/m³ 5 Hour(s) 9 Day(s)-Intermittent; Lungs, Thorax, or Respiration:Pleural effusion; Lungs, Thorax, or Respiration:Other changes				
Silica, amorphous (< 12.65%)	7631-86-9	Irritation: Eye-Rabbit • 25 mg 24 Hour(s) • Mild irritation				
Dispersing Agent (< 0.1395%)	Proprietary	Acute Toxicity: Ingestion/Oral-Rat LD50 • 3120 mg/kg; Behavioral:Somnolence (general depressed activity); Behavioral:Coma; Irritation: Skin-Rabbit • 500 mg 24 Hour(s) • Moderate irritation				

GHS Properties	Classification
Acute toxicity	OSHA HCS 2012 • No data available
Skin corrosion/Irritation	OSHA HCS 2012 • No data available
Serious eye damage/Irritation	OSHA HCS 2012 • No data available
Skin sensitization	OSHA HCS 2012 • No data available
Respiratory sensitization	OSHA HCS 2012 • No data available
Aspiration Hazard	OSHA HCS 2012 • No data available
Carcinogenicity	OSHA HCS 2012 • Carcinogenicity 1A
Germ Cell Mutagenicity	OSHA HCS 2012 • No data available
Toxicity for Reproduction	OSHA HCS 2012 • No data available
STOT-SE	OSHA HCS 2012 • No data available
STOT-RE	OSHA HCS 2012 • Specific Target Organ Toxicity Repeated Exposure 1

Target Organs

Inhalation

• |[206]|

Route(s) of entry/exposure

Inhalation, Skin, Eye, Ingestion

Medical Conditions Aggravated by Exposure Potential Health Effects

Any pre-existing conditions of the lungs. Disorders of the lungs.

Acute (Immediate)
Chronic (Delayed)

- Nuisance dust may affect the lungs but reactions are typically reversible.
- Chronic overexposure to dust containing respirable sized crystalline silica can cause delayed lung injury (silicosis). Inhalation of dust containing crystalline silica pulmonary diseases such as asthma and lung disorder associated with smoking.

Skin

Acute (Immediate)

• Exposure to dust may cause mechanical irritation.

Chronic (Delayed)

No data available.

Eye

Acute (Immediate)

• Excessive concentrations of nuisance dust in the workplace may reduce visibility and may cause unpleasant deposits in eyes.

Chronic (Delayed)

No data available.

Ingestion

Acute (Immediate)

 Excessive concentrations of nuisance dust in the workplace may cause mechanical irritation to mucous membranes.

Chronic (Delayed)

· No data available.

Carcinogenic Effects

• May cause cancer. IARC studies have shown sufficient evidence from animal studies to categorize crystalline silica as a group 1 carcinogen.

	Carcinogenic Effects							
	CAS	OSHA	IARC	NTP				
Formaldehyde	50-00-0	Specifically Regulated Carcinogen	Group 1-Carcinogenic	Known Human Carcinogen				
Titanium dioxide	13463-67-7	Not Listed	Group 2B-Possible Carcinogen	Not Listed				
Cristobalite	14464-46-1	Not Listed	Group 1-Carcinogenic	Not Listed				
Quartz	14808-60-7	Not Listed	Group 1-Carcinogenic	Known Human Carcinogen				

Key to abbreviations

LD = Lethal Dose TC = Toxic Concentration

Section 12 - Ecological Information

Toxicity

Material data lacking.

Persistence and degradability

Material data lacking.

Bioaccumulative potential

Material data lacking.

Mobility in Soil

Material data lacking.

Other adverse effects

· No studies have been found.

Section 13 - Disposal Considerations

Waste treatment methods

Product waste

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class (es)	Packing group	Environmental hazards
DOT	NDA	Not Regulated	NDA	NDA	NDA
TDG	NDA	Not Regulated	NDA	NDA	NDA
IATA/ICAO	NDA	Not Regulated	NDA	NDA	NDA

Special precautions for user • None specified.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture SARA Hazard Classifications • Chronic

State Right To Know					
Component	CAS	MA	NJ	PA	
Aluminum oxide	1344-28-1	Yes	Yes	Yes	

Cristobalite	14464-46-1	Yes	Yes	Yes
Diphosphoric acid, sodium salt (1:4)	7722-88-5	Yes	Yes	Yes
Formaldehyde	50-00-0	Yes	Yes	Yes
Quartz	14808-60-7	Yes	Yes	Yes
Silica, amorphous	7631-86-9	Yes	Yes	Yes
Titanium dioxide	13463-67-7	Yes	Yes	Yes
Dispersing Agent	Proprietary	Yes	No	Yes

		Inventory	
Component	CAS	Canada DSL	TSCA
Aluminum oxide	1344-28-1	Yes	Yes
Cristobalite	14464-46-1	Yes	Yes
Diphosphoric acid, sodium salt (1:4)	7722-88-5	Yes	Yes
Formaldehyde	50-00-0	Yes	Yes
Quartz	14808-60-7	Yes	Yes
Silica, amorphous	7631-86-9	Yes	Yes
Titanium dioxide	13463-67-7	Yes	Yes
Dispersing Agent	Proprietary	Yes	Yes

Canada

Canada - WHMIS - Classifications of Substances		
Dispersing Agent	Proprietary	Not Listed
• Formaldehyde	50-00-0	A, B1, D1A, D2A, D2B; B3, D1A, D2A, D2B, E (regulated under Formol)
		D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specification.)
Titanium dioxide	13463-67-7	Issues - Titanium dioxide, mixture containing on Health Canada's WHMIS Division website.)
Diphosphoric acid, sodium salt (1:4)	7722-88-5	D2B
Aluminum oxide	1344-28-1	Uncontrolled product according to WHMIS classification criteria
Cristobalite	14464-46-1	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS Division website.)
Silica, amorphous	7631-86-9	Uncontrolled product according to WHMIS classification criteria D2A (In certain cases, this

• Quartz	14808-60-7	classification does not apply. For more information, consult the section Substance Specific Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS Division website.)
Canada - WHMIS - Ingredient Disclosure List		
Dispersing Agent	Proprietary	Not Listed
Formaldehyde	50-00-0	0.1 %
Titanium dioxide	13463-67-7	Not Listed
Diphosphoric acid, sodium salt (1:4)	7722-88-5	1 %
Aluminum oxide	1344-28-1	1 %
Cristobalite	14464-46-1	1 %
Silica, amorphous	7631-86-9	1 %
• Quartz	14808-60-7	1 %

anada - CEPA - Priority Substances List		
Dispersing Agent	Proprietary	Not Listed
Formaldehyde	50-00-0	Priority Substance List 2 (substance considered toxic
Titanium dioxide	13463-67-7	Not Listed
Diphosphoric acid, sodium salt (1:4)	7722-88-5	Not Listed
Aluminum oxide	1344-28-1	Not Listed
Cristobalite	14464-46-1	Not Listed
Silica, amorphous	7631-86-9	Not Listed
• Quartz	14808-60-7	Not Listed
anada - CEPA - Schedule I - List of Toxic Substances		
Dispersing Agent	Proprietary	Not Listed
Formaldehyde	50-00-0	
Titanium dioxide	13463-67-7	Not Listed
Diphosphoric acid, sodium salt (1:4)	7722-88-5	Not Listed
Aluminum oxide	1344-28-1	Not Listed
Cristobalite	14464-46-1	Not Listed
Silica, amorphous	7631-86-9	Not Listed
• Quartz	14808-60-7	Not Listed

United States

Labor		
J.S OSHA - Process Safety Management - Highly Hazardous Ch	emicals	
Dispersing Agent	Proprietary	Not Listed
Formaldehyde	50-00-0	1000 lb TQ
Titanium dioxide	13463-67-7	Not Listed
Diphosphoric acid, sodium salt (1:4)	7722-88-5	Not Listed
Aluminum oxide	1344-28-1	Not Listed
Cristobalite	14464-46-1	Not Listed
Silica, amorphous	7631-86-9	Not Listed
• Quartz	14808-60-7	Not Listed
J.S OSHA - Specifically Regulated Chemicals		
Dispersing Agent	Proprietary	Not Listed
		2 ppm STEL (See 29 CFR

Formaldehyde	50-00-0	1910.1048, 15 min); 0.5 ppn Action Level (See 29 CFR
		1910.1048); 0.75 ppm TWA
- Titanium diavida	12462 67 7	(See 29 CFR 1910.1048)
• Titanium dioxide	13463-67-7	Not Listed Not Listed
Diphosphoric acid, sodium salt (1:4) Aluminum oxide	7722-88-5	
	1344-28-1	Not Listed
• Cristobalite	14464-46-1	Not Listed
• Silica, amorphous	7631-86-9	Not Listed
• Quartz	14808-60-7	Not Listed
Environment		
J.S CAA (Clean Air Act) - 1990 Hazardous Air Pollutants		
Dispersing Agent	Proprietary	Not Listed
• Formaldehyde	50-00-0	
Titanium dioxide	13463-67-7	Not Listed
Diphosphoric acid, sodium salt (1:4)	7722-88-5	Not Listed
Aluminum oxide	1344-28-1	Not Listed
Cristobalite	14464-46-1	Not Listed
Silica, amorphous	7631-86-9	Not Listed
• Quartz	14808-60-7	Not Listed
J.S CERCLA/SARA - Hazardous Substances and their Reportable Quantities		
Dispersing Agent	Proprietary	Not Listed
Formaldehyde	50-00-0	100 lb final RQ; 45.4 kg fina RQ
Titanium dioxide	13463-67-7	Not Listed
Diphosphoric acid, sodium salt (1:4)	7722-88-5	Not Listed
Aluminum oxide	1344-28-1	Not Listed
Cristobalite	14464-46-1	Not Listed
Silica, amorphous	7631-86-9	Not Listed
• Quartz	14808-60-7	Not Listed
J.S CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs		
Dispersing Agent	Proprietary	Not Listed
Formaldehyde	50-00-0	100 lb EPCRA RQ
Titanium dioxide	13463-67-7	Not Listed
Diphosphoric acid, sodium salt (1:4)	7722-88-5	Not Listed
Aluminum oxide	1344-28-1	Not Listed
Cristobalite	14464-46-1	Not Listed
Silica, amorphous	7631-86-9	Not Listed
• Quartz	14808-60-7	Not Listed
J.S CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs		
Dispersing Agent	Proprietary	Not Listed
Formaldehyde	50-00-0	500 lb TPQ
Titanium dioxide	13463-67-7	Not Listed
Diphosphoric acid, sodium salt (1:4)	7722-88-5	Not Listed
Aluminum oxide	1344-28-1	Not Listed
Cristobalite	14464-46-1	Not Listed
Silica, amorphous	7631-86-9	Not Listed
• Quartz	14808-60-7	Not Listed
J.S CERCLA/SARA - Section 313 - Emission Reporting		
Dispersing Agent	Proprietary	Not Listed

Formaldehyde	50-00-0	1 % de minimis ncentration
Titanium dioxide	13463-67-7 No	ot Listed
Diphosphoric acid, sodium salt (1:4)	7722-88-5 No	ot Listed
Aluminum oxide	1344-28-1	0 % de minimis ncentration (fibrous forms)
Cristobalite		ot Listed
Silica, amorphous	7631-86-9 No	ot Listed
• Quartz	14808-60-7 No	ot Listed
U.S RCRA (Resource Conservation & Recovery Act) - Basis for	or Listing - Appendix VII	
Dispersing Agent		ot Listed
Formaldehyde	50-00-0 K0	cluded in waste streams: 09, K010, K038, K040, 56, K157
Titanium dioxide	13463-67-7 No	ot Listed
Diphosphoric acid, sodium salt (1:4)	7722-88-5 No	ot Listed
Aluminum oxide	1344-28-1 No	ot Listed
Cristobalite	14464-46-1 No	ot Listed
Silica, amorphous	7631-86-9 No	ot Listed
• Quartz	14808-60-7 No	ot Listed
U.S RCRA (Resource Conservation & Recovery Act) - Hazardo	ous Constituents - Appendix VIII to 40 CF	R 261
Dispersing Agent	Proprietary No	ot Listed
Formaldehyde	50-00-0 wa	aste number U122
Titanium dioxide	13463-67-7 No	ot Listed
Diphosphoric acid, sodium salt (1:4)	7722-88-5 No	ot Listed
Aluminum oxide	1344-28-1 No	ot Listed
Cristobalite	14464-46-1 No	ot Listed
Silica, amorphous	7631-86-9 No	ot Listed
• Quartz	14808-60-7 No	ot Listed
U.S RCRA (Resource Conservation & Recovery Act) - U Serie Characteristics	s Wastes - Acutely Toxic Wastes & Othe	r Hazardous
Dispersing Agent	Proprietary No	ot Listed
• Formaldehyde	50-00-0 wa	aste number U122
Titanium dioxide	13463-67-7 No	ot Listed
Diphosphoric acid, sodium salt (1:4)	7722-88-5 No	ot Listed
Aluminum oxide	1344-28-1 No	ot Listed
Cristobalite	14464-46-1 No	ot Listed
Silica, amorphous	7631-86-9 No	ot Listed
• Quartz	14808-60-7 No	ot Listed

United States - California

Environment U.S California - Proposition 65 - Carcinogens List		
Dispersing Agent	Proprietary	Not Listed
Formaldehyde	50-00-0	carcinogen, initial date 1/1/88 (gas)
Titanium dioxide	13463-67-7	carcinogen, initial date 9/2/11 (airborne, unbound particles of respirable size)
Diphosphoric acid, sodium salt (1:4)	7722-88-5	Not Listed
Aluminum oxide	1344-28-1	Not Listed
Cristobalite	14464-46-1	Not Listed

Silica, amorphous	7631-86-9 Not Listed
• Quartz	carcinogen, initial date 10/1/8 14808-60-7 (airborne particles of respirable size)
U.S California - Proposition 65 - No Significant Risk Levels (NSRL)	
Dispersing Agent	Proprietary Not Listed
Formaldehyde	50-00-0 40 μg/day NSRL (gas)
Titanium dioxide	13463-67-7 Not Listed
Diphosphoric acid, sodium salt (1:4)	7722-88-5 Not Listed
Aluminum oxide	1344-28-1 Not Listed
Cristobalite	14464-46-1 Not Listed
Silica, amorphous	7631-86-9 Not Listed
• Quartz	14808-60-7 Not Listed

United States - Pennsylvania

Dispersing Agent	Proprietary	
Formaldehyde	50-00-0	
Titanium dioxide	13463-67-7	Not Listed
Diphosphoric acid, sodium salt (1:4)	7722-88-5	Not Listed
· Aluminum oxide	1344-28-1	
Cristobalite	14464-46-1	Not Listed
Silica, amorphous	7631-86-9	Not Listed
• Quartz	14808-60-7	Not Listed
.S Pennsylvania - RTK (Right to Know) - Special Hazardous	s Substances	
Dispersing Agent	Proprietary	Not Listed
Formaldehyde	50-00-0	
Titanium dioxide	13463-67-7	Not Listed
Diphosphoric acid, sodium salt (1:4)	7722-88-5	Not Listed
Aluminum oxide	1344-28-1	Not Listed
	14464-46-1	Not Listed
Cristobalite		
 Cristobalite Silica, amorphous	7631-86-9	Not Listed

Other Information

 WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information

Revision Date

27/April/2018

Last Revision Date

26/December/2014

Preparation Date

30/June/2011

Disclaimer/Statement of Liability

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. Reno Refractories MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, INCLUDING, BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR

OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF

TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key to abbreviationsNDA = No data available