Safety Data Sheet



Section 1: Identification

Due du et identifien	
Product identifier	
Product Name	・LiquiBond 50
Product Code	• 181200
Relevant identified uses o	of the substance or mixture and uses advised against
Recommended use	Refractory applications
Details of the supplier of t	the safety data sheet
Manufacturer	Reno Refractories, Inc.
	601 Reno Drive Morris, AL 35116 United States www.renorefractories.com sales@renorefractories.com
Telephone (General)	• 205-647-0240
Emergency telephone nu	mber
Manufacturer	• 1-800-262-8200 - CHEMTREC

Section 2: Hazard Identification

United States (US) According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

 Carcinogenicity 1A Specific Target Organ Toxicity Repeated Exposure 2

Label elements OSHA HCS 2012

OSHA HCS 2012

DANGER



Hazard statements • May cause cancer.

May cause damage to organs through prolonged or repeated exposure

Precautionary statements

Prevention • Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Do not breathe dust.

	Wear protective gloves/protective clothing/eye protection/face protection.
Resp	 onse • IF exposed or concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell.
Storage/Disp	bosal • Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.
Other hazards	
OSHA HCS 2012	 Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.
Canada According to: WHMIS	
Classification of the	substance or mixture
WHMIS	Other Toxic Effects - D2B

Label elements

Other hazards

WHMIS

Other Toxic Effects - D2B

WHMIS

WHMIS

 In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients

Substances

• Material does not meet the criteria of a substance.

Mixtures

	Composition					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments	
Alumina Silicate	Proprietary	46.45% TO 52.13%	NDA	OSHA HCS 2012: STOT RE 2 (Lungs)	NDA	
Aluminum oxide	CAS:1344-28-1	16.29% TO 24%	NDA	OSHA HCS 2012: Not Classified	NDA	
Silica, amorphous	CAS:7631-86-9	0% TO 15.77%	NDA	OSHA HCS 2012: Not Classified	NDA	
Cristobalite	CAS: 14464-46- 1	4.605% TO 8.626%	NDA	OSHA HCS 2012: Carc. 1A	NDA	
Aluminum(III) silicate (2:1)	CAS:1302-76-7	4.25% TO 8.55%	NDA	OSHA HCS 2012: STOT RE 2 (Lungs)	NDA	
Chemical/Setting Agent 1	Proprietary	< 4%	NDA	OSHA HCS 2012: Not Classified	NDA	
Quartz	CAS: 14808-60- 7	0.25% TO 0.9%	NDA	OSHA HCS 2012: Carc. 1A; STOT RE 1 (Lungs)	NDA	
Amorphous/fused silica	CAS :60676-86- 0	< 0.68%	NDA	OSHA HCS 2012: Not classified	NDA	

Titanium dioxide	CAS :13463-67- 7	0.05% TO 0.45%	NDA	OSHA HCS 2012: Carc. 2	NDA
Iron oxide	CAS:1309-37-1	< 0.34%	NDA	OSHA HCS 2012: Not classified	NDA
Sodium hydroxide	CAS:1310-73-2	< 0.085%	NDA	OSHA HCS 2012: Exposure limits	NDA
Calcium oxide	CAS:1305-78-8	< 0.085%	NDA	OSHA HCS 2012: Exposure limits	NDA

Section 4: First-Aid Measures

Description of first aid measures

Inhalation	 Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. Get medical attention immediately. Move victim to fresh air.
Skin	 In case of contact with substance, immediately flush skin with running water for at least 20 minutes. If skin irritation occurs: Get medical advice/attention.
Еуе	 In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.
Ingestion	 Rinse mouth. Do not give anything by mouth to an unconscious person. Get medical attention immediately.
Most important symptor	ms and effects, both acute and delayed
	 Refer to Section 11 - Toxicological Information.
Indication of any immed	liate medical attention and special treatment needed
Notes to Physician	 All treatments should be based on observed signs and symptoms of distress in

Notes to Physician	All treatments should be based on observed signs and symptoms of distress in
	thepatient. Consideration should be given to the possibility that overexposure to
	materialsother than this product may have occurred.

Section 5: Fire-Fighting Measures

Extinguishing media

0 0		
Suitable Extinguishing Media	•	Material is non-combustible. In case of fire use media as appropriate for surrounding fire.
Unsuitable Extinguishing Media	•	None known.
Special hazards arising f	rc	om the substance or mixture
Unusual Fire and Explosion Hazards	•	None known.
Hazardous Combustion Products	•	None known.
Advice for firefighters		

Wear positive pressure self-contained breathing apparatus (SCBA). • Structural firefighters' protective clothing will only provide limited protection. Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions	 Isolate hazard area and deny entry to unauthorized and/or unprotected personnel. Do not touch or walk through spilled material. Ensure adequate ventilation to remove vapors, fumes, dust etc.
Emergency Procedures	 Ventilate closed spaces before entering. Isolate hazard area and deny entry to unauthorized and/or unprotected personnel.
Preparation Date: 27/February/2017	Format: GHS Language: English (US)

Environmental precautions

• No specific actions or treatments recommended related to exposure to this material.

Methods and material for containment and cleaning up

Avoid generating dust.
 FOR SMALL SPILLS: Clean with a vacuum with a filtration system sufficient to remove and prevent recirculation of crystalline silica (a vacuum equipped with a high-efficiency particulate air (HEPA) filter is recommended).
 FOR LARGE SPILLS: Use a fine spray or mist to control dust creation and carefully scoop or shovel into clean dry container for later reuse or disposal.
 If, an appropriate vacuum is unavailabe, only wet-clean-up methods should be used (i.e. misting). Moisture should be added as necessary to reduce exposure to airborne respirable silica dust.

Section 7 - Handling and Storage

Precautions for safe handling

Handling

 Do not breathe dust. Wash thoroughly after handling. Do not use in areas without adequate ventilation. Avoid contact with skin, eyes, and clothing. Minimize dust generation and accumulation. Use good safety and industrial hygiene practices. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Wear long sleeves and/or protective coveralls. Contaminated clothing must be vacuumed before removal. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage

• Store in a covered location. Keep container closed. Keep from freezing. Storage and work area should be periodically cleaned to minimize dust accumulation.

Section 8 - Exposure Controls/Personal Protection

Control parameters

			Exposure Limits	/Guidelines		
	Result	ACGIH	Canada Ontario	Canada Quebec	Mexico	NIOSH
Silica, amorphous (7631-86-9)	TWAs	Not established	Not established	Not established	Not established	6 mg/m3 TWA
	STELs	Not established	Not established	Not established	20 mg/m3 STEL [PPT- CT] (as Ti)	Not established
Titanium dioxide (13463-67-7)	TWAs	10 mg/m3 TWA	10 mg/m3 TWA	10 mg/m3 TWAEV (containing no Asbestos and <1% Crystalline silica, total dust)	10 mg/m3 TWA VLE- PPT (as Ti)	Not established
Sodium hydroxide (1310-73-2)	Ceilings	2 mg/m3 Ceiling	2 mg/m3 Ceiling	2 mg/m3 Ceiling	2 mg/m3 Ceiling	2 mg/m3 Ceiling
Calcium oxide (1305-78-8)	TWAs	2 mg/m3 TWA	2 mg/m3 TWA	2 mg/m3 TWAEV	2 mg/m3 TWA VLE- PPT	2 mg/m3 TWA
Quartz (14808-60-7)	TWAs	0.025 mg/m3 TWA (respirable particulate matter)	0.10 mg/m3 TWA (designated substances regulation, respirable, listed under Silica, crystalline)	0.1 mg/m3 TWAEV (respirable dust)	0.1 mg/m3 TWA VLE- PPT (respirable fraction)	0.05 mg/m3 TWA (respirable dust)
	STELs	Not established	Not established	Not established	10 mg/m3 STEL [PPT- CT] (as Fe)	Not established

Iron oxide (1309-37-1)	TWAs			mg/m3 TWA respirable)		ng/m3 TWAEV ist and fume, as ; 10 mg/m3 /AEV (containing Asbestos and % Crystalline ca, regulated der Rouge, total st)	5 mg/m3 TWA VLE- PPT	5 mg/m3 TWA (dust and fume, as Fe)
Amorphous/fused silica (60676-86-0)	TWAs			mg/m3 TWA spirable)	(co Asl Cry	mg/m3 TWAEV ntaining no bestos and <1% /stalline silica, pirable dust)	0.1 mg/m3 TWA VLE- PPT; 10 mg/m3 TWA VLE-PPT (inhalable particulate); 3 mg/m3 TWA VLE-PPT (respirable particulate)	Not established
Chemical/Setting Agent 1 (Proprietary)	TWAs			ng/m3 TWA alable)		mg/m3 TWAEV me, as Mg)	10 mg/m3 TWA VLE- PPT (fume, as Mg)	Not established
Cristobalite (14464-46-1)	TWAs	0.025 mg/m3 TWA (respirable particulate matter) (de sub reg liste				5 mg/m3 TWAEV spirable dust)	0.05 mg/m3 TWA VLE-PPT (respirable fraction)	0.05 mg/m3 TWA (respirable dust)
Aluminum oxide (1344-28-1)	TWAs	Not established Not		established	(co Asl Cry	mg/m3 TWAEV ntaining no bestos and <1% /stalline silica, total st, as AI)	10 mg/m3 TWA VLE- PPT	Not established
		Ex	pos	ure Limits/Gui	del	ines (Con't.)		
				Result			OSHA	
Titanium dioxide (13463-67-7)				TWAs		15 mg/m3 TWA (to	otal dust)	
Sodium hydroxide (1310-73-2)			TWAs		2 mg/m3 TWA			
Calcium oxide (1305-78-8)			TWAs		5 mg/m3 TWA			
Quartz (14808-60-7)			TWAs		50 μg/m3 TWA			
Iron oxide (1309-37-1)			TWAs		10 mg/m3 TWA (fume); 15 mg/m3 TWA (total dust, listed under Rouge); 5 mg/m3 TWA (respirable fraction, listed under Rouge)			
Chemical/Setting Agent 1 (Proprietary)			TWAs 15 mg/m3		15 mg/m3 TWA (fu	5 mg/m3 TWA (fume, total particulate)		
Cristobalite (14464-46-1)			TWAs		50 μg/m3 TWA			
Aluminum oxide (1344-28-1)				TWAs		15 mg/m3 TWA (to	otal dust); 5 mg/m3 TW	A (respirable fraction)

Exposure Control Notations

Canada Ontario

•Cristobalite (14464-46-1): Designated Substances: (0.05 mg/m3 TWA (respirable fraction, listed under Silica, crystalline))

•Quartz (14808-60-7): Designated Substances: (0.10 mg/m3 TWA (respirable fraction, listed under Silica, crystalline))

Canada Quebec

•Quartz (14808-60-7): Carcinogens: (C2 carcinogen - effect suspected in humans)

ACGIH

•Cristobalite (14464-46-1): Carcinogens: (A2 - Suspected Human Carcinogen)

•Quartz (14808-60-7): Carcinogens: (A2 - Suspected Human Carcinogen)

• Titanium dioxide (13463-67-7): Carcinogens: (A4 - Not Classifiable as a Human Carcinogen)

•Chemical/Setting Agent 1 (Proprietary): Carcinogens: (A4 - Not Classifiable as a Human Carcinogen)

• Iron oxide (1309-37-1): Carcinogens: (A4 - Not Classifiable as a Human Carcinogen)

Exposure Limits Supplemental

OSHA

•Silica, amorphous (7631-86-9): Mineral Dusts: (20 mppcf TWA; (80)/(% SiO2) mg/m3 TWA)

•Cristobalite (14464-46-1): **Mineral Dusts:** ((1/2)(30)/(%SiO2 + 2) mg/m3 TWA, total dust; (1/2)(250)/(%SiO2 + 5) mppcf TWA, respirable fraction; (1/2)(10)/(%SiO2 + 2) mg/m3 TWA, respirable fraction)

•Quartz (14808-60-7): Mineral Dusts: ((250)/(%SiO2 + 5) mppcf TWA, respirable fraction; (10)/(%SiO2 + 2) mg/m3 TWA, respirable fraction) •Amorphous/fused silica (60676-86-0): Mineral Dusts: ((80)/(% SiO2) mg/m3 TWA; 20 mppcf TWA)

ACGIH

•Cristobalite (14464-46-1): TLV Basis - Critical Effects: (lung cancer; pulmonary fibrosis)

•Quartz (14808-60-7): TLV Basis - Critical Effects: (lung cancer; pulmonary fibrosis)

• Titanium dioxide (13463-67-7): **TLV Basis - Critical Effects:** (lower respiratory tract irritation)

•Chemical/Setting Agent 1 (Proprietary): TLV Basis - Critical Effects: (metal fume fever; upper respiratory tract irritation)

•Iron oxide (1309-37-1): TLV Basis - Critical Effects: (pneumoconiosis)

•Sodium hydroxide (1310-73-2): TLV Basis - Critical Effects: (eye, skin and upper respiratory tract irritation)

•Calcium oxide (1305-78-8): TLV Basis - Critical Effects: (upper respiratory tract irritation)

Exposure controls

Engineering Measures/Controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Ensure that dust handling systems (such as exhaust ducts, dust collectors, vessels and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is not leakage from the equipment). Collection systems must be designed and maintained to prevent the accumalation and recirculation of respirable silica into the workplace.					
Personal Protective Equipme	nt					
Respiratory	 For limited exposure use an N95 dust mask. For prolonged exposure use an air- purifying respirator with high efficiency particulate air (HEPA) filters. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced. 					
Eye/Face	 Wear protective eyewear (goggles, face shield, or safety glasses). 					
Hands	Wear appropriate gloves.					
Skin/Body	Wear long sleeves and/or protective coveralls.					
General Industrial Hygiene Considerations	 Do not breathe dust. Avoid contact with skin, eyes or clothing. Do not remove dusts from clothing by blowing or shaking. Do not eat, drink or smoke during work. Wash thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice. 					
Environmental Exposure Controls	 Follow best practice for site management and disposal of waste. Dispose of in an approved landfill. 					
Key to abbreviations						
ACGIH = American Conference of Gove Hygiene	rnmental Industrial STEL = Short Term Exposure Limits are based on 15-minute exposures					
NIOSH = National Institute of Occupation	onal Safety and Health TWAEV = Time-Weighted Average Exposure Value					

WA	_ Time-Weighted Averages are based on 8h/day, 40h/week
	exposures

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description			
Physical Form	Solid	Appearance/Description	Gray granular dry powder with ar earthy odor.
Color	Gray	Odor	Earthy
Particulate Size	600 µ	Odor Threshold	No data available
General Properties	-		
Boiling Point	No data available	Melting Point/Freezing Point	No data available
Decomposition Temperature	No data available	рН	Not relevant
Specific Gravity/Relative Density	= 2.53 Water=1	Water Solubility	Negligible < 0.1 %
Viscosity	No data available		
Volatility	-		
Vapor Pressure	No data available	Vapor Density	No data available
Evaporation Rate	No data available		
Flammability	-	<u>.</u>	
Flash Point	Not relevant	UEL	Not relevant
LEL	Not relevant	Autoignition	No data available
Flammability (solid, gas)	No data available		
Environmental	-	÷	•
Octanol/Water Partition coefficient	No data available		

Section 10: Stability and Reactivity

Reactivity

• No dangerous reaction known under conditions of normal use.

Chemical stability

• Stable under normal temperatures and pressures.

Possibility of hazardous reactions

Hazardous polymerization will not occur.
 Conditions to avoid

 No data available

 Incompatible materials

 No data available

 Hazardous decomposition products

 No data available

Section 11 - Toxicological Information

Information on toxicological effects

		Components
Iron oxide (< 1309- 0.34%)		Irritation: Eye-Rabbit • 25 mg 24 Hour(s) • Mild irritation
		Tumorigen / Carcinogen: Inhalation-Rat TCLo • 250 mg/m ³ 6 Hour(s) 2 Year(s)-Intermittent;
		Respiration:Emphysema; Biochemical:Enzyme inhibition, induction, or change in blood or tissue levels:Multiple enzyme effects; Biochemical:Metabolism (intermediary):Effect on inflammation or mediation of
Sodium hydroxide (< 0.085%)	1310- 73-2	Acute Toxicity: Skin-Rabbit TCLo • 25 pph; Behavioral:Food intake (animal); Nutritional and Gross Metabolic:Changes in Chemistry or Temperature:Body temperature increase; Skin and Appendages:After topical exposure:Primary irritation; Irritation: Eye-Rabbit • 1 mg 30 Second(s)-Rinse • Severe irritation; Skin-Rabbit • 500 mg 24 Hour(s) • Severe irritation
Calcium oxide 1305- (< 0.085%) 78-8 Acute Toxicity: Intrape		Acute Toxicity: Intraperitoneal-Mouse LD50 • 3059 mg/kg

GHS Properties	Classification
Acute toxicity	OSHA HCS 2012 • Data lacking
Skin corrosion/Irritation	OSHA HCS 2012 • Data lacking
Serious eye damage/Irritation	OSHA HCS 2012 • Data lacking
Skin sensitization	OSHA HCS 2012 • Data lacking
Respiratory sensitization	OSHA HCS 2012 • Data lacking
Aspiration Hazard	OSHA HCS 2012 • Data lacking
Carcinogenicity	OSHA HCS 2012 • Carcinogenicity 1A
Germ Cell Mutagenicity	OSHA HCS 2012 • Data lacking
Toxicity for Reproduction	OSHA HCS 2012 • Data lacking
STOT-SE	OSHA HCS 2012 • Data lacking
STOT-RE	OSHA HCS 2012 • Specific Target Organ Toxicity Repeated Exposure 2

Target Organs

Lungs

•

• Inhalation, Skin, Eye, Ingestion

• Any pre-existing conditions of the lungs. Disorders of the lungs.

• Nuisance dust may affect the lungs but reactions are typically reversible.

diseases such as asthma and lung disorder associated with smoking.

Chronic overexposure to dust containing respirable sized crystalline silica can cause

delayed lung injury (silicosis). Inhalation of dust containing crystalline silica pulmonary

Medical Conditions Aggravated by Exposure Potential Health Effects

Route(s) of entry/exposure

Inhalation

Acute (Immediate)

Chronic (Delayed)

Skin

Acute (Immediate) Chronic (Delayed)

- Exposure to dust may cause mechanical irritation.
- No data available.

Eye	
Acute (Immediate)	 Excessive concentrations of nuisance dust in the workplace may reduce visibility and may cause unpleasant deposits in eyes.
Chronic (Delayed)	No data available.
Ingestion	
Acute (Immediate)	 Excessive concentrations of nuisance dust in the workplace may cause mechanical irritation to mucous membranes.
Chronic (Delayed)	No data available.
Carcinogenic Effects	 May cause cancer. IARC studies have shown sufficient evidence from animal studies to categorize crystalline silica as a group 1 carcinogen.

Carcinogenic Effects				
CAS IARC			NTP	
Titanium dioxide	13463-67-7 Group 2B-Possible Carcinogen		Not Listed	
Quartz	14808-60-7	Group 1-Carcinogenic	Known Human Carcinogen	
Cristobalite	14464-46-1	Group 1-Carcinogenic	Not Listed	

Key to abbreviations

TC = Toxic Concentration

Section 12 - Ecological Information

Toxicity

 Material data lacking. Persistence and degradability · Material data lacking. **Bioaccumulative potential** Material data lacking. Mobility in Soil • Material data lacking. Other adverse effects No studies have been found.

Section 13 - Disposal Considerations

Waste treatment methods

- Product waste
- Dispose of content and/or container in accordance with local, regional, national, and/or • international regulations.
- Packaging waste
- Dispose of content and/or container in accordance with local, regional, national, and/or • international regulations.

Section 14 - Transport Information

	UN	UN proper shipping	Transport hazard class	Packing	Environmental
	number	name	(es)	group	hazards
DOT	NDA	Not Regulated	NDA	NDA	NDA

TDG	NDA	Not Regulated	NDA	NDA	NDA
IATA/ICAO	NDA	Not Regulated	NDA	NDA	NDA

Special precautions for user • None specified.

· No data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture SARA Hazard Classifications • Chronic

	State Right To Know				
Component	CAS	MA	NJ	PA	
Aluminum oxide	1344-28-1	Yes	Yes	Yes	
Aluminum(III) silicate (2:1)	1302-76-7	No	No	No	
Amorphous/fused silica	60676-86-0	Yes	Yes	No	
Calcium oxide	1305-78-8	Yes	Yes	Yes	
Cristobalite	14464-46-1	Yes	Yes	Yes	
Iron oxide	1309-37-1	Yes	Yes	Yes	
Chemical/Setting Agent 1	Proprietary	Yes	Yes	Yes	
Alumina Silicate	Proprietary	No	No	No	
Quartz	14808-60-7	Yes	Yes	Yes	
Silica, amorphous	7631-86-9	Yes	Yes	Yes	
Sodium hydroxide	1310-73-2	Yes	Yes	Yes	
Titanium dioxide	13463-67-7	Yes	Yes	Yes	

Inventory				
Component	CAS	Canada DSL	TSCA	
Aluminum oxide	1344-28-1	Yes	Yes	
Aluminum(III) silicate (2:1)	1302-76-7	Yes	No	
Amorphous/fused silica	60676-86-0	Yes	Yes	
Calcium oxide	1305-78-8	Yes	Yes	
Cristobalite	14464-46-1	Yes	Yes	
Iron oxide	1309-37-1	Yes	Yes	
Chemical/Setting Agent 1	Proprietary	Yes	Yes	
Alumina Silicate	Proprietary	Yes	Yes	
Quartz	14808-60-7	Yes	Yes	
Silica, amorphous	7631-86-9	Yes	Yes	
Sodium hydroxide	1310-73-2	Yes	Yes	
Titanium dioxide	13463-67-7	Yes	Yes	

Canada

Ganada		
Labor Canada - WHMIS 1988 - Classifications of Substances		
Alumina Silicate	Proprietary	Not Listed
Calcium oxide	1305-78-8	E
Iron oxide	1309-37-1	Uncontrolled product according to WHMIS classification criteria
Chemical/Setting Agent 1	Proprietary	Uncontrolled product according to WHMIS classification criteria
Sodium hydroxide	1310-73-2	E (including 0.04% in aqueous solution, 0.04N, 0.08%, 0.4% in aqueous solution, 2%, 2.5%, 4% in aqueous solution, 5%, 10%, 16%, 20%, 40%, 50% in aqueous solution, 8.7N)
• Titanium dioxide	13463-67-7	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Titanium dioxide, mixture containing on Health Canada's WHMIS Division website.)
Aluminum oxide	1344-28-1	Uncontrolled product according to WHMIS classification criteria
• Cristobalite	14464-46-1	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS Division website.)
Silica, amorphous	7631-86-9	Uncontrolled product according to WHMIS classification criteria
Amorphous/fused silica	60676-86-0	Uncontrolled product according to WHMIS classification criteria
• Quartz	14808-60-7	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS Division website.)
Aluminum(III) silicate (2:1)	1302-76-7	Not Listed
Canada - WHMIS 1988 - Ingredient Disclosure List		
Alumina Silicate	Proprietary	Not Listed
Calcium oxide	1305-78-8	1 %
Iron oxide	1309-37-1	1 %
Chemical/Setting Agent 1	Proprietary	1 %

Sodium hydroxide	1310-73-2	1 %
Titanium dioxide	13463-67-7	Not Listed
Aluminum oxide	1344-28-1	1 %
Cristobalite	14464-46-1	1 %
Silica, amorphous	7631-86-9	1 %
Amorphous/fused silica	60676-86-0	1 %
• Quartz	14808-60-7	1 %
Aluminum(III) silicate (2:1)	1302-76-7	Not Listed

United States

Environment		
U.S CERCLA/SARA - Hazardous Substances and their Reportable Quantities Alumina Silicate 	Proprietary	Not Listed
Calcium oxide	1305-78-8	Not Listed
Iron oxide	1309-37-1	Not Listed
Chemical/Setting Agent 1	Proprietary	Not Listed
Sodium hydroxide	1310-73-2	1000 lb final RQ; 454 kg final RQ
Titanium dioxide	13463-67-7	Not Listed
Aluminum oxide	1344-28-1	Not Listed
Cristobalite	14464-46-1	Not Listed
Silica, amorphous	7631-86-9	Not Listed
Amorphous/fused silica	60676-86-0	Not Listed
• Quartz	14808-60-7	Not Listed
Aluminum(III) silicate (2:1)	1302-76-7	Not Listed
U.S CERCLA/SARA - Section 313 - Emission Reporting		
Alumina Silicate	Proprietary	Not Listed
Calcium oxide	1305-78-8	Not Listed
Iron oxide	1309-37-1	Not Listed
Chemical/Setting Agent 1	Proprietary	Not Listed
Sodium hydroxide	1310-73-2	Not Listed
Titanium dioxide	13463-67-7	Not Listed
Aluminum oxide	1344-28-1	1.0 % de minimis concentration (fibrous forms)
Cristobalite	14464-46-1	Not Listed
Silica, amorphous	7631-86-9	Not Listed
Amorphous/fused silica	60676-86-0	Not Listed
• Quartz	14808-60-7	Not Listed
Aluminum(III) silicate (2:1)	1302-76-7	Not Listed

United States - California

Environment U.S California - Proposition 65 - Carcinogens List		
Alumina Silicate	Proprietary Not Listed	
Calcium oxide	1305-78-8 Not Listed	
Iron oxide	1309-37-1 Not Listed	
Chemical/Setting Agent 1	Proprietary Not Listed	
Sodium hydroxide	1310-73-2 Not Listed	
Titanium dioxide	carcinogen, 9/2/2011 13463-67-7 (airborne, unbound particle respirable size)	s of
Aluminum oxide	1344-28-1 Not Listed	

Cristobalite	14464-46-1 Not Listed
Silica, amorphousAmorphous/fused silica	7631-86-9 Not Listed 60676-86-0 Not Listed
Quartz Aluminum(III) silicate (2:1)	14808-60-7 Not Listed 1302-76-7 Not Listed

United States - Pennsylvania

- Alumina Cilicata	al Hazard List	NotListad
Alumina Silicate	Proprietary	Not Listed
Calcium oxide	1305-78-8	Not Listed
Iron oxide	1309-37-1	Not Listed
Chemical/Setting Agent 1	Proprietary	Not Listed
Sodium hydroxide	1310-73-2	
Titanium dioxide	13463-67-7	Not Listed
Aluminum oxide	1344-28-1	
Cristobalite	14464-46-1	Not Listed
 Silica, amorphous 	7631-86-9	Not Listed
 Amorphous/fused silica 	60676-86-0	Not Listed
• Quartz	14808-60-7	Not Listed
Aluminum(III) silicate (2:1)	1302-76-7	Not Listed

Other Information

• WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information

Revision Date Last Revision Date Preparation Date Disclaimer/Statement of Liability	 27/February/2017 27/February/2017 27/February/2017 27/February/2017 The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. Reno Refractories MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Key to abbreviations	

NDA = No data available