Safety Data Sheet



Section 1: Identification

Product identifier

Product Name • Reno NC 60 AZR

Product Code • 188700

Relevant identified uses of the substance or mixture and uses advised against

Recommended use • Refractory applications

Details of the supplier of the safety data sheet

Manufacturer • Reno Refractories, Inc.

P O Box 201 Morris, AL 35116 United States

www.renorefractories.com sales@renorefractories.com

Telephone (General) • 205-647-0240

Emergency telephone number

Manufacturer • 1-800-262-8200 - CHEMTREC

Section 2: Hazard Identification

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012 • Carcinogenicity 1A

Specific Target Organ Toxicity Repeated Exposure 1

Label elements
OSHA HCS 2012

DANGER



Hazard statements • May cause cancer.

Causes damage to organs - Lungs through prolonged or repeated exposure via

Inhalation

Precautionary statements

Prevention • Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

Response • IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Storage/Disposal • Dispose of content and/or container in accordance with local, regional, national, and/or

international regulations.

Other hazards

• Under United States Regulations (29 CFR 1910.1200 - Hazard Communication

Standard), this product is considered hazardous.

Canada

According to: WHMIS

Classification of the substance or mixture

WHMISOther Toxic Effects - D2A

Other Toxic Effects - D2B

Label elements

WHMIS .

(T)

• Other Toxic Effects - D2A

Other Toxic Effects - D2B

Other hazards

WHMIS
 In Canada, the product mentioned above is considered hazardous under the

Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients

Substances

Material does not meet the criteria of a substance.

Mixtures

	Composition						
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive			
Alumina Silicate	Proprietary	45.53% TO 50.25%	NDA	OSHA HCS 2012: STOT RE 2 (Lungs)			
Aluminum oxide	CAS:1344-28-1	11.82% TO 15%	NDA	OSHA HCS 2012: Not Classified			
Silica, amorphous	CAS:7631-86-9	< 14.75%	NDA	OSHA HCS 2012: Not Classified			
Zirconium(IV) silicate (1:1)	CAS:14940-68-2	7.84% TO 14%	NDA	OSHA HCS 2012: Not Classified			
Aluminum(III) silicate (2:1)	CAS:1302-76-7	4.25% TO 8.55%	NDA	OSHA HCS 2012: STOT RE 2 (Lungs)			
Amorphous silica fume	CAS:69012-64-2	1.6% TO 4%	NDA	OSHA HCS 2012: STOT RE 1 (Lungs)			
Quartz	CAS:14808-60-7	0.258% TO 0.972%	NDA	OSHA HCS 2012: Carc. 1A; STOT RE 1 (Lungs)			
Titanium dioxide	CAS:13463-67-7	0.05% TO 0.45%	NDA	OSHA HCS 2012: Carc. 2			
Cristobalite	CAS:14464-46-1	0.174% TO 0.201%	NDA	OSHA HCS 2012: Carc. 1A			
Chemical 1	Proprietary	< 0.0588%	NDA	OSHA HCS 2012: Exposure limit(s)			

Section 4: First-Aid Measures

Description of first aid measures

Inhalation

 Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. Get medical attention immediately. Move victim to fresh air.

Skin

In case of contact with substance, immediately flush skin with running water for at least 20 minutes. If skin irritation occurs: Get medical advice/attention.

Eye

In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.

Ingestion

Rinse mouth. Do not give anything by mouth to an unconscious person. Get medical attention immediately.

Most important symptoms and effects, both acute and delayed

Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

 All treatments should be based on observed signs and symptoms of distress in thepatient. Consideration should be given to the possibility that overexposure to materialsother than this product may have occurred.

Section 5: Fire-Fighting Measures

Extinguishing media

Suitable Extinguishing Media •

Material is non-combustible. In case of fire use media as appropriate for surrounding fire.

Unsuitable Extinguishing

Media

None known.

Special hazards arising from the substance or mixture

Unusual Fire and Explosion

Hazards

· None known.

Hazardous Combustion Products

None known.

Advice for firefighters

 Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection. Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions

 Isolate hazard area and deny entry to unauthorized and/or unprotected personnel. Do not touch or walk through spilled material. Ensure adequate ventilation to remove vapors, fumes, dust etc.

Emergency Procedures

Ventilate closed spaces before entering. Isolate hazard area and deny entry to unauthorized and/or unprotected personnel.

Environmental precautions

No specific actions or treatments recommended related to exposure to this material.

Methods and material for containment and cleaning up

Containment/Clean-up Measures

Avoid generating dust.

FOR SMALL SPILLS: Clean with a vacuum with a filtration system sufficient to remove

Preparation Date: 07/March/2011 Format: GHS Language: English (US) Revision Date: 01/May/2018 Page 3 of 11

and prevent recirculation of crystalline silica (a vacuum equipped with a high-efficiency particulate air (HEPA) filter is recommended).

FOR LARGE SPILLS: Use a fine spray or mist to control dust creation and carefully scoop or shovel into clean dry container for later reuse or disposal.

If, an appropriate vacuum is unavailabe, only wet-clean-up methods should be used (i.e. misting). Moisture should be added as necessary to reduce exposure to airborne respirable silica dust.

Section 7 - Handling and Storage

Precautions for safe handling

Handling

 Do not breathe dust. Wash thoroughly after handling. Do not use in areas without adequate ventilation. Avoid contact with skin, eyes, and clothing. Minimize dust generation and accumulation. Use good safety and industrial hygiene practices. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Wear long sleeves and/or protective coveralls. Contaminated clothing must be vacuumed before removal. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage

 Store in a covered location. Keep container closed. Keep from freezing. Storage and work area should be periodically cleaned to minimize dust accumulation.

Section 8 - Exposure Controls/Personal Protection

Control parameters

			Exposure Limits	s/Guidelines		
	Result	ACGIH	Canada Ontario	Canada Quebec	Mexico	NIOSH
	STELs	Not established	Not established	Not established	20 mg/m3 STEL [LMPE-CT] (as Ti)	Not established
Titanium dioxide (13463-67-7)	TWAs	10 mg/m3 TWA	10 mg/m3 TWA	10 mg/m3 TWAEV (containing no Asbestos and <1% Crystalline silica, total dust)	10 mg/m3 TWA LMPE -PPT (as Ti)	Not established
Chemical 1 (Proprietary)	TWAs	10 mg/m3 TWA (inhalable fraction)	10 mg/m3 TWA (inhalable)	10 mg/m3 TWAEV (fume, as Mg)	10 mg/m3 TWA LMPE -PPT (fume, as Mg)	Not established
Cristobalite (14464-46-1)	TWAs	0.025 mg/m3 TWA (respirable fraction)	0.05 mg/m3 TWA (designated substances regulation, respirable, listed under Silica, crystalline)	0.05 mg/m3 TWAEV (respirable dust)	0.05 mg/m3 TWA LMPE-PPT (respirable fraction)	0.05 mg/m3 TWA (respirable dust)
Quartz (14808-60-7)	TWAs	0.025 mg/m3 TWA (respirable fraction)	0.10 mg/m3 TWA (designated substances regulation, respirable, listed under Silica, crystalline)	0.1 mg/m3 TWAEV (respirable dust)	0.1 mg/m3 TWA LMPE -PPT (respirable fraction)	0.05 mg/m3 TWA (respirable dust)
Amorphous silica fume (69012-64-2)	TWAs	Not established	2 mg/m3 TWA (respirable, listed under Silica fume)	2 mg/m3 TWAEV (containing no Asbestos and <1% Crystalline silica, respirable dust)	2 mg/m3 TWA LMPE- PPT; 10 mg/m3 TWA LMPE-PPT (inhalable particulate); 3 mg/m3 TWA LMPE-PPT (respirable particulate)	Not established

Aluminum oxide (1344-28-1)	TWAs	Not established	Not	established	10 mg/m3 TWAEV (containing no Asbestos and <1% Crystalline silica, total dust, as AI)	10 mg/m3 TWA LMPE -PPT	Not established
Silica, amorphous (7631-86-9)	TWAs	Not established	Not	established	Not established	Not established	6 mg/m3 TWA
Exposure Limits/Guidelines (Con't.)							
				Result		OSHA	
Titanium dioxide (13463-67-7)				TWAs	15 mg/m3 TWA (t	15 mg/m3 TWA (total dust)	
Chemical 1 (Proprietary)				TWAs	15 mg/m3 TWA (f	15 mg/m3 TWA (fume, total particulate)	
Aluminum oxide (1344-28-1) TWAs 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fr			A (respirable fraction)				

Exposure controls

Engineering Measures/Controls

• Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Ensure that dust handling systems (such as exhaust ducts, dust collectors, vessels and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is not leakage from the equipment). Collection systems must be designed and maintained to prevent the accumalation and recirculation of respirable silica into the workplace.

Personal Protective Equipment

Respiratory

For limited exposure use an N95 dust mask. For prolonged exposure use an airpurifying respirator with high efficiency particulate air (HEPA) filters. Follow the OSHA
respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a
NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are
exceeded or symptoms are experienced.

Eye/Face

• Wear protective eyewear (goggles, face shield, or safety glasses).

Hands

Wear appropriate gloves.

Skin/Body

Wear long sleeves and/or protective coveralls.

General Industrial Hygiene Considerations

 Do not breathe dust. Avoid contact with skin, eyes or clothing. Do not remove dusts from clothing by blowing or shaking. Do not eat, drink or smoke during work. Wash thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice.

Environmental Exposure Controls

 Follow best practice for site management and disposal of waste. Dispose of in an approved landfill.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

STEL = Short Term Exposure Limits are based on 15-minute exposures

NIOSH = National Institute of Occupational Safety and Health

TWAEV = Time-Weighted Average Exposure Value

OSHA = Occupational Safety and Health Administration

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Preparation Date: 07/March/2011 Format: GHS Language: English (US)
Revision Date: 01/May/2018 OSHA HCS 2012, WHMIS

Material Description			
Physical Form	Solid	Appearance/Description	Gray granular dry powder with an earthy odor.
Color	Gray	Odor	Earthy
Particulate Size	600 µ	Odor Threshold	No data available
General Properties			
Boiling Point	No data available	Melting Point/Freezing Point	No data available
Decomposition Temperature	No data available	рН	Not relevant
Specific Gravity/Relative Density	= 2.53 Water=1	Water Solubility	Negligible < 0.1 %
Viscosity	No data available		
Volatility			
Vapor Pressure	No data available	Vapor Density	No data available
Evaporation Rate	No data available		
Flammability	-	-	-
Flash Point	Not relevant	UEL	Not relevant
LEL	Not relevant	Autoignition	No data available
Flammability (solid, gas)	No data available		
Environmental			
Octanol/Water Partition coefficient	No data available		

Section 10: Stability and Reactivity

Reactivity

• No dangerous reaction known under conditions of normal use.

Chemical stability

• Stable under normal temperatures and pressures.

Possibility of hazardous reactions

· Hazardous polymerization will not occur.

Conditions to avoid

· No data available

Incompatible materials

· No data available

Hazardous decomposition products

· No data available

Section 11 - Toxicological Information

Information on toxicological effects

	Components					
Silica, amorphous (< 14.75%)	I/631-86-9 Hirritation: EVE-Rappit • 25 mg 24 Hour(s) • Milig Irritation					
Titanium dioxide (0.05% TO 0.45%)	13463-67- 7	Irritation: Skin-Human • 300 μg 3 Day(s)-Intermittent • Mild irritation; Tumorigen / Carcinogen: Inhalation-Rat TCLo • 250 mg/m³ 6 Hour(s) 2 Year(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration:Tumors				
Chemical 1 (< 0.0588%) Multi-dose Toxicity: Inhalation-Rat TCLo • 1000 mg/m³ 4 Hour(s) 50 Day(s)-Intermittent; Lungs, Respiration:Other changes; Blood:Other hemolysis with or without anemia		Multi-dose Toxicity: Inhalation-Rat TCLo • 1000 mg/m³ 4 Hour(s) 50 Day(s)-Intermittent; <i>Lungs, Thorax, or Respiration</i> : Other changes ; <i>Blood</i> : Other hemolysis with or without anemia				

GHS Properties	Classification		
Acute toxicity	OSHA HCS 2012 • Data lacking		
Skin corrosion/Irritation	OSHA HCS 2012 • Data lacking		
Serious eye damage/Irritation	OSHA HCS 2012 • Data lacking		
Skin sensitization	OSHA HCS 2012 • Data lacking		
Respiratory sensitization	OSHA HCS 2012 • Data lacking		
Aspiration Hazard	OSHA HCS 2012 • Data lacking		
Carcinogenicity	OSHA HCS 2012 • Carcinogenicity 1A		
Germ Cell Mutagenicity	OSHA HCS 2012 • Data lacking		
Toxicity for Reproduction	OSHA HCS 2012 • Data lacking		
STOT-SE	OSHA HCS 2012 • Data lacking		
STOT-RE	OSHA HCS 2012 • Specific Target Organ Toxicity Repeated Exposure 1		

Target Organs

Route(s) of entry/exposure

Medical Conditions Aggravated by Exposure Potential Health Effects Inhalation Lungs

· Inhalation, Skin, Eye, Ingestion

• Any pre-existing conditions of the lungs. Disorders of the lungs.

Acute (Immediate)

Chronic (Delayed)

- Nuisance dust may affect the lungs but reactions are typically reversible.
- Chronic overexposure to dust containing respirable sized crystalline silica can cause delayed lung injury (silicosis). Inhalation of dust containing crystalline silica pulmonary diseases such as asthma and lung disorder associated with smoking.

Skin

Acute (Immediate)

Chronic (Delayed)

· Exposure to dust may cause mechanical irritation.

· No data available.

Eve

Acute (Immediate)

• Excessive concentrations of nuisance dust in the workplace may reduce visibility and may cause unpleasant deposits in eyes.

Chronic (Delayed)

No data available.

Ingestion

Acute (Immediate)

• Excessive concentrations of nuisance dust in the workplace may cause mechanical irritation to mucous membranes.

Chronic (Delayed)

Carcinogenic Effects

- · No data available.
- May cause cancer. IARC studies have shown sufficient evidence from animal studies to categorize crystalline silica as a group 1 carcinogen.

Carcinogenic Effects						
CAS IARC NTP						
Titanium dioxide	13463-67-7	Group 2B-Possible Carcinogen	Not Listed			
Cristobalite	14464-46-1	Group 1-Carcinogenic	Not Listed			
Quartz	14808-60-7	Group 1-Carcinogenic	Known Human Carcinogen			

Key to abbreviations

TC = Toxic Concentration

Section 12 - Ecological Information

Toxicity

· Material data lacking.

Persistence and degradability

Material data lacking.

Bioaccumulative potential

Material data lacking.

Mobility in Soil

Material data lacking.

Other adverse effects

No studies have been found.

Section 13 - Disposal Considerations

Waste treatment methods

Product waste

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class (es)	Packing group	Environmental hazards
DOT	NDA	Not Regulated	NDA	NDA	NDA
TDG	NDA	Not Regulated	NDA	NDA	NDA
IATA/ICAO	NDA	Not Regulated	NDA	NDA	NDA

Special precautions for user • None specified.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

· No data available

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture SARA Hazard Classifications • Chronic

State Right To Know					
Component	CAS	MA	NJ	PA	
Aluminum oxide	1344-28-1	Yes	Yes	Yes	
Cristobalite	14464-46-1	Yes	Yes	Yes	
Quartz	14808-60-7	Yes	Yes	Yes	
Silica, amorphous	7631-86-9	Yes	Yes	Yes	

Titanium dioxide	13463-67-7	Yes	Yes	Yes
Zirconium(IV) silicate (1:1)	14940-68-2	No	No	No

	Inventory					
Component	CAS	Canada DSL	TSCA			
Aluminum oxide	1344-28-1	Yes	Yes			
Cristobalite	14464-46-1	Yes	Yes			
Quartz	14808-60-7	Yes	Yes			
Silica, amorphous	7631-86-9	Yes	Yes			
Titanium dioxide	13463-67-7	Yes	Yes			
Zirconium(IV) silicate (1:1)	14940-68-2	Yes	Yes			

Canada

Labor Canada - WHMIS - Classifications of Substances		
Zirconium(IV) silicate (1:1)	14940-68-2	Uncontrolled product according to WHMIS classification criteria
Titanium dioxide	13463-67-7	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Titanium dioxide, mixture containing on Health Canada's WHMIS Division website.)
Aluminum oxide	1344-28-1	Uncontrolled product according to WHMIS classification criteria
Cristobalite	14464-46-1	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS Division website.)
Silica, amorphous	7631-86-9	Uncontrolled product according to WHMIS classification criteria
• Quartz	14808-60-7	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS Division website.)
Canada - WHMIS - Ingredient Disclosure List		
• Zirconium(IV) silicate (1:1)	14940-68-2	1 %
Titanium dioxide	13463-67-7	Not Listed
Aluminum oxide	1344-28-1	1 %

• Cristob	alite	14464-46-1	1 %
Silica, a	morphous	7631-86-9	1 %
Quartz		14808-60-7	1 %

United States

Environment U.S CERCLA/SARA - Section 313 - Emission Reporting		
Zirconium(IV) silicate (1:1)	14940-68-2	Not Listed
Titanium dioxide	13463-67-7	Not Listed
Aluminum oxide	1344-28-1	1.0 % de minimis concentration (fibrous forms)
Cristobalite	14464-46-1	Not Listed
Silica, amorphous	7631-86-9	Not Listed
• Quartz	14808-60-7	Not Listed

United States - California

Environment U.S California - Proposition 65 - Carcinogens List		
Zirconium(IV) silicate (1:1)	14940-68-2	Not Listed
Titanium dioxide	13463-67-7	carcinogen, initial date 9/2/11 (airborne, unbound particles of respirable size)
Aluminum oxide	1344-28-1	Not Listed
Cristobalite	14464-46-1	Not Listed
Silica, amorphous	7631-86-9	Not Listed
• Quartz	14808-60-7	carcinogen, initial date 10/1/88 (airborne particles of respirable size)

United States - Pennsylvania

Labor U.S Pennsylvania - RTK (Right to Know) - Environmental Haz	zard List	
Zirconium(IV) silicate (1:1)	14940-68-2	Not Listed
Titanium dioxide	13463-67-7	Not Listed
Aluminum oxide	1344-28-1	
Cristobalite	14464-46-1	Not Listed
Silica, amorphous	7631-86-9	Not Listed
• Quartz	14808-60-7	Not Listed

Other Information

 WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information

Revision Date

• 01/May/2018

Last Revision Date

23/September/2014

Preparation Date

• 07/March/2011

Disclaimer/Statement of Liability

• The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation,

disposal and release. Reno Refractories MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key to abbreviationsNDA = No data available