Safety Data Sheet



Section 1: Identification

Product identifier

Product Name · Reno NC Hot Gun FS

Product Code • 189860

Relevant identified uses of the substance or mixture and uses advised against

Recommended use • Refractory applications

Details of the supplier of the safety data sheet

Manufacturer • Reno Refractories, Inc.

P O Box 201 Morris, AL 35116 United States

www.renorefractories.com sales@renorefractories.com

Telephone (General) • 205-647-0240

Emergency telephone number

Manufacturer • 1-800-262-8200 - CHEMTREC

Section 2: Hazard Identification

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012 • Carcinogenicity 1A

Specific Target Organ Toxicity Repeated Exposure 1

Skin Irritation 2

Label elements

OSHA HCS 2012

DANGER



Hazard statements • May cause cancer.

Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention • Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves, clothing, and eye/face protection, .

Response • IF exposed or concerned: Get medical advice/attention.

Storage/Disposal · Dispose of content and/or container in accordance with local, regional, national, and/or

international regulations.

Other hazards

• Under United States Regulations (29 CFR 1910.1200 - Hazard Communication

Standard), this product is considered hazardous.

Canada

According to: WHMIS

Classification of the substance or mixture

• Other Toxic Effects - D2A

Other Toxic Effects - D2B

Label elements

WHMIS .

(T)

• Other Toxic Effects - D2A

Other Toxic Effects - D2B

Other hazards

 WHMIS
 In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients

Substances

Material does not meet the criteria of a substance.

Mixtures

Composition					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	
Amorphous/fused silica	CAS :60676-86-0	46.53% TO 49%	NDA	OSHA HCS 2012: Not Classified	
Mullite	CAS :1302-93-8	21.02% TO 23.41%	NDA	OSHA HCS 2012: STOT RE 2 (Lungs)	
Aluminum oxide	CAS :1344-28-1	8% TO 11%	Inhalation-Rat LC50 • 0.2 mg/L 5 Hour(s) 28 Week(s)	OSHA HCS 2012: Not Classified	
Cristobalite	CAS :14464-46-1	4.5% TO 8.76%	NDA	OSHA HCS 2012: Carc. 1A	
Silica, amorphous	CAS :7631-86-9	3% TO 6.89%	NDA	OSHA HCS 2012: Not Classified	
Amorphous silica fume	CAS :69012-64-2	2.4% TO 5%	NDA	OSHA HCS 2012: STOT RE 1 (Lungs)	

Clay	CAS :1332-58-7	0.7% TO 2.7%	NDA	OSHA HCS 2012: Eye Irrit. 2B; STOT RE 1
Quartz	CAS :14808-60-7	0.1% TO 1.455%	NDA	OSHA HCS 2012: Carc. 1A; STOT RE 1 (Lungs)
Clay	CAS :1302-78-9	0.45% TO 1.25%	NDA	OSHA HCS 2012:
Sodium silicate	CAS :1344-09-8	< 0.81%	Ingestion/Oral-Mammal LD50 • 2000 mg/kg	OSHA HCS 2012: Skin Corr. 1; Eye Irrit. 2; Acute Tox. Oral 4
Chemical 1	Proprietary	< 0.12%	NDA	OSHA HCS 2012: Exposure limits
Silica, crystalline - tridymite	CAS :15468-32-3	< 0.0125%	NDA	OSHA HCS 2012:

Section 4: First-Aid Measures

Description of first aid measures

 Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. Get medical attention immediately.

 In case of contact with substance, immediately flush skin with running water for at least 20 minutes. If skin irritation occurs: Get medical advice/attention.

· In case of contact with substance, immediately flush eyes with running water for at

least 20 minutes. If eye irritation persists: Get medical advice/attention.

Rinse mouth. Do not give anything by mouth to an unconscious person. Get medical attention immediately.

Most important symptoms and effects, both acute and delayed

· Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Inhalation

Skin

Eye

Ingestion

All treatments should be based on observed signs and symptoms of distress in thepatient. Consideration should be given to the possibility that overexposure to materialsother than this product may have occurred.

Section 5: Fire-Fighting Measures

Extinguishing media

Suitable Extinguishing Media • Material is non-combustible. In case of fire use media as appropriate for surrounding fire.

Unsuitable Extinguishing Media

None known.

Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

· None known.

Hazardous Combustion Products

None known.

Advice for firefighters

 Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection. Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Section 6 - Accidental Release Measures

Preparation Date: 13/August/2018 Format: GHS Language: English (US) OSHA HCS 2012, WHMIS Revision Date: 13/August/2018 Page 3 of 13

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Isolate hazard area and deny entry to unauthorized and/or unprotected personnel. Do
not walk through spilled material. Ensure adequate ventilation to remove vapors,
fumes, dust etc. Wear appropriate personal protective equipment, avoid direct contact.

Emergency Procedures

 Ventilate closed spaces before entering. Isolate hazard area and deny entry to unauthorized and/or unprotected personnel.

Environmental precautions

• No specific actions or treatments recommended related to exposure to this material.

Methods and material for containment and cleaning up

Containment/Clean-up Measures

Avoid generating dust.

FOR SMALL SPILLS:

FOR SMALL SPILLS: Clean with a vacuum with a filtration system sufficient to remove and prevent recirculation of crystalline silica (a vacuum equipped with a high-efficiency particulate air (HEPA) filter is recommended).

FOR LARGE SPILLS: Use a fine spray or mist to control dust creation and carefully scoop or shovel into clean dry container for later reuse or disposal.

If, an appropriate vacuum is unavailabe, only wet-clean-up methods should be used (i.e. misting). Moisture should be added as necessary to reduce exposure to airborne respirable silica dust.

Section 7 - Handling and Storage

Precautions for safe handling

Handling

Use good safety and industrial hygiene practices. Use only in well ventilated areas.
Wear appropriate personal protective equipment, avoid direct contact. Wear long
sleeves and/or protective coveralls. Do not breathe dust. Avoid contact with skin,
eyes, and clothing. Minimize dust generation and accumulation. Routine
housekeeping should be instituted to ensure that dusts do not accumulate on
surfaces. Contaminated clothing must be vacuumed before removal. Contaminated
work clothing should not be allowed out of the workplace. Wash contaminated clothing
before reuse. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage

 Keep container closed. Store in a covered location. Store in a cool, dry place. Keep from freezing. Storage and work area should be periodically cleaned to minimize dust accumulation.

Section 8 - Exposure Controls/Personal Protection

Control parameters

			Exposure Limits	/Guidelines		
	Result	ACGIH	Canada Ontario	Canada Quebec	Mexico	NIOSH
Silica, crystalline - tridymite (15468-32-3)	TWAs	Not established	Not established	0.05 mg/m3 TWAEV (respirable dust)	0.05 mg/m3 TWA VLE-PPT (respirable fraction)	0.05 mg/m3 TWA (respirable dust)
Quartz (14808-60-7)	TWAs	0.025 mg/m3 TWA (respirable particulate matter)	0.10 mg/m3 TWA (designated substances regulation, respirable, listed under Silica, crystalline)	0.1 mg/m3 TWAEV (respirable dust)	0.1 mg/m3 TWA VLE- PPT (respirable fraction)	0.05 mg/m3 TWA (respirable dust)
Chemical 1 (Proprietary)	TWAs	10 mg/m3 TWA (inhalable particulate matter)	10 mg/m3 TWA (inhalable)	10 mg/m3 TWAEV (fume, as Mg)	10 mg/m3 TWA VLE- PPT (fume, as Mg)	Not established
	STELs	Not established	Not established	Not established	20 mg/m3 STEL [PPT- CT]	Not established

Clay (1332-58-7)	TWAs	2 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)	(containing no		(coi Asb Cry	g/m3 TWAEV ntaining no pestos and <1% stalline silica, pirable dust)	10 mg/m3 TWA VLE- PPT	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)	
Amorphous silica fume (69012-64-2)	TWAs	Not established	2 mg/m3 TWA (respirable, listed under Silica fume)		(coi Asb Cry	g/m3 TWAEV ntaining no pestos and <1% stalline silica, pirable dust)	2 mg/m3 TWA VLE- PPT; 10 mg/m3 TWA VLE-PPT (inhalable particulate); 3 mg/m3 TWA VLE-PPT (respirable particulate)	Not established	
Silica, amorphous (7631-86-9)	TWAs	Not established	Not e	established	Not	established	Not established	6 mg/m3 TWA	
Cristobalite (14464-46-1)	TWAs	0.025 mg/m3 TWA (respirable particulate matter)	0.05 mg/m3 TWA (designated substances regulation, respirable, listed under Silica, crystalline)			5 mg/m3 TWAEV spirable dust)	0.05 mg/m3 TWA VLE-PPT (respirable fraction)	0.05 mg/m3 TWA (respirable dust)	
Aluminum oxide (1344-28-1)	TWAs	1 mg/m3 TWA (respirable particulate matter) as Aluminum insoluble compounds	1 mg/m3 TWA (respirable) as Aluminum insoluble compounds		(coi Asb Cry	mg/m3 TWAEV ntaining no pestos and <1% stalline silica, total t, as AI)	10 mg/m3 TWA VLE- PPT	Not established	
Amorphous/fused silica (60676-86-0)	TWAs	Not established		ng/m3 TWA birable)	(coi Asb Cry	mg/m3 TWAEV ntaining no pestos and <1% stalline silica, pirable dust)	0.1 mg/m3 TWA VLE- PPT; 10 mg/m3 TWA VLE-PPT (inhalable particulate); 3 mg/m3 TWA VLE-PPT (respirable particulate)	Not established	
		Ex	posu	ıre Limits/Gui	del	ines (Con't.)			
Silica crustallina tri	dymite		\dashv	Result			OSHA		
(15468-32-3)	Silica, crystalline - tridymite (15468-32-3)			TWAs 50 μg/m3 TWA (listed ι		ed under Respirable crystalline silica)			
Quartz (14808-60-7)				TWAs		50 μg/m3 TWA (lis	listed under Respirable crystalline silica)		
Chemical 1 (Proprietary)				TWAs 1		15 mg/m3 TWA (fume, total particulate)			
Clay (1332-58-7)				TWAs		15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)			
Cristobalite (14464-46-1)			-	TWAs		50 μg/m3 TWA (listed under Respirable crystalline silica)			
Aluminum oxide (1344-28-1)			7	TWAs 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable			A (respirable fraction)		

Exposure Control Notations Mexico

- •Aluminum oxide (1344-28-1): Carcinogens: (A4 Not classifiable as a human carcinogen)
- •Clay (1332-58-7): Carcinogens: (A4 Not classifiable as a human carcinogen)

Canada Ontario

- Cristobalite (14464-46-1): Designated Substances: (0.05 mg/m3 TWA (respirable fraction, listed under Silica, crystalline))
- Quartz (14808-60-7): Designated Substances: (0.10 mg/m3 TWA (respirable fraction, listed under Silica, crystalline))

Canada Quebec

•Quartz (14808-60-7): Carcinogens: (C2 carcinogen - effect suspected in humans)

ACGIH

- •Cristobalite (14464-46-1): Carcinogens: (A2 Suspected Human Carcinogen)
- •Quartz (14808-60-7): Carcinogens: (A2 Suspected Human Carcinogen)
- •Aluminum oxide as Aluminum insoluble compounds: Carcinogens: (A4 Not Classifiable as a Human Carcinogen)
- Chemical 1 (Proprietary): Carcinogens: (A4 Not Classifiable as a Human Carcinogen)
- •Clay (1332-58-7): Carcinogens: (A4 Not Classifiable as a Human Carcinogen)

Exposure Limits Supplemental OSHA

- •Silica, amorphous (7631-86-9): Mineral Dusts: (20 mppcf TWA; (80)/(% SiO2) mg/m3 TWA)
- •Cristobalite (14464-46-1): **Mineral Dusts:** ((1/2)(250)/(%SiO2 + 5) mppcf TWA, respirable fraction; (1/2)(10)/(%SiO2 + 2) mg/m3 TWA, respirable fraction)
- •Amorphous/fused silica (60676-86-0): Mineral Dusts: ((80)/(% SiO2) mg/m3 TWA: 20 mppcf TWA)
- •Quartz (14808-60-7): Mineral Dusts: ((250)/(%SiO2 + 5) mppcf TWA, respirable fraction; (10)/(%SiO2 + 2) mg/m3 TWA, respirable fraction)
- •Silica, crystalline tridymite (15468-32-3): **Mineral Dusts**: ((1/2)(250)/(%SiO2 + 5) mppcf TWA, respirable fraction; (1/2)(10)/(%SiO2 + 2) mg/m3 TWA, respirable fraction)

ACGIH

- Cristobalite (14464-46-1): TLV Basis Critical Effects: (lung cancer; pulmonary fibrosis)
- •Quartz (14808-60-7): TLV Basis Critical Effects: (lung cancer; pulmonary fibrosis)
- •Aluminum oxide as Aluminum insoluble compounds: **TLV Basis Critical Effects:** (pneumoconiosis; lower respiratory tract irritation; neurotoxicity)
- •Chemical 1 (Proprietary): TLV Basis Critical Effects: (metal fume fever; upper respiratory tract irritation)
- •Clay (1332-58-7): TLV Basis Critical Effects: (pneumoconiosis)

Exposure controls

Engineering Measures/Controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Ensure that dust handling systems (such as exhaust ducts, dust collectors, vessels and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is not leakage from the equipment). Collection systems must be designed and maintained to prevent the accumulation and recirculation of respirable silica into the workplace.

Personal Protective Equipment

Respiratory

For limited exposure use an N95 dust mask. For prolonged exposure use an airpurifying respirator with high efficiency particulate air (HEPA) filters. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face

Wear protective eyewear (goggles, face shield, or safety glasses).

Hands

Wear appropriate gloves.

Skin/Body

Wear long sleeves and/or protective coveralls.

General Industrial Hygiene Considerations

 Do not breathe dust. Avoid contact with skin, eyes or clothing. Do not remove dusts from clothing by blowing or shaking. Do not eat, drink or smoke during work. Wash thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice.

Environmental Exposure Controls

Follow best practice for site management and disposal of waste. Dispose of in an approved landfill.

Preparation Date: 13/August/2018

Format: GHS Language: English (US)

Revision Date: 13/August/2018

OSHA HCS 2012, WHMIS

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

NIOSH = National Institute of Occupational Safety and Health

OSHA = Occupational Safety and Health Administration

STEL = Short Term Exposure Limits are based on 15-minute exposures

TWAEV = Time-Weighted Average Exposure Value

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description			
Physical Form	Solid	Appearance/Description	No data available
Color	Gray	Odor	Earthy
Particulate Size	600 µ	Odor Threshold	No data available
General Properties		•	-
Boiling Point	No data available	Melting Point/Freezing Point	No data available
Decomposition Temperature	No data available	рН	No data available
Specific Gravity/Relative Density	= 2.53 Water=1	Water Solubility	Negligible < 0.1 %
Viscosity	No data available		
Volatility		-	_
Vapor Pressure	No data available	Vapor Density	No data available
Evaporation Rate	No data available	VOC (Wt.)	0 %
VOC (Vol.)	0 %		
Flammability		-	-
Flash Point	No data available	UEL	No data available
LEL	No data available	Autoignition	No data available
Flammability (solid, gas)	No data available		
Environmental			
Octanol/Water Partition coefficient	No data available		

Section 10: Stability and Reactivity

Reactivity

· No dangerous reaction known under conditions of normal use.

Chemical stability

· Stable under normal temperatures and pressures.

Possibility of hazardous reactions

· Hazardous polymerization will not occur.

Conditions to avoid

Revision Date: 13/August/2018

· No data available

Incompatible materials

· No data available

Hazardous decomposition products

No data available

Section 11 - Toxicological Information

Preparation Date: 13/August/2018

Information on toxicological effects

		Components
Silica, amorphous (3% TO 6.89%)	7631-86-9	Irritation: Eye-Rabbit • 25 mg 24 Hour(s) • Mild irritation
Cristobalite (4.5% TO 8.76%)	14464-46- 1	Acute Toxicity: Inhalation-Human TCLo • 16 mppcf 8 Hour(s) 17.9 Year(s)-Intermittent; Lungs, Thorax, or Respiration:Fibrosis, focal (pneumoconiosis); Lungs, Thorax, or Respiration:Dyspnea; Multi-dose Toxicity: Inhalation-Mouse TCLo • 43 mg/m³ 5 Hour(s) 9 Day(s)-Intermittent; Lungs, Thorax, or Respiration:Pleural effusion; Lungs, Thorax, or Respiration:Other changes
Quartz (0.1% TO 1.455%)	14808-60- 7	Acute Toxicity: Ingestion/Oral-Rat TDLo • 120 g/kg; Gastrointestinal:Hypermotility, diarrhea; Gastrointestinal:Other changes; Inhalation-Rat TCLo • 1 mg/kg; Lungs, Thorax, or Respiration:Other changes; Biochemical:Metabolism (intermediary):Effect on inflammation or mediation of inflammation; Multi-dose Toxicity: Inhalation-Rat TCLo • 6.2 mg/m³ 6 Hour(s) 6 Week(s)-Intermittent; Lungs, Thorax, or Respiration:Other changes; Blood:Changes in spleen; Immunological Including Allergic:Increase in cellular immune response; Inhalation-Rat TCLo • 58 mg/m³ 13 Week(s)-Intermittent; Lungs, Thorax, or Respiration:Other changes; Endocrine:Changes in thymus weight; Blood:Changes in leucocyte (WBC) count; Inhalation-Rat TCLo • 80 mg/m³ 26 Week(s)-Intermittent; Lungs, Thorax, or Respiration:Fibrosis, focal (pneumoconiosis); Blood:Changes in spleen; Immunological Including Allergic:Decrease in cellular immune response; Inhalation-Rat TCLo • 108 mg/m³ 6 Hour(s) 3 Day(s)-Intermittent; Biochemical:Enzyme inhibition, induction, or change in blood or tissue levels:Phosphatases; Biochemical:Enzyme inhibition, induction, or change in blood or tissue levels:Other oxidoreductases; Biochemical:Metabolism (intermediary):Other proteins; Tumorigen / Carcinogen: Inhalation-Rat TCLo • 50 mg/m³ 6 Hour(s) 71 Week(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Liver:Tumors
Aluminum oxide (8% TO 11%)	1344-28-1	Multi-dose Toxicity: Inhalation-Rat LC50 • 0.2 mg/L 5 Hour(s) 28 Week(s) • Comments: Rat Lung, Thorax, or Respiration: Structural or functional change in trachea or bronchi Lung, Thorax, or Respiration: Chronic pulmonary edema or congestion; Inhalation-Rabbit TCLo • 200 mg/m³ 5 Hour(s) 28 Week(s)-Intermittent; Lungs, Thorax, or Respiration:Structural or functional change in trachea or bronchi; Lungs, Thorax, or Respiration:Chronic pulmonary edema; Related to Chronic Data:Death in the Other Multiple Dose data type field; Inhalation-Rat TCLo • 200 mg/m³ 5 Hour(s) 28 Week(s)-Intermittent; Lungs, Thorax, or Respiration:Structural or functional change in trachea or bronchi; Lungs, Thorax, or Respiration:Chronic pulmonary edema; Related to Chronic Data:Death in the Other Multiple Dose data type field
Chemical 1 (< 0.12%)	Proprietary	Acute Toxicity: Inhalation-Human TCLo • 400 mg/m³; Multi-dose Toxicity: Inhalation-Rat TCLo • 1000 mg/m³ 4 Hour(s) 50 Day(s)-Intermittent; Lungs, Thorax, or Respiration:Other changes; Blood:Other hemolysis with or without anemia; Tumorigen / Carcinogen: Intratracheal-Hamster TDLo • 480 mg/kg 30 Week(s)-Intermittent; Tumorigenic:Equivocal tumorigenic agent by RTECS criteria; Sense Organs and Special Senses:Olfaction:Tumors; Lungs, Thorax, or Respiration:Tumors
Clay (0.7% TO 2.7%)	1332-58-7	Multi-dose Toxicity: Inhalation-Rat TCLo • 30 mg/m³ 96 Week(s)-Intermittent; Lungs, Thorax, or Respiration:Fibrosis (interstitial); Lungs, Thorax, or Respiration:Other changes; Lungs, Thorax, or Respiration:Tumors
Clay (0.45% TO 1.25%)	1302-78-9	Multi-dose Toxicity: Ingestion/Oral-Rat TDLo • 700 mg/kg 7 Day(s)-Intermittent; Endocrine:Other changes; Tumorigen / Carcinogen: Ingestion/Oral-Mouse TDLo • 12000 g/kg 28 Week(s)-Continuous; Tumorigenic:Equivocal tumorigenic agent by RTECS criteria; Liver:Tumors
Sodium silicate (< 0.81%)	1344-09-8	Acute Toxicity: Skin-Rabbit LD50 • >4640 mg/kg; Behavioral:Somnolence (general depressed activity); Lungs, Thorax, or Respiration:Dyspnea; Irritation: Eye-Rabbit • 10 mg 24 Hour(s) • Severe irritation; Skin-Rabbit • 500 mg 24 Hour(s) • Severe irritation

GHS Properties	Classification	
Acute toxicity	OSHA HCS 2012 • No data available	
Skin corrosion/Irritation	OSHA HCS 2012 • Skin Irritation 2	

Serious eye damage/Irritation	OSHA HCS 2012 • No data available		
Skin sensitization	OSHA HCS 2012 • No data available		
Respiratory sensitization	OSHA HCS 2012 • No data available		
Aspiration Hazard	OSHA HCS 2012 • No data available		
Carcinogenicity	OSHA HCS 2012 • Carcinogenicity 1A		
Germ Cell Mutagenicity	OSHA HCS 2012 • No data available		
Toxicity for Reproduction	OSHA HCS 2012 • No data available		
STOT-SE	OSHA HCS 2012 • No data available		
STOT-RE	OSHA HCS 2012 • Specific Target Organ Toxicity Repeated Exposure 1		

Route(s) of entry/exposure

Medical Conditions
Aggravated by Exposure
Potential Health Effects
Inhalation

Inhalation, Skin, Eye, Ingestion

Any pre-existing conditions of the lungs. Disorders of the lungs.

Acute (Immediate)

• Nuisance dust may affect the lungs but reactions are typically reversible.

Chronic (Delayed)

 Chronic overexposure to dust containing respirable sized crystalline silica can cause delayed lung injury (silicosis). Inhalation of dust containing crystalline silica pulmonary diseases such as asthma and lung disorder associated with smoking.

Skin

Acute (Immediate)

• Exposure to dust may cause mechanical irritation.

Chronic (Delayed)

· No data available.

Eye

Acute (Immediate)

 Excessive concentrations of nuisance dust in the workplace may reduce visibility and may cause unpleasant deposits in eyes.

Chronic (Delayed)

No data available.

Ingestion

Acute (Immediate)

• Excessive concentrations of nuisance dust in the workplace may cause mechanical irritation to mucous membranes.

Chronic (Delayed)

No data available.

Carcinogenic Effects

• May cause cancer. IARC studies have shown sufficient evidence from animal studies to categorize crystalline silica as a group 1 carcinogen.

Carcinogenic Effects						
CAS IARC NTP						
Quartz	14808-60-7	Group 1-Carcinogenic	Known Human Carcinogen			
Cristobalite	14464-46-1	Group 1-Carcinogenic	Not Listed			

Key to abbreviations

LD = Lethal Dose

TC = Toxic Concentration

Section 12 - Ecological Information

Toxicity

· Material data lacking.

Persistence and degradability

Format: GHS Language: English (US)
OSHA HCS 2012, WHMIS

Material data lacking.

Bioaccumulative potential

Material data lacking.

Mobility in Soil

· Material data lacking.

Other adverse effects

No studies have been found.

Section 13 - Disposal Considerations

Waste treatment methods

Product waste

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class (es)	Packing group	Environmental hazards
DOT	NDA	Not Regulated	NDA	NDA	NDA
TDG	NDA	Not Regulated	NDA	NDA	NDA
IATA/ICAO	NDA	Not Regulated	NDA	NDA	NDA

Special precautions for user

None specified.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No data available

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture SARA Hazard Classifications • Chronic

State Right To Know						
Component	CAS	MA	NJ	PA		
Aluminum oxide	1344-28-1	Yes	Yes	Yes		
Amorphous/fused silica	60676-86-0	Yes	Yes	No		
Clay	1302-78-9	No	No	No		
Cristobalite	14464-46-1	Yes	Yes	Yes		
Chemical 2	Proprietary	No	No	No		
Clay	1332-58-7	Yes	Yes	Yes		
Chemical 1	Proprietary	Yes	Yes	Yes		
Mullite	1302-93-8	No	No	No		
Quartz	14808-60-7	Yes	Yes	Yes		

Amorphous silica fume	69012-64-2	No	No	No
Silica, amorphous	7631-86-9	Yes	Yes	Yes
Silica, crystalline - tridymite	15468-32-3	Yes	Yes	Yes
Sodium silicate	1344-09-8	No	No	No

		Inventory	
Component	CAS	Canada DSL	TSCA
Aluminum oxide	1344-28-1	Yes	Yes
Amorphous/fused silica	60676-86-0	Yes	Yes
Clay	1302-78-9	Yes	Yes
Cristobalite	14464-46-1	Yes	Yes
Chemical 2	Proprietary	Yes	Yes
Clay	1332-58-7	Yes	Yes
Chemical 1	Proprietary	Yes	Yes
Mullite	1302-93-8	Yes	Yes
Quartz	14808-60-7	Yes	Yes
Amorphous silica fume	69012-64-2	Yes	Yes
Silica, amorphous	7631-86-9	Yes	Yes
Silica, crystalline - tridymite	15468-32-3	No	No
Sodium silicate	1344-09-8	Yes	Yes

Canada

Canada - WHMIS 1988 - Classifications of Substances		
Chemical 2	Proprietary	Uncontrolled product according to WHMIS classification criteria
Silica, crystalline - tridymite	15468-32-3	D2A
• Clay	1332-58-7	D2A
Mullite	1302-93-8	Not Listed
Amorphous silica fume	69012-64-2	Not Listed
• Chemical 1	Proprietary	Uncontrolled product according to WHMIS classification criteria
Aluminum oxide	1344-28-1	Uncontrolled product according to WHMIS classification criteria
Cristobalite	14464-46-1	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specifilssues - Silica, crystalline, encapsulated on Health Canada's WHMIS Division website.) Uncontrolled product

Silica, amorphous	7631-86-9	according to WHMIS classification criteria
Amorphous/fused silica	60676-86-0	Uncontrolled product according to WHMIS
	4044.00.0	classification criteria D2B (SiO2:Na2O ratio >2.4:1);
Sodium silicate	1344-09-8	E (SiO2:Na2O ratio <2.4:1)
• Quartz	14808-60-7	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS Division website.)
• Clay	1302-78-9	D2A
Canada - WHMIS 1988 - Ingredient Disclosure List		
Chemical 2	Proprietary	Not Listed
Silica, crystalline - tridymite	15468-32-3	1 %
• Clay	1332-58-7	Not Listed
• Mullite	1302-93-8	Not Listed
Amorphous silica fume	69012-64-2	Not Listed
Chemical 1	Proprietary	1 %
Aluminum oxide	1344-28-1	1 %
Cristobalite	14464-46-1	1 %
Silica, amorphous	7631-86-9	1 %
Amorphous/fused silica	60676-86-0	1 %
Sodium silicate	1344-09-8	Not Listed
• Quartz	14808-60-7	1 %
• Clay	1302-78-9	Not Listed

United States

Environment			
U.S CERCLA/SARA - Section 313 - Emission Reporting			
Chemical 2	Proprietary	Not Listed	
Silica, crystalline - tridymite	15468-32-3	Not Listed	
• Clay	1332-58-7	Not Listed	
• Mullite	1302-93-8	Not Listed	
Amorphous silica fume	69012-64-2	Not Listed	
Chemical 1	Proprietary	Not Listed	
Aluminum oxide	1344-28-1	1.0 % de minimis concentration (fibrous forms)	
Cristobalite	14464-46-1	Not Listed	
Silica, amorphous	7631-86-9	Not Listed	
Amorphous/fused silica	60676-86-0	Not Listed	
Sodium silicate	1344-09-8	Not Listed	
• Quartz	14808-60-7	Not Listed	
• Clay	1302-78-9	Not Listed	

United States - California

Environment U.S California - Proposition 65 - Carcinogens List		
Chemical 2	Proprietary	Not Listed
Silica, crystalline - tridymite	15468-32-3	Not Listed

• Clay	1332-58-7 Not Listed
Mullite	1302-93-8 Not Listed
Amorphous silica fume	69012-64-2 Not Listed
Chemical 1	Proprietary Not Listed
Aluminum oxide	1344-28-1 Not Listed
Cristobalite	14464-46-1 Not Listed
Silica, amorphous	7631-86-9 Not Listed
Amorphous/fused silica	60676-86-0 Not Listed
Sodium silicate	1344-09-8 Not Listed
• Quartz	14808-60-7 Not Listed
• Clay	1302-78-9 Not Listed

United States - Pennsylvania

Chemical 2	Proprietary	Not Listed
Silica, crystalline - tridymite	15468-32-3	Not Listed
Clay	1332-58-7	Not Listed
Mullite	1302-93-8	Not Listed
Amorphous silica fume	69012-64-2	Not Listed
Chemical 1	Proprietary	Not Listed
· Aluminum oxide	1344-28-1	
Cristobalite	14464-46-1	Not Listed
· Silica, amorphous	7631-86-9	Not Listed
Amorphous/fused silica	60676-86-0	Not Listed
Sodium silicate	1344-09-8	Not Listed
Quartz	14808-60-7	Not Listed
Clay	1302-78-9	Not Listed

Other Information

 WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information

Revision Date

Last Revision Date

Preparation Date

Disclaimer/Statement of Liability

- 13/August/2018
- 13/August/2018
- 13/August/2018
- The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. Reno Refractories MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key to abbreviations

NDA = No data available