Safety Data Sheet



Section 1: Identification

Product identifier

Product Name Reno Plastic 85 PF

Product Code • 234300

Relevant identified uses of the substance or mixture and uses advised against

Recommended use • Refractory applications

Details of the supplier of the safety data sheet

Manufacturer • Reno Refractories, Inc.

P O Box 201 Morris, AL 35116 United States

www.renorefractories.com sales@renorefractories.com

Telephone (General) • 205-647-0240

Emergency telephone number

Manufacturer • 1-800-262-8200 - CHEMTREC

Section 2: Hazard Identification

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012 • Skin Irritation 2

Serious Eye Damage 1 Carcinogenicity 1A

Specific Target Organ Toxicity Repeated Exposure 2

Label elements

OSHA HCS 2012

DANGER







Hazard statements · Causes skin irritation

Causes serious eye damage

May cause cancer.

May cause damage to organs through prolonged or repeated exposure

Precautionary statements

Preparation Date: 23/November/2015

Revision Date: 13/March/2018

Prevention • Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

Response • If on skin: Wash with plenty of water.

Specific treatment, see supplemental first aid information. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician. IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Storage/Disposal • Dispose of content and/or container in accordance with local, regional, national, and/or

international regulations.

Other hazards

• Under United States Regulations (29 CFR 1910.1200 - Hazard Communication

Standard), this product is considered hazardous.

Canada

According to: WHMIS

Classification of the substance or mixture

WHMIS
 Other Toxic Effects - D2A

Other Toxic Effects - D2B

Corrosive - E

Label elements

WHMIS .





• Other Toxic Effects - D2A Other Toxic Effects - D2B

Corrosive - E

Other hazards

WHMIS
 In Canada, the product mentioned above is considered hazardous under the

Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients

Substances

Material does not meet the criteria of a substance.

Mixtures

| Composition | | | | | |
|---------------|-------------|---|-------------|--|--|
| Chemical Name | Identifiers | % | H D50/I C50 | Classifications According to Regulation/Directive | |

| Bauxite | CAS :1318-16- | 46.64% TO 50.16% | NDA | OSHA HCS 2012: STOT RE 2 (Lungs) |
|--------------------------------------|-------------------------|---------------------|--|--|
| Aluminum oxide | CAS :1344-28-1 | 17.77% TO 27% | NDA | OSHA HCS 2012: Not Classified - Criteria not met |
| Water | CAS :7732-18-5 | 5% TO 9% | NDA | OSHA HCS 2012: Not hazardous |
| Aluminum(III) silicate (2:1) | CAS :1302-76-7 | 4.25% TO 8.55% | NDA | OSHA HCS 2012: STOT RE 2 (Lungs) |
| Bentonite | CAS :1302-78-9 | 1.94% TO 5% | NDA | OSHA HCS 2012: STOT RE 2(lungs) |
| Phosphoric acid | CAS :7664-38-2 | 2.4% TO 4.55% | Ingestion/Oral-Rat LD50 • 1.25 g/kg Inhalation-Rat LC50 • 25.5 mg/m³ | OSHA HCS 2012: Skin Corr. 1C, Eye Dam. |
| Silica, amorphous | CAS :7631-86-9 | 3.44% TO 3.84% | NDA | OSHA HCS 2012: Data Lacking |
| Titanium dioxide | CAS :13463-67 | 1.77% TO 2.3% | NDA | OSHA HCS 2012: Carc. 2 |
| Iron oxide | CAS :1309-37- | 1.06% TO 1.14% | NDA | OSHA HCS 2012: Not Classified - Criteria not met |
| Phosphoric acid, aluminum salt (1:3) | CAS :13530-50 -2 | 0.4% TO 1.05% | NDA | OSHA HCS 2012: None |
| Quartz | CAS :14808-60 -7 | < 1.05% | NDA | OSHA HCS 2012: Carc. 1A; STOT RE 1 (Lungs) |
| Boron oxide | CAS :1303-86-2 | 0.04% TO 0.35% | Ingestion/Oral-Rat LD50 • 3150 mg/kg | OSHA HCS 2012: Not Classified - Criteria not met |
| Urea, 1,3-diethyl-2-thio- | CAS:105-55-5 | < 0.015% | Ingestion/Oral-Rat LD50 • 316 mg/kg | OSHA HCS 2012: WHMIS: |
| Cristobalite | CAS :14464-46 | < 0.009% | NDA | OSHA HCS 2012: Carc. 1A |

Section 4: First-Aid Measures

Description of first aid measures

Inhalation

 Move victim to fresh air. Give artificial respiration if victim is not breathing. Administer oxygen if breathing is difficult. Get medical attention immediately.

Skin

• In case of contact with substance, immediately flush skin with running water for at least 20 minutes. If skin irritation occurs: Get medical advice/attention.

Eye

• In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.

Ingestion

 Rinse mouth. Do not give anything by mouth to an unconscious person. Get medical attention immediately.

Most important symptoms and effects, both acute and delayed

Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

 All treatments should be based on observed signs and symptoms of distress in thepatient. Consideration should be given to the possibility that overexposure to materialsother than this product may have occurred.

Section 5: Fire-Fighting Measures

Extinguishing media

Preparation Date: 23/November/2015

Format: GHS Language: English (US)
OSHA HCS 2012, WHMIS

Suitable Extinguishing Media • Material is non-combustible. In case of fire use media as appropriate for surrounding

Unsuitable Extinguishing

Media

· None known.

Special hazards arising from the substance or mixture

Unusual Fire and Explosion

Hazards

· None known.

Hazardous Combustion

None known.

Products

Advice for firefighters

Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection. Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions

 Isolate hazard area and deny entry to unauthorized and/or unprotected personnel. Do not touch or walk through spilled material. Ensure adequate ventilation to remove vapors, fumes, dust etc.

Emergency Procedures

 Ventilate closed spaces before entering. Isolate hazard area and deny entry to unauthorized and/or unprotected personnel.

Environmental precautions

No specific actions or treatments recommended related to exposure to this material.

Methods and material for containment and cleaning up

Containment/Clean-up Measures

· Avoid generating dust.

FOR SMALL SPILLS: Clean with a vacuum with a filtration system sufficient to remove and prevent recirculation of crystalline silica (a vacuum equipped with a high-efficiency

particulate air (HEPA) filter is recommended). FOR LARGE SPILLS: Use a fine spray or mist to control dust creation and carefully scoop or shovel into clean dry container for later reuse or disposal.

If, an appropriate vacuum is unavailabe, only wet-clean-up methods should be used (i.e. misting). Moisture should be added as necessary to reduce exposure to airborne

respirable silica dust.

Section 7 - Handling and Storage

Precautions for safe handling

Handling

· Do not breathe dust. Avoid contact with skin, eyes, and clothing. Minimize dust generation and accumulation. Use good safety and industrial hygiene practices. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Wear long sleeves and/or protective coveralls. Contaminated clothing must be vacuumed before removal. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Wash thoroughly after handling. Do not use in areas without adequate ventilation.

Conditions for safe storage, including any incompatibilities

Storage

 Store in a covered location. Keep container closed. Keep from freezing. Storage and work area should be periodically cleaned to minimize dust accumulation.

Section 8 - Exposure Controls/Personal Protection

Control parameters

Format: GHS Language: English (US) OSHA HCS 2012, WHMIS

| | | | Ex | posure Limits | s/Gu | idelines | | |
|----------------------------------|--------|---|--|--|--|--|---|---------------------------------------|
| | Result | ACGIH | | anada Ontario | 11 | anada Quebec | Mexico | NIOSH |
| Cristobalite (14464-46-1) | TWAs | 0.025 mg/m3 TWA (respirable particulate matter) | 0.05 (desi subs regul listed | mg/m3 TWA gnated tances lation, respirable, I under Silica, alline) | | 5 mg/m3 TWAEV pirable dust) | 0.05 mg/m3 TWA VLE -PPT (respirable fraction) | 0.05 mg/m3 TWA (respirable dust) |
| Boron oxide | STELs | Not established | Not e | established | Not | established | 20 mg/m3 STEL [PPT- CT] | Not established |
| (1303-86-2) | TWAs | 10 mg/m3 TWA | 10 m | g/m3 TWA | 10 r | ng/m3 TWAEV | 10 mg/m3 TWA VLE- PPT | 10 mg/m3 TWA |
| Quartz (14808-60-7) | TWAs | 0.025 mg/m3 TWA (respirable particulate matter) | (desi subs regul listed | | | mg/m3 TWAEV pirable dust) | 0.1 mg/m3 TWA VLE- PPT (respirable fraction) | 0.05 mg/m3 TWA (respirable dust) |
| | STELs | Not established | Not e | established | Not | established | 10 mg/m3 STEL [PPT- CT] (as Fe) | Not established |
| Iron oxide (1309-37-1) | TWAs | 5 mg/m3 TWA (respirable particulate matter) | | /m3 TWA pirable) | (dus Fe); TW/ no / <1% regu | g/m3 TWAEV st and fume, as 10 mg/m3 AEV (containing Asbestos and 6 Crystalline silica, ulated under uge, total dust) | 5 mg/m3 TWA VLE- PPT | 5 mg/m3 TWA (dust and fume, as Fe) |
| | STELs | Not established | Not e | established | Not | established | 20 mg/m3 STEL [PPT- CT] (as Ti) | Not established |
| Titanium dioxide (13463-67-7) | TWAs | 10 mg/m3 TWA | 10 mg/m3 TWA | | (cor Asb | ng/m3 TWAEV ntaining no estos and <1% stalline silica, total t) | 10 mg/m3 TWA VLE- PPT (as Ti) | Not established |
| Phosphoric acid | STELs | 3 mg/m3 STEL | 3 mg | /m3 STEL | 3 m | g/m3 STEV | 3 mg/m3 STEL [PPT- CT] | 3 mg/m3 STEL |
| (7664-38-2) | TWAs | 1 mg/m3 TWA | 1 mg | /m3 TWA | 1 m | g/m3 TWAEV | 1 mg/m3 TWA VLE- PPT | 1 mg/m3 TWA |
| Silica, amorphous (7631-86-9) | TWAs | Not established | Not e | established | Not | established | Not established | 6 mg/m3 TWA |
| Aluminum oxide (1344-28-1) | TWAs | Not established | Not established (| | (cor Asb Crys | ng/m3 TWAEV ntaining no estos and <1% stalline silica, total t, as AI) | 10 mg/m3 TWA VLE- PPT | Not established |
| | | Ex | cpos | ure Limits/Gu | idel | ines (Con't.) | | |
| | | | | Result | | | OSHA | |
| Cristobalite (14464-46-1) | | | | TWAs 50 μg/m3 TWA (li: | | (listed under Respirable crystalline silica) | | |
| Boron oxide (1303-86-2) | | | | TWAs | 15 mg/m3 TWA (total dust) | | | |
| Quartz (14808-60-7) | | | | TWAs | | 50 μg/m3 TWA (listed under Respirable crystalline silica) | | |

| Iron oxide (1309-37-1) | TWAs | 10 mg/m3 TWA (fume); 15 mg/m3 TWA (total dust, listed under Rouge); 5 mg/m3 TWA (respirable fraction, listed under Rouge) |
|----------------------------------|------|---|
| Titanium dioxide (13463-67-7) | TWAs | 15 mg/m3 TWA (total dust) |
| Phosphoric acid (7664-38-2) | TWAs | 1 mg/m3 TWA |
| Aluminum oxide (1344-28-1) | TWAs | 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction) |

Exposure Control Notations

Canada Ontario

- Cristobalite (14464-46-1): Designated Substances: (0.05 mg/m3 TWA (respirable fraction, listed under Silica, crystalline))
- •Quartz (14808-60-7): Designated Substances: (0.10 mg/m3 TWA (respirable fraction, listed under Silica, crystalline))

Canada Quebec

Quartz (14808-60-7): Carcinogens: (C2 carcinogen - effect suspected in humans)

ACGIH

- Cristobalite (14464-46-1): **Carcinogens:** (A2 Suspected Human Carcinogen)
- •Quartz (14808-60-7): Carcinogens: (A2 Suspected Human Carcinogen)
- •Titanium dioxide (13463-67-7): Carcinogens: (A4 Not Classifiable as a Human Carcinogen)
- •Iron oxide (1309-37-1): Carcinogens: (A4 Not Classifiable as a Human Carcinogen)

Exposure Limits Supplemental OSHA

- Silica, amorphous (7631-86-9): Mineral Dusts: (20 mppcf TWA; (80)/(% SiO2) mg/m3 TWA)
- •Cristobalite (14464-46-1): **Mineral Dusts:** ((1/2)(250)/(%SiO2 + 5) mppcf TWA, respirable fraction; (1/2)(10)/(%SiO2 + 2) mg/m3 TWA, respirable fraction)
- •Quartz (14808-60-7): **Mineral Dusts:** ((250)/(%SiO2 + 5) mppcf TWA, respirable fraction; (10)/(%SiO2 + 2) mg/m3 TWA, respirable fraction) **ACGIH**
- Cristobalite (14464-46-1): TLV Basis Critical Effects: (lung cancer; pulmonary fibrosis)
- •Quartz (14808-60-7): TLV Basis Critical Effects: (lung cancer; pulmonary fibrosis)
- •Titanium dioxide (13463-67-7): **TLV Basis Critical Effects:** (lower respiratory tract irritation)
- •Iron oxide (1309-37-1): TLV Basis Critical Effects: (pneumoconiosis)
- Phosphoric acid (7664-38-2): TLV Basis Critical Effects: (eye, skin and upper respiratory tract irritation)
- •Boron oxide (1303-86-2): TLV Basis Critical Effects: (eye and upper respiratory tract irritation)

Exposure controls

Engineering Measures/Controls

• Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Ensure that dust handling systems (such as exhaust ducts, dust collectors, vessels and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is not leakage from the equipment). Collection systems must be designed and maintained to prevent the accumalation and recirculation of respirable silica into the workplace.

Personal Protective Equipment

Respiratory

For limited exposure use an N95 dust mask. For prolonged exposure use an airpurifying respirator with high efficiency particulate air (HEPA) filters. Follow the OSHA
respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a
NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are
exceeded or symptoms are experienced.

Wear protective eyewear (goggles, face shield, or safety glasses).

Eye/Face

Wear appropriate gloves.

Hands

Preparation Date: 23/November/2015

Revision Date: 13/March/2018

Skin/Body

General Industrial Hygiene Considerations

- Wear long sleeves and/or protective coveralls.
- Avoid breathing dust. Avoid contact with skin, eyes or clothing. Do not remove dusts from clothing by blowing or shaking. Do not eat, drink or smoke during work. Wash hands before eating, drinking, or smoking. Wash thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice.

Environmental Exposure Controls

 Follow best practice for site management and disposal of waste. Dispose of in an approved landfill.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

STEL = Short Term Exposure Limits are based on 15-minute exposures

NIOSH = National Institute of Occupational Safety and Health

TWAEV = Time-Weighted Average Exposure Value

OSHA = Occupational Safety and Health Administration

WA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

| Material Description | | | |
|-------------------------------------|--------------------|------------------------------|--|
| Physical Form | Solid | Appearance/Description | Light gray, granular, partial putty- like solid with no odor. |
| Color | Light gray. | Odor | Odorless |
| Particulate Size | 600 µ | Odor Threshold | No data available |
| General Properties | | | |
| Boiling Point | No data available | Melting Point/Freezing Point | No data available |
| Decomposition Temperature | No data available | рН | Not relevant |
| Specific Gravity/Relative Density | 2.5 to 2.7 Water=1 | Water Solubility | Negligible < 0.1 % |
| Viscosity | No data available | | |
| Volatility | | | |
| Vapor Pressure | No data available | Vapor Density | No data available |
| Evaporation Rate | No data available | | |
| Flammability | - | • | - |
| Flash Point | No data available | UEL | No data available |
| LEL | No data available | Autoignition | No data available |
| Flammability (solid, gas) | Not flammable. | | |
| Environmental | - | • | - |
| Octanol/Water Partition coefficient | No data available | | |

Section 10: Stability and Reactivity

Reactivity

· No dangerous reaction known under conditions of normal use.

Chemical stability

• Stable under normal temperatures and pressures.

Possibility of hazardous reactions

· Hazardous polymerization not indicated.

Conditions to avoid

· None known.

Incompatible materials

· None known.

Hazardous decomposition products

· None known.

Section 11 - Toxicological Information

Information on toxicological effects

| | Components | | | | | |
|-------------------------------------|----------------|--|--|--|--|--|
| | 7631- 86-9 | Irritation: Eye-Rabbit • 25 mg 24 Hour(s) • Mild irritation | | | | |
| Titanium dioxide (1.77% TO 2.3%) | 13463- 67-7 | Irritation: Skin-Human • 300 μg 3 Day(s)-Intermittent • Mild irritation; Tumorigen / Carcinogen: Inhalation-Rat TCLo • 250 mg/m³ 6 Hour(s) 2 Year(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration:Tumors | | | | |
| Phosphoric acid (2.4% TO 4.55%) | 7664- 38-2 | Acute Toxicity: Ingestion/Oral-Rat LD50 • 1.25 g/kg; Lungs, Thorax, or Respiration:Acute pulmonary edema; Liver:Changes in liver weight; Inhalation-Rat LC50 • 25.5 mg/m³; Lungs, Thorax, or Respiration:Acute pulmonary edema; Liver:Changes in liver weight | | | | |
| Boron oxide (0.04% TO 0.35%) | 1303- 86-2 | Acute Toxicity: Ingestion/Oral-Rat LD50 • 3150 mg/kg; Irritation: Eye-Rabbit • 50 mg; Multi-dose Toxicity: Inhalation-Rat TCLo • 150 mg/m³ 2 Hour(s) 15 Day(s)-Intermittent; Sense Organs and Special Senses:Olfaction:Other changes; Lungs, Thorax, or Respiration:Other changes; Nutritional and Gross Metabolic:Gross Metabolite Changes:Weight loss or decreased weight gain | | | | |

| GHS Properties | Classification |
|-------------------------------|--|
| Acute toxicity | OSHA HCS 2012 • No data available |
| Skin corrosion/Irritation | OSHA HCS 2012 • Skin Irritation 2 |
| Serious eye damage/Irritation | OSHA HCS 2012 • Serious Eye Damage 1 |
| Skin sensitization | OSHA HCS 2012 • No data available |
| Respiratory sensitization | OSHA HCS 2012 • No data available |
| Aspiration Hazard | OSHA HCS 2012 • No data available |
| Carcinogenicity | OSHA HCS 2012 • Carcinogenicity 1A |
| Germ Cell Mutagenicity | OSHA HCS 2012 • No data available |
| Toxicity for Reproduction | OSHA HCS 2012 • No data available |
| STOT-SE | OSHA HCS 2012 • No data available |
| STOT-RE | OSHA HCS 2012 • Specific Target Organ Toxicity Repeated Exposure 2 |

Target Organs

Lungs

Route(s) of entry/exposure

· Inhalation, Skin, Eye, Ingestion

Medical Conditions
Aggravated by Exposure
Potential Health Effects
Inhalation

Any pre-existing conditions of the lungs. Disorders of the lungs.

Acute (Immediate)

• Exposure to dust may cause irritation.

Chronic (Delayed) • Chronic overexposure to dust containing respi

 Chronic overexposure to dust containing respirable sized crystalline silica can cause delayed lung injury (silicosis). Inhalation of dust containing crystalline silica pulmonary diseases such as asthma and lung disorder associated with smoking.

Skin

Acute (Immediate)

Causes skin irritation. Exposure to dust may cause irritation.

Chronic (Delayed)

No data available.

Eye

Acute (Immediate)

• Causes serious eye irritation. Excessive concentrations of nuisance dust in the workplace may reduce visibility and may cause unpleasant deposits in eyes.

Chronic (Delayed)

· No data available.

Ingestion

Acute (Immediate)

• Excessive concentrations of nuisance dust in the workplace may cause mechanical irritation to mucous membranes.

Chronic (Delayed)

No data available.

Carcinogenic Effects

 May cause cancer. IARC studies have shown sufficient evidence from animal studies to categorize crystalline silica as a group 1 carcinogen.

| Carcinogenic Effects | | | | | |
|----------------------|------------|------------------------------|-----------------------------|--|--|
| CAS IARC NTP | | | | | |
| Cristobalite | 14464-46-1 | Group 1-Carcinogenic | Not Listed | | |
| Quartz | 14808-60-7 | Group 1-Carcinogenic | Known Human Carcinogen | | |
| Titanium dioxide | 13463-67-7 | Group 2B-Possible Carcinogen | Evidence of Carcinogenicity | | |

Key to abbreviations

MLD = Mild

TC = Toxic Concentration

Section 12 - Ecological Information

Toxicity

Material data lacking.

Persistence and degradability

Material data lacking.

Bioaccumulative potential

Material data lacking.

Mobility in Soil

Material data lacking.

Other adverse effects

No studies have been found.

Section 13 - Disposal Considerations

Waste treatment methods

Product waste

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

• Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

Preparation Date: 23/November/2015

Revision Date: 13/March/2018

Page 9 of 14

Format: GHS Language: English (US)
OSHA HCS 2012, WHMIS

| | UN number | UN proper shipping name | Transport hazard class (es) | Packing group | Environmental hazards |
|-----------|--------------|-------------------------|-----------------------------|------------------|--------------------------|
| DOT | NDA | Not regulated | NDA | NDA | NDA |
| TDG | NDA | Not regulated | NDA | NDA | NDA |
| IATA/ICAO | NDA | Not regulated | NDA | NDA | NDA |

Special precautions for user • None known.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

· Not relevant.

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture SARA Hazard Classifications • Chronic

| | State Right To Know | | | | |
|--------------------------------------|---------------------|-----|-----|-----|--|
| Component | CAS | MA | NJ | PA | |
| Aluminum oxide | 1344-28-1 | Yes | Yes | Yes | |
| Aluminum(III) silicate (2:1) | 1302-76-7 | No | No | No | |
| Bauxite | 1318-16-7 | No | No | No | |
| Bentonite | 1302-78-9 | No | No | No | |
| Boron oxide | 1303-86-2 | Yes | Yes | Yes | |
| Cristobalite | 14464-46-1 | Yes | Yes | Yes | |
| Iron oxide | 1309-37-1 | Yes | Yes | Yes | |
| Phosphoric acid | 7664-38-2 | Yes | Yes | Yes | |
| Phosphoric acid, aluminum salt (1:3) | 13530-50-2 | No | No | No | |
| Quartz | 14808-60-7 | Yes | Yes | Yes | |
| Silica, amorphous | 7631-86-9 | Yes | No | Yes | |
| Titanium dioxide | 13463-67-7 | Yes | Yes | Yes | |
| Urea, 1,3-diethyl-2- thio- | 105-55-5 | Yes | No | No | |
| Water | 7732-18-5 | No | No | No | |

| Inventory | | | | | |
|------------------------------|------------|------------|------|--|--|
| Component | CAS | Canada DSL | TSCA | | |
| Aluminum oxide | 1344-28-1 | Yes | Yes | | |
| Aluminum(III) silicate (2:1) | 1302-76-7 | Yes | No | | |
| Bauxite | 1318-16-7 | No | No | | |
| Bentonite | 1302-78-9 | Yes | Yes | | |
| Boron oxide | 1303-86-2 | Yes | Yes | | |
| Cristobalite | 14464-46-1 | Yes | Yes | | |
| Iron oxide | 1309-37-1 | Yes | Yes | | |
| | | | | | |

| Phosphoric acid | 7664-38-2 | Yes | Yes |
|--------------------------------------|------------|-----|-----|
| Phosphoric acid, aluminum salt (1:3) | 13530-50-2 | Yes | Yes |
| Quartz | 14808-60-7 | Yes | Yes |
| Silica, amorphous | 7631-86-9 | Yes | Yes |
| Titanium dioxide | 13463-67-7 | Yes | Yes |
| Urea, 1,3-diethyl-2-thio- | 105-55-5 | Yes | Yes |
| Water | 7732-18-5 | Yes | Yes |

Canada

| Labor Canada - WHMIS 1988 - Classifications of Substances | | |
|--|------------|---|
| Phosphoric acid, aluminum salt (1:3) | 13530-50-2 | Not Listed |
| • Urea, 1,3-diethyl-2-thio- | 105-55-5 | Not Listed |
| Bauxite | 1318-16-7 | Not Listed |
| Boron oxide | 1303-86-2 | Not Listed |
| • Iron oxide | 1309-37-1 | Uncontrolled product according to WHMIS classification criteria |
| Phosphoric acid | 7664-38-2 | E (including 5-35% in aqueous solution, 35%, aqueous solution 35-80%, 85% or less) |
| Titanium dioxide | 13463-67-7 | D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Titanium dioxide, mixture containing on Health Canada's WHMIS Division website.) |
| Aluminum oxide | 1344-28-1 | Uncontrolled product according to WHMIS classification criteria |
| Cristobalite | 14464-46-1 | D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS Division website.) |
| Silica, amorphous | 7631-86-9 | Uncontrolled product according to WHMIS classification criteria |
| • Quartz | 14808-60-7 | D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS Division website.) |
| Aluminum(III) silicate (2:1) | 1302-76-7 | Not Listed |
| Bentonite | 1302-78-9 | D2A |
| | | Uncontrolled product |

| • Water | 7732-18-5 | according to WHMIS classification criteria |
|--|------------|--|
| Canada - WHMIS 1988 - Ingredient Disclosure List | | |
| Phosphoric acid, aluminum salt (1:3) | 13530-50-2 | Not Listed |
| Urea, 1,3-diethyl-2-thio- | 105-55-5 | Not Listed |
| Bauxite | 1318-16-7 | 1 % |
| Boron oxide | 1303-86-2 | 1 % |
| Iron oxide | 1309-37-1 | 1 % |
| Phosphoric acid | 7664-38-2 | 1 % |
| Titanium dioxide | 13463-67-7 | Not Listed |
| Aluminum oxide | 1344-28-1 | 1 % |
| Cristobalite | 14464-46-1 | 1 % |
| Silica, amorphous | 7631-86-9 | 1 % |
| • Quartz | 14808-60-7 | 1 % |
| Aluminum(III) silicate (2:1) | 1302-76-7 | Not Listed |
| Bentonite | 1302-78-9 | Not Listed |
| • Water | 7732-18-5 | Not Listed |

United States

| Environment | | |
|--|------------|--|
| U.S CERCLA/SARA - Hazardous Substances and their Reportable Quantities | | |
| Phosphoric acid, aluminum salt (1:3) | 13530-50-2 | Not Listed |
| Urea, 1,3-diethyl-2-thio- | 105-55-5 | Not Listed |
| Bauxite | 1318-16-7 | Not Listed |
| Boron oxide | 1303-86-2 | Not Listed |
| • Iron oxide | 1309-37-1 | Not Listed |
| Phosphoric acid | 7664-38-2 | 5000 lb final RQ; 2270 kg final RQ |
| Titanium dioxide | 13463-67-7 | Not Listed |
| Aluminum oxide | 1344-28-1 | Not Listed |
| Cristobalite | 14464-46-1 | Not Listed |
| Silica, amorphous | 7631-86-9 | Not Listed |
| • Quartz | 14808-60-7 | Not Listed |
| Aluminum(III) silicate (2:1) | 1302-76-7 | Not Listed |
| Bentonite | 1302-78-9 | Not Listed |
| • Water | 7732-18-5 | Not Listed |
| U.S CERCLA/SARA - Section 313 - Emission Reporting | | |
| Phosphoric acid, aluminum salt (1:3) | 13530-50-2 | Not Listed |
| Urea, 1,3-diethyl-2-thio- | 105-55-5 | Not Listed |
| Bauxite | 1318-16-7 | Not Listed |
| Boron oxide | 1303-86-2 | Not Listed |
| Iron oxide | 1309-37-1 | Not Listed |
| Phosphoric acid | 7664-38-2 | Not Listed |
| Titanium dioxide | 13463-67-7 | Not Listed |
| Aluminum oxide | 1344-28-1 | 1.0 % de minimis concentration (fibrous forms) |
| Cristobalite | 14464-46-1 | Not Listed |
| Silica, amorphous | 7631-86-9 | Not Listed |
| • Quartz | 14808-60-7 | Not Listed |
| Aluminum(III) silicate (2:1) | 1302-76-7 | Not Listed |
| Bentonite | 1302-78-9 | Not Listed |
| • Water | 7732-18-5 | Not Listed |

United States - California

| Environment U.S California - Proposition 65 - Carcinogens List | | |
|--|------------|---|
| Phosphoric acid, aluminum salt (1:3) | 13530-50-2 | Not Listed |
| Urea, 1,3-diethyl-2-thio- | 105-55-5 | Not Listed |
| Bauxite | 1318-16-7 | Not Listed |
| Boron oxide | 1303-86-2 | Not Listed |
| Iron oxide | 1309-37-1 | Not Listed |
| Phosphoric acid | 7664-38-2 | Not Listed |
| Titanium dioxide | 13463-67-7 | carcinogen, 9/2/2011 (airborne, unbound particles of respirable size) |
| Aluminum oxide | 1344-28-1 | Not Listed |
| Cristobalite | 14464-46-1 | Not Listed |
| Silica, amorphous | 7631-86-9 | Not Listed |
| • Quartz | 14808-60-7 | Not Listed |
| Aluminum(III) silicate (2:1) | 1302-76-7 | Not Listed |
| Bentonite | 1302-78-9 | Not Listed |
| Water | 7732-18-5 | Not Listed |
| | | |

United States - Pennsylvania

| Phosphoric acid, aluminum salt (1:3) | 13530-50-2 | Not Listed |
|--------------------------------------|------------|------------|
| Urea, 1,3-diethyl-2-thio- | 105-55-5 | Not Listed |
| Bauxite | 1318-16-7 | Not Listed |
| Boron oxide | 1303-86-2 | Not Listed |
| on oxide | 1309-37-1 | Not Listed |
| Phosphoric acid | 7664-38-2 | |
| Titanium dioxide | 13463-67-7 | Not Listed |
| Aluminum oxide | 1344-28-1 | |
| Cristobalite | 14464-46-1 | Not Listed |
| Silica, amorphous | 7631-86-9 | Not Listed |
| Quartz | 14808-60-7 | Not Listed |
| Aluminum(III) silicate (2:1) | 1302-76-7 | Not Listed |
| Bentonite | 1302-78-9 | Not Listed |
| Vater | 7732-18-5 | Not Listed |

Other Information

 WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information

Revision Date

Last Revision Date

Preparation Date

Disclaimer/Statement of

- 13/March/2018
- 23/November/201523/November/2015
- The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation,

Liability

disposal and release. Reno Refractories MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key to abbreviationsNDA = No data available