



RENO REFRACTORIES, INC

COAT IT CRM

---

TECHNICAL DATA SHEET

---

**COAT IT CRM** is a protective surface treatment/coating for refractory or metal. This is a durable coating that seals the refractory surface for protection against corrosion and adhesion.

**SERVICE TEMPERATURE:** 2900°F  
**MATERIAL REQUIRED FOR ESTIMATING:** 185 lbs./cu. ft. (One lb/sqft @ 2 mm thick)  
**LIQUID ADDITIVE REQUIRED:** 25%

**TYPICAL CHEMICAL ANALYSIS** (Reducing Conditions)

Al <sub>2</sub> O <sub>3</sub>	SiO <sub>2</sub>	Cr <sub>2</sub> O <sub>3</sub>	Fe <sub>2</sub> O <sub>3</sub>	Alkalies	Other
85	6.7	8	0.05	0.17	0.08

**PACKAGING:** 50 lb. Bags, 80 per Pallet (4,000 lbs)

17-067

439500 L – 5/3/17

---

The data presented represents typical average results obtained by testing under ASTM or other acceptable procedures as required. They are subject to normal variations and should not be used for specification purposes.

Reno Refractories, Inc. PO Box 201, Morris, Alabama 35116  
205.647.0240 | Toll Free 1.800.741.7366