

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 11/15/2021

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Trade name : Reno ElectroShot™ 370

Product code : 190940

1.2. Recommended use and restrictions on use

Recommended use : Refractory Applications

1.3. Supplier

Reno Refractories, Inc. 601 Reno Drive P.O. Box 201 Morris Al 35116 - Unite

Morris, AL 35116 - United States T 205-647-0240 - F 205-647-6854

sales@r-ref.com - www.renorefractories.com

1.4. Emergency telephone number

Emergency number : 1-800-262-8200 CHEMTREC

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Corrosive to metals Category 1 Carcinogenicity Category 1A May be corrosive to metals

May cause cancer

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)





Signal word (GHS US) : Danger

Hazard statements (GHS US) : May be corrosive to metals

May cause cancer

Precautionary statements (GHS US) : Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep only in original container.

Wear protective gloves/protective clothing/eye protection/face protection.

If exposed or concerned: Get medical advice/attention.

Absorb spillage to prevent material-damage.

Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container to hazardous or special waste collection point, in accordance

with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS US classification
Titanium dioxide	(CAS-No.) 13463-67-7	≤ 0.841	Carc. 2, H351

11/15/2021 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Crystalline silica	(CAS-No.) 14808-60-7	≤ 0.3	Carc. 1A, H350 STOT RE 1, H372
Silicon carbide	(CAS-No.) 409-21-2	≤ 0.25	Carc. 1B, H350

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire

: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting

: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not

handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Wear personal protective equipment. Floors, walls and other surfaces in the hazard area must be cleaned regularly.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

11/15/2021 EN (English US) 2/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in corrosive resistant container with a resistant inner liner. Keep only in original container.

Store in a well-ventilated place. Keep cool.

Incompatible materials : Metals.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Titanium dioxide (13463-67-7) USA - ACGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m²) 10 mg/m² Remark (ACGIH) TIL è Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen) Regulatory reference ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Titanium dioxide (Total dust) DSHA PEL (TWA) (mg/m²) Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 Crystalline silica (14808-60-7) USA - ACGIH - Occupational Exposure Limits Local name Silica crystalline - quartz ACGIH 70X4 (mg/m²) 0.025 mg/m² (Respirable fraction) Remark (ACGIH) Regulatory reference ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Quartz (Respirable) (Silica: Crystalline) Remark (OSHA) Table Z-3. For OSHA PEL (TWA): Use formulas: (250 / (%SiO2+5))) for mppcf and (10 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m²) 3 mg/m² (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm² (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm² (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm² (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm² (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm² (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm² (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm² (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 10 mg/m² (finalable fraction. T	Reno ElectroShot™ 370		
USA - ACGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m²) Remark (ACGIH) Regulatory reference ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Titanium dioxide (Total dust) DSHA PEL (TWA) (mg/m²) Titanium dioxide (Total dust) Titanium dioxide Titanium dioxid	No additional information available		
Local name Titanium dioxide ACGIH TWA (mg/m³) 10 mg/m³ Regwark (ACGIH) Regulatory reference ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name OSHA PEL (TWA) (mg/m³) 15 mg/m³ Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 Crystalline silica (14808-60-7) USA - ACGIH - Occupational Exposure Limits Local name Silica crystaline - quartz ACGIH TWA (mg/m³) 0.025 mg/m³ (Respirable fraction) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinoger Regulatory reference (US-OSHA) Table Z-3. For OSHA PEL (TWA): Use formulas: (250 / (%SiO2+5)) for mppof and (10 mg/m² / (%SiO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m²) Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m²) 3 mg/m² (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm² (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm² (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm² (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm² (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm² (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm² (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm² (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm² (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline sili	Titanium dioxide (13463-67-7)		
ACGIH TWA (mg/m³) Remark (ACGIH) Remark (ACGIH) Remark (ACGIH) Remark (ACGIH) Regulatory reference USA - OSHA - Occupational Exposure Limits Local name OSHA PEL (TWA) (mg/m³) Regulatory reference (US-OSHA) OSHA - Occupational Exposure Limits Local name Cuartz (Respirable) (Silica: Crystalline) Remark (OSHA) Table Z-3. For OSHA PEL (TWA): Use formulas: (250 / (%SiO2+5)) for mpporf and (10 mg/m³) (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA - Occupational Exposure Limits Local name Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name Silicon carbide (409-21-2) Regulatory reference Silicon Silicon Carbide (409-21-2) Regulatory reference Silicon Carbide (409-21-2) Silic	USA - ACGIH - Occupational Exposure Lin	nits	
Remark (ACGIH) Regulatory reference ACGIH 2020 ITU® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen) ACGIH 2020 ISSA - OSHA - Occupational Exposure Limits Local name SIlica crystalline silica (14808-60-7) ISSA - ACGIH - Occupational Exposure Limits Local name Silica crystalline - quartz ACGIH TWA (mg/m²) Regulatory reference (US-OSHA) COSHA Annotated Table Z-1 CVF graph and CACGIH ACGIH TWA (mg/m²) Regulatory reference ACGIH 2020 ISSA - ACGIH - Occupational Exposure Limits Local name ACGIH 2020 ISSA - OSHA - Occupational Exposure Limits Local name Quartz (Respirable) (Silica: Crystalline) Regulatory reference (US-OSHA) Table Z-3. For OSHA PEL (TWA): Use formulas: (250 / (%SiO2+5)) for mppcf and (10 mg/m3 / (%SiO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m²) ACGIH TWA (mg/m²) Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m²) ACGIH TWA (mg/m²) ACGIH TWA (mg/m²) Respirable fraction. The value is for particulate matter containing no asbestor and < 1% crystalline silica) O.1 fibers/cm² (Respirable fibers: length > 5 μm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase contrast illumination) 10 mg/m² (Inhalable fraction. The value is for particulate matter containing no asbestor and < 1% crystalline silica) Non fibrous = TLV® Basis: URT irr Fibrous (including whiskers) = TLV® Basis: Mesothelioma; cancer. Notations: A2 (Suspected Human Carcinogen) Regulatory reference USA - OSHA - Occupational Exposure Limits Local name Silicon carbide Silicon carbide fraction. The value is for particulate matter containing no asbestor and < 1% crystalline silica) Non fibrous = TLV® Basis: URT irr Fibrous (including whiskers) = TLV® Basis: Mesothelioma; cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH 2020 USA - OSHA	Local name	Titanium dioxide	
Regulatory reference USA - OSHA - Occupational Exposure Limits Local name OSHA PEL (TWA) (mg/m³) 15 mg/m³ Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 Crystalline silica (14808-60-7) USA - AGGIH - Occupational Exposure Limits Local name Silica crystalline - quartz ACGIH TWA (mg/m³) 0.025 mg/m³ (Respirable fraction) Regulatory reference US-OSHA PEL (TWA) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinoger ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Quartz (Respirable) (Silica: Crystalline) Remark (OSHA) Table Z-3. For OSHA PEL (TWA); Use formulas: (250 / (%SiO2+5)) for mppcf and (10 mg/m³ / (%SiO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1. OSHA Annotated Table Z-3 Mineral Dusts Silicon carbide (409-21-2) USA - AGGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m²) 3 mg/m² (Respirable fraction. The value is for particulate matter containing no asbestc and <1% crystalline silica) 0.1 fibers/cm² (Respirable fibers: length > 5 μm; aspect ratio ≥ 3.1, as determined by the membrane filer method at 400-450X magnification (4-mm objective), using phase contrast ill ulmination ill mination in the membrane filer method at 400-450X magnification (4-mm objective), using phase contrast ill ulmination ill mination illl mination illl mination illl mination illl mination illl mination ill	ACGIH TWA (mg/m³)	10 mg/m³	
USA - OSHA - Occupational Exposure Limits Local name Titanium dioxide (Total dust) DSHA PEL (TWA) (mg/m²) Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 Crystalline silica (14808-60-7) USA - ACGIH - Occupational Exposure Limits Local name Silica crystalline - quartz ACGIH TWA (mg/m²) 0.025 mg/m² (Respirable fraction) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinoger ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Quartz (Respirable) (Silica: Crystalline) Remark (OSHA) Table Z-3. For OSHA PEL (TWA): Use formulas: (250 / (%,SiO2+5)) for mppcf and (10 mg/m²) / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m²) 3 mg/m² (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm² (Respirable fibers: length > 5 μm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase contrast illumination) Remark (ACGIH) Non fibrous = TLV® Basis: URT irr Fibrous (including whiskers) = TLV® Basis: Mesothelioma; cancer. Notations: A2 (Suspected Human Carcinogen) Regulatory reference USA - OSHA - Occupational Exposure Limits Local name Silicon carbide Silicon carbide OSHA PEL (TWA) (mg/m²) 15 mg/m² (Respirable fraction)	Remark (ACGIH)	TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen)	
Titanium dioxide (Total dust) OSHA PEL (TWA) (mg/m³) 15 mg/m³ Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 Crystalline silica (14808-60-7) USA - ACGIH - Occupational Exposure Limits Local name Silica crystaline - quartz ACGIH TWA (mg/m³) 0.025 mg/m³ (Respirable fraction) Remark (ACGIH) Regulatory reference USA - OSHA - Occupational Exposure Limits Local name Quartz (Respirable) (Silica: Crystalline) Remark (OSHA) Table Z-3. For OSHA PEL (TWA): Use formulas: (250 / (%SiO2+5)) for mppcf and (10 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name Silicon carbide (409-21-1) 10 mg/m³ (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 10 mg/m³ ((Inhalable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 10 mg/m³ (Inhalable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 10 mg/m³ (Inhalable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 10 mg/m³ (Inhalable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) Regulatory reference ACGIH - Occupational Exposure Limits Local name Silicon carbide Silicon carbide Silicon carbide Silicon carbide Silicon carbide Silicon arbide Silicon arbide Silicon arbide Silicon arbide Silicon fraction Silicon fractio	Regulatory reference	ACGIH 2020	
ACGIH TWA (mg/m³) ASHA PEL (TWA) (mg/m³) 15 mg/m³ Regulatory reference (US-OSHA) OSHA Annotated Table Z-1 Silica crystalline - quartz ACGIH - Occupational Exposure Limits Local name Silica crystalline - quartz ACGIH TWA (mg/m³) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinoger Regulatory reference USA - OSHA - Occupational Exposure Limits Local name Quartz (Respirable) (Silica: Crystalline) Remark (OSHA) Table Z-3. For OSHA PEL (TWA); Use formulas: (250 / (%SiO2+5)) for mppcf and (10 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m³) 3 mg/m³ (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm² (Respirable fibers: length > 5 μm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase contrast illumination) 10 mg/m³ ((Inhalable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 10.1 fibers/cm² (Respirable fibers: length > 5 μm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase contrast illumination) 10 mg/m³ ((Inhalable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) Regulatory reference ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Silicon carbide Silicon filter detroit of the silican carbide Silicon filter detroit of the sil	USA - OSHA - Occupational Exposure Lim	its	
Regulatory reference (US-OSHA) Crystalline silica (14808-60-7) USA - ACGIH - Occupational Exposure Limits Local name Silica crystalline - quartz ACGIH TWA (mg/m³) 0.025 mg/m³ (Respirable fraction) Remark (ACGIH) Regulatory reference ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Quartz (Respirable) (Silica: Crystalline) Regulatory reference (US-OSHA) Table Z-3. For OSHA PEL (TWA): Use formulas: (250 / (%SiO2+5)) for mppcf and (10 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m²) 3 mg/m³ (Respirable fraction. The value is for particulate matter containing no asbestc and < 1% crystalline silica) 0.1 fibers/cm³ (Respirable fibers: length > 5 μm; aspect ratio ≥ 3:1, as determined by the membrane lifter method at 400-450X magnification (4-mm objective), using phase contrast illumination) 10 mg/m³ (Inhalable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm³ (Respirable fibers: length > 5 μm; aspect ratio ≥ 3:1, as determined by the membrane lifter method at 400-450X magnification (4-mm objective), using phase contrast illumination) 10 mg/m³ (Inhalable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.5 (Suspected Human Carcinogen) Regulatory reference ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Silicon carbide	Local name	Titanium dioxide (Total dust)	
Crystalline silica (14808-60-7) USA - ACGIH - Occupational Exposure Limits Local name Silica crystalline - quartz ACGIH TWA (mg/m³) 0.025 mg/m³ (Respirable fraction) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinoger ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Quartz (Respirable) (Silica: Crystalline) Remark (OSHA) Table Z-3. For OSHA PEL (TWA): Use formulas: (250 / (%SiO2+5)) for mppcf and (10 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name Silicon carbide ACGIH TWA (mg/m³) Silicon carbide Silicon carbide ACGIH TWA (mg/m³) Silicon carbide fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm² (Respirable fibers: length > 5 μm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase contrast illumination) 10 mg/m³ (Inhalable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) Non fibrous = TLV® Basis: URT irr Fibrous (including whiskers) = TLV® Basis: Mesothelioma; cancer. Notations: A2 (Suspected Human Carcinogen) ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Silicon carbide	OSHA PEL (TWA) (mg/m³)	15 mg/m³	
USA - ACGIH - Occupational Exposure Limits Local name Silica crystaline - quartz 0.025 mg/m³ (Respirable fraction) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinoger ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Quartz (Respirable) (Silica: Crystalline) Remark (OSHA) Table Z-3. For OSHA PEL (TWA): Use formulas: (250 / (%SIO2+5)) for mppcf and (10 mg/m³ / (%SIO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name Silicon carbide ACGIH TWA (mg/m³) Silicon carbide ACGIH TWA (mg/m³) Silicon carbide Nor fibers/cm³ (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm³ (Respirable fibers: length > 5 µm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase contrast illumination) 10 mg/m³ (Inhalable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) Non fibrous = TLV® Basis: URT irr Fibrous (including whiskers) = TLV® Basis: Mesothelioma; cancer. Notations: A2 (Suspected Human Carcinogen) Regulatory reference ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Silicon carbide Silicon carbide Silicon farbide Silicon carbide Silicon farbide Silicon carbide Silicon farbide	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	
Silica crystaline - quartz ACGIH TWA (mg/m³) 0.025 mg/m³ (Respirable fraction) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinoger Acgulatory reference ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Remark (OSHA) Table Z-3. For OSHA PEL (TWA): Use formulas: (250 / (%SiO2+5)) for mppcf and (10 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m³) 3 mg/m³ (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm³ (Respirable fibers: length > 5 μm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase contrast illumination) 10 mg/m³ (Inhalable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) Remark (ACGIH) Non fibrous = TLV® Basis: URT irr Fibrous (including whiskers) = TLV® Basis: Mesothelioma; cancer. Notations: A2 (Suspected Human Carcinogen) Regulatory reference ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Silicon carbide OSHA PEL (TWA) (mg/m³) 15 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)	Crystalline silica (14808-60-7)		
ACGIH TWA (mg/m³) 0.025 mg/m³ (Respirable fraction) Remark (ACGIH) TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinoger ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Quartz (Respirable) (Silica: Crystalline) Remark (OSHA) Table Z-3. For OSHA PEL (TWA): Use formulas: (250 / (%SiO2+5)) for mppcf and (10 mg/m³ / (%SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m³) 3 mg/m³ (Respirable fraction. The value is for particulate matter containing no asbestc and < 1% crystalline silica) 0.1 fibers/cm³ (Respirable fibers: length > 5 μm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase contrast illumination) 10 mg/m³ (Inhalable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) Remark (ACGIH) Non fibrous = TLV® Basis: URT irr Fibrous (including whiskers) = TLV® Basis: Mesothelioma; cancer. Notations: A2 (Suspected Human Carcinogen) Regulatory reference ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Silicon carbide OSHA PEL (TWA) (mg/m³) 15 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)	USA - ACGIH - Occupational Exposure Lin	nits	
Regulatory reference ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Remark (OSHA) Quartz (Respirable) (Silica: Crystalline) Regulatory reference (US-OSHA) ACGIH 2020 USA - OSHA PEL (TWA): Use formulas: (250 / (%SiO2+5)) for mppcf and (10 mg/m³ (Respirable) (Silica: Crystalline) Remark (OSHA) Quartz (Respirable) (Silica: Crystalline) Acgulatory reference (US-OSHA) OSHA PEL (TWA): Use formulas: (250 / (%SiO2+5)) for mppcf and (10 mg/m³ (7 %SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m³) 3 mg/m³ (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm³ (Respirable fibers: length > 5 μm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase contrast illumination) 10 mg/m³ (Inhalable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) Non fibrous = TLV® Basis: URT irr Fibrous (including whiskers) = TLV® Basis: Mesothelioma; cancer. Notations: A2 (Suspected Human Carcinogen) Regulatory reference USA - OSHA - Occupational Exposure Limits Local name OSHA PEL (TWA) (mg/m³) 15 mg/m³ (Respirable fraction)	Local name	Silica crystaline - quartz	
Regulatory reference ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Remark (OSHA) Quartz (Respirable) (Silica: Crystalline) Regulatory reference (US-OSHA) ACGIH 2020 USA - OSHA PEL (TWA): Use formulas: (250 / (%SiO2+5)) for mppcf and (10 mg/m³ (Respirable) (Silica: Crystalline) Remark (OSHA) Quartz (Respirable) (Silica: Crystalline) Acgulatory reference (US-OSHA) OSHA PEL (TWA): Use formulas: (250 / (%SiO2+5)) for mppcf and (10 mg/m³ (7 %SiO2+2)) for mg/m³. CAS No. source: eCFR Table Z-1. Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m³) 3 mg/m³ (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm³ (Respirable fibers: length > 5 μm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase contrast illumination) 10 mg/m³ (Inhalable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) Non fibrous = TLV® Basis: URT irr Fibrous (including whiskers) = TLV® Basis: Mesothelioma; cancer. Notations: A2 (Suspected Human Carcinogen) Regulatory reference USA - OSHA - Occupational Exposure Limits Local name OSHA PEL (TWA) (mg/m³) 15 mg/m³ (Respirable fraction)	ACGIH TWA (mg/m³)	0.025 mg/m³ (Respirable fraction)	
USA - OSHA - Occupational Exposure Limits Local name Remark (OSHA) Table Z-3. For OSHA PEL (TWA): Use formulas: (250 / (%SiO2+5)) for mppcf and (10 mg/m3 / (%SiO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m³) 3 mg/m³ (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm³ (Respirable fibers: length > 5 μm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase contrast illumination) 10 mg/m³ (Inhalable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) Non fibrous = TLV® Basis: URT irr Fibrous (including whiskers) = TLV® Basis: Mesothelioma; cancer. Notations: A2 (Suspected Human Carcinogen) Regulatory reference USA - OSHA - Occupational Exposure Limits Local name Silicon carbide OSHA PEL (TWA) (mg/m³) 15 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)	Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)	
USA - OSHA - Occupational Exposure Limits Local name Remark (OSHA) Table Z-3. For OSHA PEL (TWA): Use formulas: (250 / (%SiO2+5)) for mppcf and (10 mg/m3 / (%SiO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m³) 3 mg/m³ (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm³ (Respirable fibers: length > 5 μm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase contrast illumination) 10 mg/m³ (Inhalable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) Non fibrous = TLV® Basis: URT irr Fibrous (including whiskers) = TLV® Basis: Mesothelioma; cancer. Notations: A2 (Suspected Human Carcinogen) Regulatory reference USA - OSHA - Occupational Exposure Limits Local name Silicon carbide OSHA PEL (TWA) (mg/m³) 15 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)	Regulatory reference	ACGIH 2020	
Table Z-3. For OSHA PEL (TWA): Use formulas: (250 / (%SiO2+5)) for mppcf and (10 mg/m3 / (%SiO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m³) 3 mg/m³ (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm³ (Respirable fibers: length > 5 μm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase contrast illumination) 10 mg/m³ (Inhalable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) Remark (ACGIH) Non fibrous = TLV® Basis: URT irr Fibrous (including whiskers) = TLV® Basis: Mesothelioma; cancer. Notations: A2 (Suspected Human Carcinogen) Regulatory reference ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name OSHA PEL (TWA) (mg/m³) 15 mg/m³ (Respirable fraction)		its	
mg/m3 / (%SiO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1. Regulatory reference (US-OSHA) OSHA Annotated Table Z-3 Mineral Dusts Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m³) 3 mg/m³ (Respirable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) 0.1 fibers/cm³ (Respirable fibers: length > 5 μm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase contrast illumination) 10 mg/m³ (Inhalable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) Remark (ACGIH) Non fibrous = TLV® Basis: URT irr Fibrous (including whiskers) = TLV® Basis: Mesothelioma; cancer. Notations: A2 (Suspected Human Carcinogen) Regulatory reference ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Silicon carbide OSHA PEL (TWA) (mg/m³) 15 mg/m³ (Respirable fraction)	Local name	Quartz (Respirable) (Silica: Crystalline)	
Silicon carbide (409-21-2) USA - ACGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m³) ACGIH TWA (mg/m³) Silicon carbide ACGIH TWA (mg/m³) ACGIH TWA (mg/m³) Silicon carbide ACGIH TWA (mg/m³) Silicon carbide fraction. The value is for particulate matter containing no asbestor and < 1% crystalline silica) 0.1 fibers/cm³ (Respirable fibers: length > 5 μm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase contrast illumination) 10 mg/m³ (Inhalable fraction. The value is for particulate matter containing no asbestor and < 1% crystalline silica) Remark (ACGIH) Non fibrous = TLV® Basis: URT irr Fibrous (including whiskers) = TLV® Basis: Mesothelioma; cancer. Notations: A2 (Suspected Human Carcinogen) Regulatory reference ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Silicon carbide OSHA PEL (TWA) (mg/m³) 15 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)	Remark (OSHA)	Table Z-3. For OSHA PEL (TWA): Use formulas: (250 / (%SiO2+5)) for mppcf and (10 mg/m3 / (%SiO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1.	
USA - ACGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m³) Silicon carbide 3 mg/m³ (Respirable fraction. The value is for particulate matter containing no asbestor and < 1% crystalline silica) 0.1 fibers/cm³ (Respirable fibers: length > 5 μm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase contrast illumination) 10 mg/m³ (Inhalable fraction. The value is for particulate matter containing no asbestor and < 1% crystalline silica) Remark (ACGIH) Non fibrous = TLV® Basis: URT irr Fibrous (including whiskers) = TLV® Basis: Mesothelioma; cancer. Notations: A2 (Suspected Human Carcinogen) Regulatory reference ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Silicon carbide OSHA PEL (TWA) (mg/m³) 15 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts	
USA - ACGIH - Occupational Exposure Limits Local name ACGIH TWA (mg/m³) Silicon carbide 3 mg/m³ (Respirable fraction. The value is for particulate matter containing no asbestor and < 1% crystalline silica) 0.1 fibers/cm³ (Respirable fibers: length > 5 μm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase contrast illumination) 10 mg/m³ (Inhalable fraction. The value is for particulate matter containing no asbestor and < 1% crystalline silica) Remark (ACGIH) Non fibrous = TLV® Basis: URT irr Fibrous (including whiskers) = TLV® Basis: Mesothelioma; cancer. Notations: A2 (Suspected Human Carcinogen) Regulatory reference ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Silicon carbide OSHA PEL (TWA) (mg/m³) 15 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)	Silicon carbide (409-21-2)		
Silicon carbide ACGIH TWA (mg/m³) 3 mg/m³ (Respirable fraction. The value is for particulate matter containing no asbestor and < 1% crystalline silica) 0.1 fibers/cm³ (Respirable fibers: length > 5 μm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase contrast illumination) 10 mg/m³ (Inhalable fraction. The value is for particulate matter containing no asbestor and < 1% crystalline silica) Remark (ACGIH) Non fibrous = TLV® Basis: URT irr Fibrous (including whiskers) = TLV® Basis: Mesothelioma; cancer. Notations: A2 (Suspected Human Carcinogen) Regulatory reference ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Silicon carbide OSHA PEL (TWA) (mg/m³) 15 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)	, ,	nits	
and < 1% crystalline silica) 0.1 fibers/cm³ (Respirable fibers: length > 5 μm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase contrast illumination) 10 mg/m³ (Inhalable fraction. The value is for particulate matter containing no asbesto and < 1% crystalline silica) Remark (ACGIH) Non fibrous = TLV® Basis: URT irr Fibrous (including whiskers) = TLV® Basis: Mesothelioma; cancer. Notations: A2 (Suspected Human Carcinogen) Regulatory reference USA - OSHA - Occupational Exposure Limits Local name Silicon carbide OSHA PEL (TWA) (mg/m³) 15 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)	Local name		
Fibrous (including whiskers) = TLV® Basis: Mesothelioma; cancer. Notations: A2 (Suspected Human Carcinogen) Regulatory reference ACGIH 2020 USA - OSHA - Occupational Exposure Limits Local name Silicon carbide OSHA PEL (TWA) (mg/m³) 15 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)	ACGIH TWA (mg/m³)	0.1 fibers/cm³ (Respirable fibers: length > 5 µm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase-contrast illumination) 10 mg/m³ (Inhalable fraction. The value is for particulate matter containing no asbestos	
USA - OSHA - Occupational Exposure Limits Local name Silicon carbide OSHA PEL (TWA) (mg/m³) 15 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)	Remark (ACGIH)	Fibrous (including whiskers) = TLV® Basis: Mesothelioma; cancer. Notations: A2	
Local name Silicon carbide OSHA PEL (TWA) (mg/m³) 15 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)	Regulatory reference	ACGIH 2020	
OSHA PEL (TWA) (mg/m³) 15 mg/m³ (Total dust) 5 mg/m³ (Respirable fraction)	USA - OSHA - Occupational Exposure Lim	its	
5 mg/m³ (Respirable fraction)	Local name	Silicon carbide	
Regulatory reference (US-OSHA) OSHA Annotated Table Z-1	OSHA PEL (TWA) (mg/m³)		
	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1	

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

11/15/2021 EN (English US) 3/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid

Appearance : Granular powder.

Color : Gray

Odor : Almost odorless Odor threshold No data available рΗ No data available Melting point No data available Freezing point Not applicable Boiling point : No data available Flash point Not applicable Relative evaporation rate (butyl acetate=1) : No data available : Non flammable. Flammability (solid, gas) Vapor pressure No data available Relative vapor density at 20 °C : No data available Relative density No data available Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : Not applicable Decomposition temperature : No data available : No data available Viscosity, kinematic Viscosity, dynamic : No data available **Explosion limits** : Not applicable

9.2. Other information

Explosive properties

Oxidizing properties

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

11/15/2021 EN (English US) 4/8

No data available

: No data available

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

metals.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Titanium dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg body weight (OECD 425: Acute Oral Toxicity: Up-and-Down Procedure, Rat, Female, Experimental value, Oral, 14 day(s))
LC50 Inhalation - Rat	> 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))

Silicon carbide (409-21-2)		
	LD50 oral rat	> 2000 mg/kg body weight (OECD 423: Acute Oral Toxicity – Acute Toxic Class Method, Rat, Female, Experimental value, Oral)
	LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal)
	Skin corrosion/irritation	Not classified

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : May cause cancer.

Titanium dioxide (13463-67-7)		
IARC group	2B - Possibly carcinogenic to humans	
Crystalline silica (14808-60-7)		
IARC group	1 - Carcinogenic to humans	
Silicon carbide (409-21-2)		
IARC group	2A - Probably carcinogenic to humans	

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Crystalline silica (14808-60-7)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified
Viscosity, kinematic : No data available

SECTION 12: Ecological information

12.1	Tow	alte.
12.1	Tox	ICILY

Ecology - general	:	The product is not considered harmful to aquatic organisms or to cause long-term adverse
		effects in the environment

Titanium dioxide (13463-67-7)	
LC50 fish 1	> 100 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)

11/15/2021 EN (English US) 5/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Titanium dioxide (13463-67-7)	
ErC50 (algae)	61 mg/l (EPA 600/9-78-018, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

12.2. Persistence and degradability

Titanium dioxide (13463-67-7)		
Persistence and degradability	Biodegradability: not applicable.	
Chemical oxygen demand (COD)	Not applicable (inorganic)	
ThOD	Not applicable (inorganic)	
Crystalline silica (14808-60-7)		
Persistence and degradability	Biodegradability: not applicable.	
Chemical oxygen demand (COD)	Not applicable (inorganic)	
ThOD	Not applicable (inorganic)	
Silicon carbide (409-21-2)		
Persistence and degradability	Biodegradability: not applicable.	
Chemical oxygen demand (COD)	Not applicable	
ThOD	Not applicable	
BOD (% of ThOD)	Not applicable	

12.3. Bioaccumulative potential

Titanium dioxide (13463-67-7)		
Bioaccumulative potential	Not bioaccumulative.	
Crystalline silica (14808-60-7)		
Bioaccumulative potential	No bioaccumulation data available.	
Silicon carbide (409-21-2)		
Bioaccumulative potential	Bioaccumulation: not applicable.	

12.4. Mobility in soil

Titanium dioxide (13463-67-7)		
Ecology - soil	Low potential for mobility in soil.	
Crystalline silica (14808-60-7)		
Ecology - soil	No (test)data on mobility of the substance available.	

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not applicable

Transportation of Dangerous Goods

Not applicable

11/15/2021 EN (English US) 6/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport by sea

Not applicable

Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

Reno ElectroShot™ 370

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

Titanium dioxide (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List)

Crystalline silica (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

Silicon carbide (409-21-2)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

Titanium dioxide (13463-67-7)

Listed on IARC (International Agency for Research on Cancer)

Crystalline silica (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

Silicon carbide (409-21-2)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

Component	State or local regulations
Titanium dioxide(13463-67-7)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
Crystalline silica(14808-60-7)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
Silicon carbide(409-21-2)	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 11/15/2021

Full text of H-phrases:

H350	May cause cancer
H351	Suspected of causing cancer
H372	Causes damage to organs through prolonged or repeated exposure

SDS US (GHS HazCom 2012)

11/15/2021 EN (English US) 7/8

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information provided in the Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of it's publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release. Reno Refractories, Inc. makes no warranties, expressed or implied, with respect to such information, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose or course of performance or usage of trade. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

11/15/2021 EN (English US) 8/8