Safety Data Sheet



Section 1: Identification

Product identifier

Product Name · Reno ASAP 60 JC

Product Code • 146100

Relevant identified uses of the substance or mixture and uses advised against

Recommended use • Refractory applications

Details of the supplier of the safety data sheet

Manufacturer
 Reno Refractories, Inc.

P O Box 201 Morris, AL 35116 United States

www.renorefractories.com sales@renorefractories.com

Telephone (General) • 205-647-0240

Emergency telephone number

Manufacturer • 1-800-262-8200 - CHEMTREC

Section 2: Hazard Identification

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

Classification of the substance or mixture

OSHA HCS 2012 • Carcinogenicity 1A

Specific Target Organ Toxicity Repeated Exposure 1

Label elements
OSHA HCS 2012

DANGER



Hazard statements • May cause cancer.

Causes damage to organs - lungs through prolonged or repeated exposure

Precautionary statements

Prevention • Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

Response • IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Storage/Disposal • Dispose of content and/or container in accordance with local, regional, national, and/or

international regulations.

Other hazards

• Under United States Regulations (29 CFR 1910.1200 - Hazard Communication

Standard), this product is considered hazardous.

Canada

According to: WHMIS

Classification of the substance or mixture

WHMIS
 Other Toxic Effects - D2A

Label elements

WHMIS .

(T)

• Other Toxic Effects - D2A

Other hazards

WHMIS
 In Canada, the product mentioned above is considered hazardous under the

Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients

Substances

Material does not meet the criteria of a substance.

Mixtures

	Composition						
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments		
Alumina silicate	Proprietary	48.51% TO 51.59%	NDA	OSHA HCS 2012: STOT RE 2 (Lungs)	NDA		
Aluminum(III) silicate (2:1)	CAS:1302-76-7	15.3% TO 19%	NDA	OSHA HCS 2012: STOT RE2 (Lungs)	NDA		
Silica, amorphous	CAS:7631-86-9	< 16.71%	NDA	OSHA HCS 2012: Data Lacking	NDA		
Cement, alumina, chemicals	CAS :65997-16-2	7% TO 8%	NDA	OSHA HCS 2012: Skin Irrit. 2, Eye Irrit. 2A	NDA		
Amorphous silica fume	CAS :69012-64-2	6% TO 7%	NDA	OSHA HCS 2012: STOT RE 1 (Lungs)	NDA		
Quartz	CAS :14808-60-7	0.9% TO 2%	NDA	OSHA HCS 2012: Carc. 1A; STOT RE 1(Lungs)	NDA		
Aluminum oxide	CAS:1344-28-1	0% TO 1.3%	NDA	OSHA HCS 2012: Not Classified - Criteria not met	NDA		

Skin

Titanium dioxide	CAS :13463-67-	0.18% TO 1%	NDA	OSHA HCS 2012: Carc. 2	NDA	
Cristobalite	CAS :14464-46-1	0.189% TO 0.221%	NDA	OSHA HCS 2012: Carc. 1A	NDA	

Section 4: First-Aid Measures

Description of first aid measures

Inhalation

 Move victim to fresh air. Give artificial respiration if victim is not breathing. Administer oxygen if breathing is difficult. Get medical attention immediately.

In case of contact with substance, immediately flush skin with running water for at

least 20 minutes.

In case of contact with substance, immediately flush eyes with running water for at Eve

least 20 minutes. Get medical attention immediately.

Rinse mouth. Do not give anything by mouth to an unconscious person. Get medical Ingestion

attention immediately.

Most important symptoms and effects, both acute and delayed

Refer to Section 11 - Toxicological Information.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

All treatments should be based on observed signs and symptoms of distress in thepatient. Consideration should be given to the possibility that overexposure to materialsother than this product may have occurred.

Section 5: Fire-Fighting Measures

Extinguishing media

Suitable Extinguishing Media · Material is non-combustible. In case of fire use media as appropriate for surrounding

fire.

Unsuitable Extinguishing

Media

· None known.

Special hazards arising from the substance or mixture

Unusual Fire and Explosion

Hazards

· None known.

Hazardous Combustion Products

None known.

Advice for firefighters

 Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection. Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions

 Isolate hazard area and deny entry to unauthorized and/or unprotected personnel. Do not touch or walk through spilled material. Ensure adequate ventilation to remove vapors, fumes, dust etc.

Emergency Procedures

Ventilate closed spaces before entering. Isolate hazard area and deny entry to unauthorized and/or unprotected personnel.

Environmental precautions

No specific actions or treatments recommended related to exposure to this material.

Methods and material for containment and cleaning up

Containment/Clean-up Measures

 Avoid generating dust.
 FOR SMALL SPILLS: Clean with a vacuum with a filtration system sufficient to remove and prevent recirculation of crystalline silica (a vacuum equipped with a high-efficiency particulate air (HEPA) filter is recommended).

FOR LARGE SPILLS: Use a fine spray or mist to control dust creation and carefully scoop or shovel into clean dry container for later reuse or disposal.

If, an appropriate vacuum is unavailabe, only wet-clean-up methods should be used (i.e. misting). Moisture should be added as necessary to reduce exposure to airborne respirable silica dust.

Section 7 - Handling and Storage

Precautions for safe handling

Handling

 Do not breathe dust. Avoid contact with skin, eyes, and clothing. Minimize dust generation and accumulation. Use good safety and industrial hygiene practices. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Wear long sleeves and/or protective coveralls. Contaminated clothing must be vacuumed before removal. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Wash thoroughly after handling. Do not use in areas without adequate ventilation.

Conditions for safe storage, including any incompatibilities

Storage

 Store in a covered location. Keep from freezing. Storage and work area should be periodically cleaned to minimize dust accumulation.

Section 8 - Exposure Controls/Personal Protection

Control parameters

	Exposure Limits/Guidelines							
	Result	ACGIH	Canada Ontario	Canada Quebec	Mexico	NIOSH		
Reno ASAP 60 JC	TWAs	10 mg/m3 TWA (inhalable particles, recommended); 3 mg/m3 TWA (respirable particles, recommended) as Particulates not otherwise classified (PNOC)	10 mg/m3 TWA (inhalable particulate); 3 mg/m3 TWA (respirable particulate) as Particulates not otherwise classified (PNOC)	10 mg/m3 TWAEV (including dust, inert or nuisance particulates; containing no Asbestos and <1% Crystalline silica, total dust) as Particulates not otherwise classified (PNOC)	Not established	Not established		
Aluminum oxide (1344-28-1)	TWAs	1 mg/m3 TWA (respirable fraction) as Aluminum insoluble compounds	1 mg/m3 TWA (respirable) as Aluminum insoluble compounds	10 mg/m3 TWAEV (containing no Asbestos and <1% Crystalline silica, total dust, as AI)	10 mg/m3 TWA LMPE -PPT	Not established		
	STELs	Not established	Not established	Not established	20 mg/m3 STEL [LMPE-CT] (as Ti)	Not established		
Titanium dioxide				10 mg/m3 TWAEV				

(13463-67-7)	TWAs	10 mg/m3 TWA	10 n dust	ng/m3 TWA (total :)	Àsb	ntaining no pestos and <1% stalline silica, total t)	10 mg/m3 TWA LMPE -PPT (as Ti)	Not established
Cristobalite (14464-46-1)	TWAs	0.025 mg/m3 TWA (respirable fraction)	(des	5 mg/m3 TWA signated 0.05 mg/m3 TWAEV ostance regulation, pirable) (respirable dust)		0.05 mg/m3 TWA LMPE-PPT (respirable fraction)	0.05 mg/m3 TWA (respirable dust)	
Quartz (14808-60-7)	TWAs	0.025 mg/m3 TWA (respirable fraction)	(des	stance regulation (respirable dust)		0.1 mg/m3 TWA LMPE-PPT (respirable fraction)	0.05 mg/m3 TWA (respirable dust)	
Amorphous silica fume (69012-64-2)	TWAs	Not established		g/m3 TWA pirable)	2 mg/m3 TWAEV (containing no Asbestos and <1% Crystalline silica, respirable dust)		2 mg/m3 TWA LMPE- PPT; 10 mg/m3 TWA LMPE-PPT (inhalable particulate); 3 mg/m3 TWA LMPE-PPT (respirable particulate)	Not established
Silica, amorphous (7631-86-9)	TWAs	Not established	Not	established	Not	established	Not established	6 mg/m3 TWA
		Ex	cpos	ure Limits/Gu	idel	ines (Con't.)		
				Result			OSHA	
				T) 4 / 4		15 mg/m3 TWA (to	otal dust); 5 mg/m3 TW	A (respirable fraction)
Reno ASAP 60 JC		TWAs		as Particulates not otherwise classified (PNOC)				
Aluminum oxide (1344-28-1)			TWAs		15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction		A (respirable fraction)	
Titanium dioxide (13463-67-7)				TWAs		15 mg/m3 TWA (to	otal dust)	

Exposure controls

Engineering Measures/Controls

• Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Ensure that dust handling systems (such as exhaust ducts, dust collectors, vessels and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is not leakage from the equipment). Collection systems must be designed and maintained to prevent the accumalation and recirculation of respirable silica into the workplace.

Personal Protective Equipment

Respiratory

For limited exposure use an N95 dust mask. For prolonged exposure use an airpurifying respirator with high efficiency particulate air (HEPA) filters. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face

Wear protective eyewear (goggles, face shield, or safety glasses).

Hands

· Wear appropriate gloves.

Skin/Body

Wear long sleeves and/or protective coveralls.

General Industrial Hygiene Considerations

Avoid breathing dust. Avoid contact with skin, eyes or clothing. Do not remove dusts from clothing by blowing or shaking. Do not eat, drink or smoke during work. Wash hands before eating, drinking, or smoking. Wash thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice.

Environmental Exposure Controls

Follow best practice for site management and disposal of waste. Dispose of in an approved landfill.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial

STEL = Short Term Exposure Limits are based on 15-minute exposures

'' Hygiene

NIOSH = National Institute of Occupational Safety and Health

TWAEV = Time-Weighted Average Exposure Value

OSHA = Occupational Safety and Health Administration

= Time-Weighted Averages are based on 8h/day, 40h/week

exposures

Section 9 - Physical and Chemical Properties

Information on Physical and Chemical Properties

Material Description			
Physical Form	Solid	Appearance/Description	Gray granular dry powder with an earthy odor.
Color	Gray	Odor	Earthy
Particulate Size	600 µ	Odor Threshold	No data available
General Properties			
Boiling Point	No data available	Melting Point/Freezing Point	3200 °F(1760 °C)
Decomposition Temperature	No data available	рН	No data available
Specific Gravity/Relative Density	= 2.53 Water=1	Water Solubility	Negligible < 0.1 %
Viscosity	No data available		
Volatility		-	-
Vapor Pressure	No data available	Vapor Density	No data available
Evaporation Rate	No data available	VOC (Wt.)	0 %
Flammability		-	-
Flash Point	No data available	UEL	No data available
LEL	No data available	Autoignition	No data available
Flammability (solid, gas)	Not flammable.		
Environmental			
Octanol/Water Partition coefficient	No data available		

TWA

Section 10: Stability and Reactivity

Reactivity

No dangerous reaction known under conditions of normal use.

Chemical stability

Stable under normal temperatures and pressures.

Possibility of hazardous reactions

Hazardous polymerization not indicated.

Conditions to avoid

· None known.

Incompatible materials

None known.

Hazardous decomposition products

· None known.

Section 11 - Toxicological Information

Information on toxicological effects

	Components				
Silica, amorphous (< 16.71%)	7631-86- 9	Irritation: Eye-Rabbit • 25 mg 24 Hour(s) • Mild irritation			
Titanium dioxide (0.18% TO 1%)	13463- 67-7	Irritation: Skin-Human • 300 μg 3 Day(s)-Intermittent • Mild irritation; Tumorigen / Carcinogen: Inhalation-Rat TCLo • 250 mg/m³ 6 Hour(s) 2 Year(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration:Tumors			

GHS Properties	Classification
Acute toxicity	OSHA HCS 2012 • No data available
Skin corrosion/Irritation	OSHA HCS 2012 • No data available
Serious eye damage/Irritation	OSHA HCS 2012 • No data available
Skin sensitization	OSHA HCS 2012 • No data available
Respiratory sensitization	OSHA HCS 2012 • No data available
Aspiration Hazard	OSHA HCS 2012 • No data available
Carcinogenicity	OSHA HCS 2012 • Carcinogenicity 1A
Germ Cell Mutagenicity	OSHA HCS 2012 • No data available
Toxicity for Reproduction	OSHA HCS 2012 • No data available
STOT-SE	OSHA HCS 2012 • No data available
STOT-RE	OSHA HCS 2012 • Specific Target Organ Toxicity Repeated Exposure 1

Target Organs

Medical Conditions Aggravated by Exposure Potential Health Effects Inhalation

Lungs

· Any pre-existing conditions of the lungs. Disorders of the lungs.

Acute (Immediate)

Chronic (Delayed)

Exposure to dust may cause irritation.

Chronic overexposure to dust containing respirable sized crystalline silica can cause delayed lung injury (silicosis). Inhalation of dust containing crystalline silica pulmonary diseases such as asthma and lung disorder associated with smoking. IARC studies have shown sufficient evidence from animal studies to categorize crystalline silica as a group 1 carcinogen.

Skin

Acute (Immediate)

Exposure to dust may cause irritation.

Chronic (Delayed) No data available.

Eye

Acute (Immediate)

Excessive concentrations of nuisance dust in the workplace may reduce visibility and may cause unpleasant deposits in eyes.

Chronic (Delayed)

No data available.

Ingestion

Acute (Immediate)

Excessive concentrations of nuisance dust in the workplace may cause mechanical irritation to mucous membranes.

Chronic (Delayed)

No data available.

Carcinogenic Effects

· May cause cancer.

Carcinogenic Effects					
CAS IARC NTP					
Titanium dioxide	13463-67-7	Group 2B-Possible Carcinogen	Not Listed		
Cristobalite	14464-46-1	Group 1-Carcinogenic	Not Listed		
Quartz	14808-60-7	Group 1-Carcinogenic	Known Human Carcinogen		

Key to abbreviations

MLD = Mild

TC = Toxic Concentration

Section 12 - Ecological Information

Toxicity

Material data lacking.

Persistence and degradability

Material data lacking.

Bioaccumulative potential

· Material data lacking.

Mobility in Soil

Material data lacking.

Other adverse effects

No studies have been found.

Section 13 - Disposal Considerations

Waste treatment methods

Product waste

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	UN number	UN proper shipping name	Transport hazard class (es)	Packing group	Environmental hazards
DOT	NDA	Not regulated	NDA	NDA	NDA
TDG	NDA	Not regulated	NDA	NDA	NDA
IATA/ICAO	NDA	Not regulated	NDA	NDA	NDA

Special precautions for user • None known.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant.

Preparation Date: 01/June/2009

Format: GHS Language: English (US) OSHA HCS 2012, WHMIS Revision Date: 27/April/2018 Page 8 of 11

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture SARA Hazard Classifications • Chronic

State Right To Know					
Component	CAS	MA	NJ	PA	
Aluminum oxide	1344-28-1	Yes	Yes	Yes	
Cristobalite	14464-46-1	Yes	Yes	Yes	
Quartz	14808-60-7	Yes	Yes	Yes	
Silica, amorphous	7631-86-9	Yes	Yes	Yes	
Titanium dioxide	13463-67-7	Yes	Yes	Yes	

	Inventory					
Component	CAS	Canada DSL	TSCA			
Aluminum oxide	1344-28-1	Yes	Yes			
Cristobalite	14464-46-1	Yes	Yes			
Quartz	14808-60-7	Yes	Yes			
Silica, amorphous	7631-86-9	Yes	Yes			
Titanium dioxide	13463-67-7	Yes	Yes			

Canada

Labor		
Canada - WHMIS - Classifications of Substances		
Titanium dioxide	13463-67-7	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Titanium dioxide, mixture containing on Health Canada's WHMIS Division website.)
Aluminum oxide	1344-28-1	Uncontrolled product according to WHMIS classification criteria
 Aluminum oxide as Aluminum insoluble compounds Cristobalite 	14464-46-1	Not Listed D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS Division website.)
Silica, amorphous	7631-86-9	Uncontrolled product according to WHMIS classification criteria D2A (In certain cases, this
• Quartz	14808-60-7	classification does not apply. For more information, consult the section Substance Specific Issues - Silica, crystalline, encapsulated on Health

		Canada's WHMIS Division website.)
Canada - WHMIS - Ingredient Disclosure List		
Titanium dioxide	13463-67-7	Not Listed
Aluminum oxide	1344-28-1	1 %
Aluminum oxide as Aluminum insoluble compounds		Not Listed
Cristobalite	14464-46-1	1 %
Silica, amorphous	7631-86-9	1 %
• Quartz	14808-60-7	1 %

United States

Environment U.S CERCLA/SARA - Section 313 - Emission Reporting		
Titanium dioxide	13463-67-7	Not Listed
Aluminum oxide	1344-28-1	1.0 % de minimis concentration (fibrous forms)
Aluminum oxide as Aluminum insoluble compounds		Not Listed
Cristobalite	14464-46-1	Not Listed
Silica, amorphous	7631-86-9	Not Listed
• Quartz	14808-60-7	Not Listed

United States - California

Environment U.S California - Proposition 65 - Carcinogens List		
		carcinogen, initial date 9/2/11
Titanium dioxide	13463-67-7	(airborne, unbound particles of respirable size)
Aluminum oxide	1344-28-1	Not Listed
Aluminum oxide as Aluminum insoluble compounds		Not Listed
Cristobalite	14464-46-1	Not Listed
Silica, amorphous	7631-86-9	Not Listed
		carcinogen, initial date 10/1/88
• Quartz	14808-60-7	(airborne particles of respirable size)

United States - Pennsylvania

Labor		
U.S Pennsylvania - RTK (Right to Know) - Environmental Hazard List		
Titanium dioxide	13463-67-7	Not Listed
Aluminum oxide	1344-28-1	
Aluminum oxide as Aluminum insoluble compounds		Not Listed
Cristobalite	14464-46-1	Not Listed
Silica, amorphous	7631-86-9	Not Listed
• Quartz	14808-60-7	Not Listed

United States - Rhode Island

Labor U.S Rhode Island - Hazardous Substance List		
Titanium dioxide	13463-67-7	Toxic
Aluminum oxide	1344-28-1	Toxic
Aluminum oxide as Aluminum insoluble compounds		Not Listed
Cristobalite	14464-46-1	Not Listed

• Silica, amorphous 7631-86-9 Not Listed

Quartz
 14808-60-7 Toxic (dust and fiber)

Other Information

 WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information

Revision Date

Last Revision Date

Preparation Date

Disclaimer/Statement of Liability

- 27/April/2018
- 21/October/2013
- 01/June/2009
- The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. Reno Refractories MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, WITH RESPECT TO SUCH INFORMATION, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key to abbreviationsNDA = No data available